

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

John M. Powell
W. Penley & J. Heritage
September, 1971
C.S. File 54/59

Section Corner to Sections 12 and 13 only. **128**
Found - GLO Brass Cap at Section Corner properly marked. - SEE ALSO REN.#100
12" D. Fir, now 20", S. 8 1/2° W., 186.1 ft. opened for scribe "3".
12" Ash, now rotted, N. 24° W., 114.8 ft. shows old axe work N. 24 1/2° W.
New BT's: 11" D. Fir, S. 43° W., 32.7 ft. scribed T30S RLW S13 CS BT.
10" D. Fir, N. 64° W., 36.0 ft. scribed T30S RLW S12 CS BT.
Note: This Brass Cap lies under 36" log.

9/24/71

1/4 Corner to Section 13 only. **129**
Found - 1923 GLO Brass Cap at 1/4 corner properly marked.
40" D. Fir, now 49", N. 49° W., 19.1 ft. Shows good scar.
24" D. Fir, now stump, S. 66° W., 41.6 ft. Found some fragments of
scribing.
New BT's: 22" D. Fir, S. 35 1/2° W., 21.8 ft. Scribed 1/4 S13 CS BT. SEE REN.# 98 &
Gov't PLAT.
Note: This cor. now lies about 75.0 ft. north of old cutting cor.
Also approx. 200 ft. east to draw.

9/23/71

Section Corner to sections 13 and 24 only. - SEE GOV'T. PLAT FOR DIST. **130**
Found - 1923 GLO Brass Cap at section corner properly marked. BTWN. CORNERS.
16" D. Fir, now burnt stob, S. 1° W., 23.1 ft. Scribe visible
T30S RLW S24.
38" D. Fir, now stump, N. 6° W., 40.9 ft.
New BT's: 8" Hemlock, N. 8° E., 25.6 ft. Scribed T30S RLW S13 CS BT.
36" D. Fir, S 77° W., 15.4 ft. Scribed T30S RLW S24 CS BT.
Note: This corner lies on east slope approx. 90.0 ft. west of draw.

9/23/71

1/4 Corner Sections 7 and 18. **131**
Found - 3" x 5" x 14" Stone mkd. 1/4 S. Refer to affidavits C.S. 55/299.
Orig. BT's not found.
New BT's - 6" Oak, N. 2° E., 21.6 ft. scribed "1/4 S7 BT."
4" Oak, S. 46° W., 9.0 ft. scribed "1/4 S18 BT."
FD OK, Dec '94, M121-45 May, 1973

Sec. Corner, Secs. 5 & 6, T.30-1; Secs. 31 & 32, T29-1. **132**
Found - Brass cap mkd. T29S, RLW, S31, T30s, RLW. S6, S5,
RLS 222 1970. Ren.#125
15" x 12" x 6" orig. stone & 1 1/4 x 27" iron bolt #219
alongside brass cap.
30" orig. madrone, blown down - bears N. 88° E., 32.9 ft.
22" orig. white fir, blown down, bears S. 38° E., 32.9 ft.
24" orig. D. Fir, stump, bears N. 61° W., 25.1 ft.
12" white fir, scribes visible, bears S. 11° W., 18.9 ft.
10" black oak, scribes vis. bears N. 85° W., 9.6 ft.
New BT - 6" D. Fir, scribed T29S, RLW, S32 BT, bears N. 12 1/2° E.
45.8 ft. and nailed a brass washer to lower face.

1/4 Cor. For Secs 4 and Sec. 33 of T29-1. **133**
Set - 2" x 30" I. Pipe with brass cap properly mkd. and
with PLS 483 stamp.
New BT's - 18" Incense cedar, N. 6 1/2° E., 64.4 ft. mkd. "1/4
S33 BT.
11.2" P.Pine S. 2 1/4° W., 32.9 ft. Mkd. "1/4 S4 BT".

Center 1/4 Cor. of Sec. 5 **134**
Set - 2" pipe with 3" Brass disk top stamped T30S RLW C 1/4 S 5
PLS 961 1976.
From which: A 8" Cedar bears N. 64° 06' E., 18.2 ft. scribed C 1/4
S 5 BT,
A 9" Cedar bears S. 63° 24' W., 62.8 ft. scribed C 1/4
S 5 BT.

Eugene Bloom
Baughman Surveying
M 48 - 66
C.S. 55/299
May, 1973

Bruce A. Shaner
for Umpqua Nat'l
Forest
M 49 - 43
10/23/73

Charles Hurst
For: U.S. Forest
Service
Oct. 20, 1975
M 58 - 38

Larry J. Friar
For: Umpqua Nat'l
Forest
Oct. 1975
M 58 - 42

RE-REVIEWED SEE CORNER NO. #170

RE-REVIEWED SEE CORNER NO. #219

JAN 1972

JAN '75