

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

135

Center 1/4 Section 6
Set - 2" pipe with 3" Brass disk top stamped: T30S R1W C1/4 S6,
PLS 961 1975

From which:

A 8" Fir, bears S.04°02'E., 32.5 ft. scribed C1/4 S6 BT
A 8" Fir, bears S.84°25'W., 23.9 ft. scribed C 1/4 S6 BT.

Larry J. Friar
For: Umpqua Nat'l For
Tiller Land Survey
Nov. 18
Nov. 1975
M 58 - 56

136

1/4 Corner for Sections 6 and 7.

Found - Remains of stake in ground under rock mound.

Set - 2" Pipe with 3" Brass disk top stamped: T30S R1W 1/4 S6 S7
PLS 961 1975

From which:

A 7" Fir, bears S.27°40'W., 32.2 ft. scribed 1/4 S7 BT.
A 6" Pine, bears N.36°16'W., 34.9 ft. scribed 1/4 S 6 BT.

137

Center 1/4 Corner of Sec. 7

Set - 2" Pipe with 2 1/2" brass disk top stamped: T30S R1W C 1/4 S 7
PLS 961 1975

From which:

A 10" Cedar bears S.01°16'E., 75.3 ft. scribed C 1/4 S7 BT.
A 7" Oak, bears N.78°W., 32.4 ft. scribed C1/4 S7 BT.

Larry J. Friar
For: Umpqua Nat'l For.
November, 1975
M 58 - 66

11/75

1/4 Corner Sec. 7 and 18

REN.#131

Found- A 3" Brass cap, cemented into a drill hole in a 2' x4'x4' Boulder
stamped: T 30 S R1W

PLS 961 1975 1/4 S 7
S18

and lying nearby a 3" x 5" x 14" stone marked "1/4 S" and a 3" x 5" x5"
stone marked F5M

From which Bloom's trees bear as follows:

6" W Oak scribed "1/4 S 7 BT" Bears N2°E., 21.6 ft.

4" W Oak Scribed "1/4 S18 BT" Bears S46°W., 9.0 ft.

138

Section corner to sec.12 & 13 T30-2 & 7 & 18 T30-1 REN.#35 T 30-2

Found-A stone, firmly set 18"x10"x5" mkd with 4 notches on the south side,
and at least 1 notch on the north. Markham's 1958 3/4 x 24" I.pipe is set
alongside the stone, from which two remaining orig. BT's are located

Orig. 15" now 22" D. fir alive and well-healed bears S44°W., 23.8 ft.,
(Rec. S48°W., 23.8 ft.)

Orig. 6" now 17" D fir, alive and well-healed, bears N34°W., 20.5 ft., (Rec. N30°
W., 20.5 ft.)

15" now 35" sugar pine marked during a subsequent Gov. resurvey, alive and in
good condition, bears N 18°E., 25.7 ft. BT's mkd. by Markham in 1958 are

a 5" now 7" chinquapin, alive, scribing visible on rotting face bears S88°W.,
17.0ft. (Rec. N87°W., 17.0 ft.)

A 5" now 6" chinquapin, in poor condition, scribe visible bears N 72°W., 25.8ft.
(Rec. N 69°W., 25.8 ft.)

At the corner point, we set a 1" x 30" I.Pipe, 26" in the ground, with brass
cap attached, Marked T 30 S

DOUGLAS CO. SURVEYOR
1975

R	S12	S 7	R
2	S13	S18	1
W			W

Gary L Langlitz
Clell E Goodwin
A. Vic. Cangie
M. Lenora Ladig
CS 57/39
12/18/75

We place the corner some on the east and Markham's pipe on the west side of the
Brass cap, and mark the following BT

A 5" D. fir, scribed "NW S18 CSBT" on a double blaze bears S 68°E., 32.3 ft.

Compass declination setting: 20° East 12/18/75

FD OK, Dec. '94, M121-45

139

1/4 Corner for Sections 18 and 19

Set - 2" Pipe with 3" Brass disk top properly stamped

From which:

A 8" Fir, bears N.26°08'E., 16.4 ft. scribed 1/4 S18 BT.

A 8" Chinquapin, bears S.65°28'W., 39.2 ft. scribed 1/4 S19 BT.

Larry Friar
For: Umpqua Nat'l
Forest

140

Section corner for Secs. 18, 17, 19 and 20

Set - 2" pipe with 3" brass disk top properly stamped

From which:

A 14" Fir, bears N.78°05'E., 47.1 ft. scribed T30S R1W S17 BT.

A 24" Pine bears S.21°31'E., 97.0 ft. scribed T30S R1W S19 BT.

A 10" Fir, bears S.44°42'W., 97.1 ft. scribed T30S R1W S19 BT.

A 10" Madrone, bears N.26°37'W., 28.8 ft. scribed T30S R1W S18 BT.

Feb. 1976
M 56 - 37