

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

141

1/4 Corner for Secs. 17 and 20
Set - 2" Pipe with 3" Brass disk top properly stamped.
From which:
A 10" Fir, bears S.82°00' E., 31.3 ft. scribed 1/4 S20 BT.
A 12" Fir, bears S.03°39'E., 38.7 ft. scribed 1/4 S20 BT.

142

Section Corner for Secs. 17, 16, 20 and 21
Set - 2" pipe with 3" Brass disk top properly stamped
From which:
A 20" Fir, bears N.69°45'W., 44.6 ft. scribed T30S R1W S17 BT.
A 36" Twin cedar, bears N.72°30'E., 33.9 ft. scribed T30S R1W S16 BT.
A 36" Cedar, bears S.22°30'E., 29.6 ft. scribed T30S R1W S21 BT.
A 20" Fir, bears S.65°30'W., 67.3 ft. scribed T30S R1W S20 BT.

143

1/4 Corner for Sections 16 and 21
Set - 2" pipe with 3" brass disk top properly stamped
From which:
A 18" Fir, bears S.35°30'E., 61.6 ft. scribed 1/4 S21 BT
A 16" Fir, bears S.39°W., 51.5 ft. scribed 1/4 S21 BT.

144

1/4 Corner for Sections 19 and 20
Set - 2" pipe with 3" brass disk top properly stamped
From which:
A 12" Fir, bears S.88°35'E., 33.5 ft. scribed 1/4 S20 BT.
A 8" Fir, bears N.53°55'W., 13.5 ft. scribed 1/4 S19 BT.

145

Center 1/4 Cor. for Sec. 20
Set - 2" pipe with 3" brass disk top properly stamped
From which:
A 12" Fir, bears N.14°39'W., 17.3 ft. scribed C 1/4 S20 BT.
A 8" Fir, bears N.79°12'E., 6.0 ft. scribed C 1/4 S20 BT.

146

1/4 Corner for Sections 20 and 21.
Set - 2" pipe with 3" brass disk top properly stamped
From which:
A 8" Fir, bears S.72°30'W., 43.5 ft. scribed 1/4 S20 BT.
A 8" Fir, bears S.57°45'E., 27.8 ft. scribed 1/4 S21 BT.

147

1/4 Corner for Sections 20 and 29
Set - 2" pipe with 3" brass disk top properly stamped
From which:
A 9" Hemlock, bears N.41°W., 47.3 ft. scribed 1/4 S20 BT.
A 12" Fir, bears S.39°E., 38.7 ft. scribed 1/4 S29 BT.

2/76

148

1/4 Corner for Secs. 18 and 17
Found - A 24" Fir stump, Orig. BT, bears N.85°E., 12.54 ft.,
opened for scribe.
Set - 2" Pipe with 3" brass disk top properly stamped
From which:
A 10" Fir, bears N.33°00'W., 46.7 ft. scribed 1/4 S18 BT.
A 12" Fir, bears S.75°30'E., 40.3 ft. scribed 1/4 S17 BT

FD OK, Dec. '94, M121-45

2/76

149

Section Corner for Secs. 11, 12, 13 and 14.
Found - 1923 GLO brass cap properly stamped.
Mound of stone approx. 3 ft. across the base and 1 1/2 feet high,
bears West approx. 3 feet.
New BT's-18" Pine, bears S.15°W., 23.2 ft. Tree double blazed & scribed
"T30S R1W S14 CS BT".
20" D. Fir, bears N.79°W., 21.4 ft. Tree double blazed & scribed
"T30S R1W S11 CS BT"
A 12" D. Fir, bears N.40°E., 20.2 ft. Tree double blazed and scribed
"T30S R1W S12 CS BT"
A 18" D. Fir, bears S.47°E., 47.2 ft. Tree double blazed & scribed
"T30S R1W S13 CS BT"

Larry J. Friar
For: Umpqua National Forest
February, 1976
M 56 - 37

L.E. Monrean
P. L. Earle
K. Cheney
Doug. Co. Surveyors
Aug. 16, 1976
C.S. 59/18