

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 30 T. S. R 1 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

154

Dennis Gaylor, U.S.F.S.
Deputy, Doug. Co.
Surveyors Office
Walt Barton, Witness
April 7, 1977
C.S. 59/31

Corner #2 of H.E.S. #195.
Found - No monument found. Corner location falls in center of a skid trail. Original corner monument destroyed.
A Broken & decayed 13" Fir stob bears S.10°30'W., 58.08 ft. Scribing visible "X2 HES 195 BT".
A 30" Fir stump bears S.35°W., (Rec. S.25°W.) 64.02 ft. Open and find scribing "95 BT".
Set - At the intersection of record distances from the two orig. BT's:
A 2 1/2" brass cap flush with the ground mkd: County Surveyors Office T30S R1W Cor. 2 | HES 195 1977. Placed a 2' x 2' mound of stone around the downhill (south) side of the pipe.
New BT's- A 26" D. Fir bears S.26°E., 22.2 ft. scribed "X2 HES 195 CS BT" on a double blaze.
A 16" D. Fir bears S.11°W., 20.9 ft. scribed "X2 HES 195 CS BT" on a double blaze. Placed county BT tags on both trees.
Note - Corner lies 75 ft. north of old road, used for former logging access. (16°E declination, Rock in area).

4/7/77

155

Closing Corner for Secs. 9 and 10 only, North.
Found - 2 1/2" Brass cap on a 1" I.P. Cap stamped County Surveyors Office T30S R1W S3 C.C. 1969. Cap is 19" above ground. Ren. #120
S9 S10

The orig. corner stone, marked with 4 grooves on one side is lying alongside the iron pipe.
Orig. 12" D. Fir bears S.41°W., 36.3 ft. is down. Scribing is visible on previously opened blaze.
A 12" Cedar, Orig. 10", bears S.67°W., 49.5 ft. scribing visible on a single blaze, "T30S R1W S9 CC CS BT"
A 19" D. Fir stump (orig. 18") bears S.62°E., 38.3 ft. scribing visible on a single blaze. "T30S R1W S10 CC CS BT".
New BT - A 10" Yew bears S.17°30'E., 95.1 ft. scribed "T30S R1W S10 CC CS BT" on a double blaze.
Corner lies 500 ft south of F.S Road No. 2929.

10/20/77

156

Section corner for Secs. 4 and 3 only. South
Found - A 14" now 18" D. Fir stump bears N.41°E., 42.9 ft. Stump is nearly covered by dirt. After considerable digging, I open a small portion of the healed blaze and find scribing & reverse scribing.
The BT's to the NW, SW and the SE are all gone. (extensive logging in the vicinity).

Set - 1 1/2" Galv. I.P. with 2 1/2" brass cap stamped County Surveyors Office T 30 S R 1 W 1977

S 4 | S 3
only

I place a stone mound around the pipe 2 ft. x 2 ft. x 1 ft. high. Set by reference to only remaining orig. bearing tree.
New BT's- A 6" Grand Fir bears N.64°E., 12.9 ft. scribed "T30S R1W S 3 CS BT" on a double blaze.
A 6" Grand Fir bears N.67°30'W., 25.0 ft. scribed "T30S R1W S4 CS BT" on a double blaze. Placed County BT signs on both trees.
Corner lies 500 ft. south of F.S. Road No. 2929. The corner for Secs. 9 and 10 only bears N.87°E., 167.2 ft. (Rec. East, 165.0 ft.)

10/20/77

157

1/4 Corner for Secs. 16 and 15.
Found - 26" x 16" x 10" stone set solidly in place. No marks visible. Stone is 5" out of ground.
A 31" Pine stump, orig. 10", bears N.75 1/2°E., 94.8 ft. (Rec. 94.38 ft.) scribing visible "S 1/4 S" Ren. #2
A 15" Ponderosa Pine orig. 8", bears S.57°W., 94.1 ft. scribing visible on previously opened blaze, "S 1/4 (Rec. dist. is 95.04'")
Set - Moving the stone aside, I SET in its place a 2 1/2" brass cap on a 1 1/2" Galv. I.P. I buried the corner stone alongside. Brass cap stamped: County Surveyor's Office T30S R1W 1/4 S16 S15 1977
New BT's- A 10" D. Fir bears S.39°E., 50.7 ft. scribed "1/4 S15 CS BT" on a double blaze.
A 11" Oak bears S.55°W., 67.3 ft. scribed "1/4 S16 CS BT" on a double blaze. I placed county BT signs on all 3 living BT's.

Dennis Gaylor, U.S.F.S.
Deputy, Doug. Co. Surveyors Office
Roland Simshauser
Oct. 1977
C.S. 59/40

Dennis Gaylor USFS
Deputy, Doug. Co.
Surveyors Office
Roland Simshauser
Nov. 10, 1977
C.S. 59/42