

Douglas County Surveyor's Record of
Government Corners Renewed

T 30

T. S.

R 1

R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

William Ruppert
For: U.S. Forest
Service
Sept. 1977
M 69 - 4

1/4 Corner for Secs. 27 and 34. **RE-RENEWED, SEE CORNER NO. #229** 162
Set - Brass cap stamped T30S R1W 1/4 S27 S34 RLS 866 1978
BT's- 10" D. Fir bears N.64°00'W., 80.7 ft. scribed "1/4 S27 BT"
9" W. Fir bears S.42°42'W., 128.4 ft. scribed "1/4 S34 BT."
Sept. 1977

Section Corner for Secs. 21, 22, 28 and 27. 163
Set by proportionate methods.
Set - 2" x 30" Gal. I.P. with brass cap stamped T30S R1W S21 S22 S28 S27
RLS 866 1978.
BT's- 12" D. Fir, N.30°08'E., 23.6 ft. "T30S R1W S22 BT".
14" D. Fir, S.85°16'E., 19.6 ft. "T30S R1W S27 BT".
18" D. Fir S.15°20'W., 38.7 ft. "T30S R1W S28 BT"
19" D. Fir N.51°28'W., 33.8 ft. "T30S R1W S21 BT".
1/78

Witness Corners for 164
1/4 Corner for Secs. 21 and 22=
Note - True point for 1/4 corner falls in Jackson Creek #222
Found - 19" D. Fir with good face bears N.70°W. 47.0 ft. from true corner.
See Renewals #'s 8 and 9.
Set - Brass caps stamped T30S R1W and T30S R1W
RM 1/4
1/4 S21 S 22 1/3" PER MAP. CORRECTION MADE J.H.
S.89°01'13"E 61.92 N.89°01'12"W 218.79
RLS 866 1978 LS 866

1/4 Corner for Secs. 22 and 27 165
Found - 8" Oak snag bears N.68°30'E., 21.8 ft. Ren. #12
8" Fir snag bears S.32°55'E., 24.5 ft. show good scar
8" Fir snag bears S.34°40'W., 21.5 ft. show good scar
15" Cedar N.77°W., 51.0 ft. visible scribe
10" W. Oak N.54°10'W., 47.0 ft. show good scar
1" steel shaft, 6" flange. **RE-RENEWED, SEE CORNER NO. #223**
Set - 2" x 30" Gal. I.P. with brass cap stamped T30S R1W S22 S27 1/4
PLS 866 1977

Center 1/4 Corner for Sec. 22 166
Set - 2" x 30" Gal. I.P. with brass cap stamped T30S R1W C 1/4 S22
RLS 866 1978.
BT's- 8" D. Fir bears N.48°24'E., 3.2 ft. "C 1/4 S22 BT."
13" D. Fir bears N.35°05'E., 29.3 ft. "C 1/4 S22 BT".

Section Corner for Secs. 22 23, 27 and 26. 167
Found - 1923 GLO brass cap
29" D. Fir S.34°19'E., 16.2 ft. good scar
35" D. Fir S.41°00'W., 27.6 ft. good scar
44" D. Fir N.38°34'W., 9.0 ft. good scar
15" D. Fir N.16°05'E., 29.5 ft. windfall no scribe found.
Scribed - 20" D. Fir bears N.27°07'E., 48.6 ft. "T30S R1W S23 BT".

1/4 Corner for Secs. 21 and 28. 168
Found - Approx. 18" D. Fir bark ring, N.80°51'W., 13.2 ft. wood decomposed.
Approx. 18" D. Fir bark ring, S.53°18'W., 13.2 ft. wood decomposed.
Set - Brass cap stamped T30S R1W 1/4 S21 S28 PLS 866 1978
BT's- 10" D. Fir, S.75°19'W., 13.2 ft. "1/4 S28 BT"
10" D. Fir N.26°09'E., 10.7 ft. "1/4 S21 BT"
Note - See also filed narrative in C.S. 58/156.
1/78

William Ruppert PLS 866
For: U.S. Forest Service
Jan. 1978
M 65 - 66 and C.S. 58/156

O V E R