

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 30      T. S.      R 1      R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

William Ruppert  
LS #866  
For: U.S. Forest  
Service  
January, 1978  
M 65 - 80

175

1/4 Corner for Secs. 12 and 13.  
Found - 1923 US GLO brass cap properly marked.  
32" P. Pine, N.19°24'W., 87.4 ft. good scar  
10" D. Fir, N.10°10'E., 10.0 ft. vis. scar.  
37" P. Pine S.27°21'E., 103.5 ft. good scar.      Ren. #105  
15" D. Fir fallen, S.37°25'W., 10.8 ft. good scar.  
Scribed: 13" D. Fir, S.65°19'W., 58.6 ft. scribed "1/4 S13 BT".

176

1/4 Corner for Sections 15 and 14.  
Found - County renewed corner as proportioned by Cain Nov. 11, 1920  
1976 County brass cap bears N.01°25'W., 14.31 ft.      See Ren. #151  
30" windfall N.87°21'W., 14.11 ft. 1/4 1/2 1/4 P.  
60" rotten pine stump S.82°07'E., 108.0 ft. scribing visible.  
5" D. Fir, S.65°25'E., 14.3 ft. scribing visible.  
7" D. Fir N.37°24'W., 7.7 ft. scribing visible.  
Set - 2" x 30" Gal. I.P. with 2 1/2" brass cap stamped "T30S RLW 1/4  
S15 S14 RLS 866 1978.  
New BT's- 19" D. Fir, N.86°36'W., 28.6 ft. "1/4 S15 BT".  
10" Madrone, N.28°09'E., 17.0 ft. "1/4 S14 BT".

William Ruppert  
LS #866  
For: U.S. Forest  
Service  
January 1978  
M 70 - 1

177

Center 1/4 corner for Sec. 14  
Set - 2" x 30" Gal. I.P. with brass cap stamped "T30S RLW C 1/4 S14 RLS  
866 1978.  
BT's - 12" D. Fir, S.56°10'E., 44.3 ft. "C 1/4 S14 BT".  
14" D. Fir, S.06°10'E., 5.2 ft. "C 1/4 S14 BT".

178

Angle point, Govt. lot 1, Section 1; and Sec. 36 of T.29-1  
Found - Mound of rocks.  
Set - 2" x 30" Gal I.P. with brass cap stamped "AP T29S RLW S36  
RLS 866 1978"      L1  
T30S  
S1  
Scribed: 16" D. Fir, S.21°16'W., 20.2 ft. "A.P.T.30S RLW S1 BT".  
14" D. Fir, N.82°26'E., 13.2 ft. "A.P.T29S RLW S36 BT".  
14" D. Fir, S.34°38'E., 46.4 ft. "A.P.T.30S RLW S1 BT".

William Ruppert, LS #866  
For: U.S. National Forest  
January, 1978  
M 70 - 2

179

Corner for Lots 2 and 3, Sec. 1.  
Set - Brass cap by proportional measurement stamped "T30S RLW S1 | L2  
L3  
RLS 866  
1978

Scribed: 7" Hemlock, N.26°01'E., 30.3 ft. "L2 S1 BT"  
6" W. Fir, S.43°26'E., 40.8 ft. "L3 S1 BT".

180

Twp. Corner to Sec. 1, T30-1; Sec. 36, T29-1 & Sec. 31, T29-1E  
Found - 1" pipe with brass cap marked 1968 County Surveyors Office.  
54" Pine stump, S.01°07'E., 72.7 ft.      Ren. #70  
21" D. Fir windfall, S.15°53'E., 59.0 ft. probably moved.  
15" Incence Cedar, N.49°36'E., 70.2 ft. visible scribing.  
17" Madrone, N.55°43'W., 97.3 ft. visible scribing.  
New BT - 6" D. Fir, S.26°59'W., 60.3 ft. "T30S RLW S1, BT".

Glenn S. Baughman  
L.S. #536  
For: U.S. Forest Serv.  
Filed May 23, 1978  
C.S. 58/153

181

Section corner for Secs. 18 & 19; and Secs. 13, 24 of T30-2  
Found - A 1" I.P. with 2 1/2" Brass cap 14" above ground.  
8" D. Fir stob bears S.9°E., 7.9 ft. (Rec. S.14°E.) scribes  
visible open blaze.      Ren. #86  
20" D. Fir bears S.53 1/2°E., 14.8 ft. bark scribes visible.  
18" D. Fir stump bears S.79°W., 19.4 ft. bark scribes visible.  
24" D. Fir bears N.56°E., 20.0 ft. bark scribes visible.  
24" D. Fir bears N.62°W., 48.2 ft. bark scribes visible.  
6" x 8" x 5" high stone buried alongside 1" I.P.  
New BT - A 10" Madrone bears S.74°W., 18.0 ft. scribed "T30S R2W S24 BT"  
on double blazed face.

Corner lies at the foot of a very steep north slope & 50 ft. south of dirt  
road built recently. Cor. has been run over by Cat. during logging & I.P. is  
badly bent.      PD OK, Dec. '94, M121-45