

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 S T. S. R 1 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

191

David K. Bateman
R.L.S. #1068
For: U.S. Forest
Service
Aug. 31, 1978
M 73 - 24

1/4 Corner for Secs. 2 and 11
Found - 12" D. Fir, N.49°E., 16.4 ft. with visible scribing.
12" D. Fir, S.15°W., 17.0 ft. Ren. #113
1967 Alum. Cap R.E. 4287, S.03°38'00"E., 4.15 ft.
5" x 6" x 12" Stone, S.76°07'25"W., 37.80 ft. marked "X" on North
face and "1/4" on South face from which found: (Not of Record)
13" D. Fir, S.78°E., 15.5 ft. with healed face. Not of record.
14" D. Fir, N.35°E., 13.9 ft. with healed face, Not of record.
8/31/78

FD 1977
BT's 7/18/81
E. Geisler
C.S. 5/15/81
Cap out of ground

192

Larry D. Bishop
For: U. S. Forest
Service
M 73 - 43
Sept. 12, 1978

Center 1/4 Corner for Section 4.
Set - 3" Brass cap rivited to a 2" x 30" galv. steel pipe.
Brass cap mkd. T30S R1W C 1/4 S4 PLS 896 1978.
BT's - 12" D. Fir bears N.43°E., 22.3 ft. scribed C 1/4 S4 Upper blaze.
8" White Fir bears S.46°E., 3.7 ft. scribed C 1/4 S4. Upper blaze.
All bearing trees have a one inch brass disk stamped LS 896 nailed with a
steel finishing nail to the lower blaze which is also scribed "BT".
9/12/78

193

Larry Bishop
For: U.S. Nation-
al Forest
Sept. 27, 1978
M 74 - 18

Center 1/4 Corner for Section 8.
Set - 3" brass cap rivited to a 2" x 30" galv. steel pipe stamped
T30S R1W S8 C 1/4 1978 PLS 896.
BT's - 14" Yew, N.74°E., 17.75 ft. scribed C 1/4 S8 upper blaze.
12" I. Cedar, N.83°W., 31.6 ft. scribed C 1/4 S8 upper blaze.
All bearing trees marked during this survey have a 1 inch brass disk
stamped LS 896 nailed with a steel finishing nail to the lower blaze which
is also scribed "BT".
9/27/78

1-79

194

Glenn Baughman
For: U.S. Forest
Service
April, 1979
C.S. 58/176

1/4 Corner for Secs. 6 and 5.
Found - 1" Iron pipe with 1968 County brass cap. Ren. #31
11" now 14" White fir, S.89°E., 46.1 ft.
8" now 10" White fir, S.61°E., 32.6 ft.
Set - I marked a 6" Douglas Fir, S.32°W., 21.9 ft. "1/4 S6 BT" and
attached a brass washer stamped Land Surveyor 536 on lower face.
4/79

RE-RENEWED, SEE CORNER NO. #213

195

William Ruppert
LS #866
For: U. S. Forest
Service
April 1979
M 70 - 60

Section corner for SEcs. 7, 8, 17 and 18. Ren. #73
Found - 1" iron pipe with 2 1/2" brass cap, 1968 County Surveyors Office
20" D. Fir, N.18°30'E., 23.1 ft. good scar
19" D. Fir S.22°30'E., 21.6 ft. good scar
21" D. Fir, N.89°45'W., 14.9 ft. good scar.
21" D. Fir, S.4°30'W., 15.5 ft. good scar.
Scribed New BT:
9" D. Fir, S.74°00'E., 59.2 ft. "T30S R1W S17 BT"

196

Glenn Baughman
For: U.S. Forest
Service
July 1979
C.S. 58/176

Township corner for Sec. 6; and Sec. 1 of T30-2; Sec. 31 of T.29-1 and
Sec. 36 of T.29-2
Found - 1" Iron pipe, 10" above the ground with a 2 1/2" brass cap mkd.
"T29S R2W R1W S36 S31 S6 S1 T30S 1917"
From which:
A 22" Oak bears N.70°W., 37.0 ft.
An 18" Oak stob bears N.8°E., 47.5 ft.
An 18" Oak stump bears S.89°E., 118.8 ft.
An 18" D. Fir bears N.44°W., 26.8 ft.
A 16" D. Fir bears N.73°E., 17.5 ft.
An 18" D. fir bears S.9°E., 13.0 ft. Ren. #34
A 12" D. Fir bears S.41°W., 33.0 ft.
New BT - 10" D. Fir bears S.25°E., 38.4 ft., I marked "T30S R1W S6 BT" on a
double blaze and nailed a brass washer stamped "LS 536 into lower
blaze."
7/79

197

Section corner for Secs. 31 and 32; and Secs. 6 and 5 of T.31-1
Found - A 1" iron pipe projecting 16" above the ground with a 2 1/2" Brass
cap mkd. County Surveyors Office
From which:
A 11" D. Fir with partially healed blaze, bears S.35°W., 9.2 ft.
A 28" D. Fir, wind thrown stump, bears N.20°W., 15.2 ft.

RE-RENEWED, SEE CORNER NO. #237 Ren. #16