

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

C O N T -----

Glen Baughman  
For: U.S. Forest  
Service  
July 1979  
C.S. 58/176

A 24" D. Fir stump, bears N.2°E., 21.8 ft. #237 197  
A 12" D. Fir with healed blaze, bears N.80°E., 40.8 ft.  
A 18" D. Fir with healed blaze, bears S.52°E., 51.3 ft.  
A 26" D. Fir with scribe marks visible on a partially healed  
blaze, bears S.72°W., 21.2 ft.  
New BT - A 16" W. Fir bears N.56°W., 140.1 ft. I marked "T30S R1W S31 BT"  
on a double blaze and nailed a brass washer stamped "LS 536  
into lower blaze.

7/79

Center 1/4 Corner Section 34. 198

Set - Brass Cap stamped "T.30S. r.1W., W.M. C1/4 S34 RLS 430  
1980".

BT's - A 14" incense cedar bears N.40°E., 39.5 ft. and scribed  
"C1/4 S34 BT" #240

A 20" incense cedar bears N.1°W., 54.2 ft. and scribed  
"C1/4 S34 BT".

199

Section Corner to Sections 34 & 35, T.30S. R.1W. See Ren. #101

Fd.- GLO Brass Cap at corner properly marked.

14" Oak original BT snag, scribes visable bears N.49°E.,  
34.5 ft. (Record N.45°E., 33.7 ft.)

34" D. Fir original BT with visable face bears S.40°E.  
4.0 ft.

14" D. Fir bears N.2 1/2°W., 15.6 ft. marked by Douglas  
County Surveyor's Office.

New BT- 20" Douglas Fir bears N.76°E., 35.5 ft. scribed "T30S  
R1W S35 BT".

200

1/4 Corner to sections 34 and 35.

Set - Brass cap stamped "T30S, R1W, W.M. 1/4S S34, S35 RLS 430

BT's - 50" Ponderosa pine which is original BT. Partial scribes  
visable, rescribed "1/4 S34 BT" bears S.30°W., 5.3 ft.  
Burned out pine stump which is original BT bears N.10°E.,  
67.5 ft. (record 62.7 ft.)

6" D. fir bears N.40°E., 12.3 ft. scribed "1/4 S35 BT".

16" D. fir bears N.73 1/2°W., 86.0 ft. scribed "1/4 S34  
BT".

201

1/4 Corner for Section 23 only. (East)

Found - A 1923 US GLO brass cap properly marked, on 1" I.P. firmly set  
protruding 9" from soil.

Center of large stone measuring 16"x24"x5" deep bears N.87 1/2°W.,  
4.6 ft. There are smaller stones strewn about this large stone  
This may be the remains of the pile of stone originally set  
west of the monument.

An orig. 24" now 27" Cedar bears S.2 1/2°W., 153.1 ft. (Rec.  
S.1°W., 153.1 ft.) Tree has a fully healed single blaze, no  
scribing visible.

A 12" now a 15" Madrone (Laurel) bears N.22 1/2°W., 7.0 ft. Tree  
has a partially healed double blaze with scribing "1/4 S23  
CS T visible. Ren. #25

Set - Monument is in good condition and because both bearing tree  
distances agree with record the position of the monument is  
accepted.

New BT's- A 9" D. Fir bears N.86°W., 17.8 ft. scribed "1/4 S23 CS BT" on a  
double blaze.

An 18" Madrone bears S.56 1/2°E., 22.9 ft. bark scribed "1/4 S23  
CS BT"

Both trees are tagged with DCSO BT tags noting 1/4 corner is for Section  
23 only.

9/11/80

Bruce A. Shaner  
For: U.S. Forest Service  
April 1980  
RM 3 - 29

Stephen Flause  
Deputy, Doug. Co.  
Surveyors Office  
Bill Stewart  
Karen Mosely  
Sept. 11, 1980  
C.S. 61/11