

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30 T. S. R 1 R. W. W. M.

KOKS-CHAPMAN CO., EUGENE, ORE. 31981

202

1/4 Corner for Sections 19 and 30.  
Found - 2" I.P. firmly set, projecting 8" above ground with properly marked brass cap set by Baughman in 1968. Ren. #109  
A 14" Madrone, south trunk of a triple clump, N.23 1/2°E., 28.9 ft. (Rec. N.21°E., 27.3 ft.) with scribe marks "1/4 S19 T30S R1W BT" visible on partly healed blaze.  
A 14" S. Pine snag, S.12 1/4°E., 17.3 ft. (Rec. S.11°E., 17.0 Ft.) with scribe marks "1/4 S30 T30S R1W BT" visible on partly healed blaze.  
Set - Added 2 ft. mound of stone to corner monument.  
New BT - 8" I. Cedar, S.25°E., 13.0 ft. scribed "1/4 S30 CS BT".  
10/28/80

Leonard Herzstein  
U.S.F.S. - Deputy  
Doug. Co. Surveyors  
Office  
Witnessess - Joe Richey  
Art Arciniega  
Oct. 28, 1980  
C.S. 61/11

203

Section corner for Sections 19, 20, 29 and 30.  
Found - 1968 County brass cap, properly marked on a 1 1/2" I.P., firmly set, projecting 10" above ground. Ren. #61  
Orig. 22" D. Fir snag, S.89°W., 7.9 ft. to face with S.M. "BT" visible on previously opened blaze.  
A 24" D. Fir, N.15 1/2°E., 26.5 ft. with partly healed blaze. #61  
A 15" D. Fir, S.33°E., 32.3 ft. (Rec. 33.4 ft.) with healed doubled blaze. Ren. #61  
A 35" D. Fir stump, S.45°W., 44.9 ft. with partly healed blaze.  
A 11" W. Fir, N.17°W., 29.3 ft. (Rec. D. Fir) bears N.15°W., 28.8 ft.) with partly healed blaze.  
Set - Added 2 ft. diam. mound of stone, I.P. now projecting 4".  
New BT - A 5" W. Fir, S.30 1/4°W., 31.4 ft. marked "T30S R1 W S30 CS BT"  
10/30/80

Leonard Herzstein  
U.S.F.S. - Deputy  
Doug. Co. Surveyors  
Office  
Witnessess - Art  
Arciniega, Joe Richey  
Oct. 30, 1980  
C.S. 61/11

204

1/4 Corner for Sections 10 and 11  
Set - Brass cap marked: T30S R1W W.M. 1/4 S, S10, S11 RLS 430, 1980  
BT's - 18" D. Fir, BT. I scribed "1/4 S10 BT" bears S.30°W., 44.8 ft.  
10" D. Fir BT. I scribed "1/4 S11 BT" bears S.59°E., 47.7 ft.  
11/80

Bruce Shaner PLS #430  
For: Tiller Ranger  
Dist. Umpqua Nat'l  
Forest  
Nov. 1980 M 79-63

205

1/4 Corner for Sections 10 and 15  
Set - Brass cap mkd. T30S R1W, W.M. 14/ S10 S15 RLS 430 1980"  
New BT's - 12" Ponderosa Pine ET, I scribed "1/4 S15 BT" bears S.68°W., 51.6"  
20" Ponderosa Pine BT, I scribed "1/4 S10 BT" bears N.23°E., 33.3"  
1/81

Bruce Shaner  
For: U.S. Forest  
Service  
January 1981  
RM 3 - 42

206

Center 1/4 Corner for Section 15.  
Set - Brass cap mkd. "T30S R1W W.M. C1/4 S15 RLS 430 1980"  
New BT's- 8" Douglas Fir BT, I scribed "C 1/4 S15 BT" bears N.15°W., 29.6 ft.  
10" D. Fir BT, I scribed "C 1/4 S15 BT" bears S.51°E., 72.0 ft.  
1/81

207

1/4 Corner for Secs. 31 and 32  
Set - Brass cap marked "T30S R1W W.M. 1/4 S31 S32 R.L.S. 430 1981"  
BT's - 10" D. Fir, BT, I scribed "1/4 S31 BT" bears S.30°W., 8.9 ft.  
12" D. Fir BT, I scribed "1/4 S32 BT" bears N.89°E., 34.5 ft.

208

Section corner for Secs. 29, 30, 31 and 32.  
Found - 1" I.P. Ren. #11  
20" D. Fir snag, orig. BT, scribes visible bears N.46°W., 19.8 ft.  
25" D. Fir stump, orig. UT partial face, bears N.47°E., 13.2 ft. (GLO rec. N.20°E; Markham rec. 1961, N.47°E.)  
22" W. Fir BT scribes visible bears S.29°W., 8.7 ft.  
30" D. Fir BT bark scribes visible bears S.6°W., 38.0 ft.  
32" W. Fir stump BT face visible bears N.55°E., 31.7 ft.  
16" D. Fir BT scribes visible bears N.8°W., 96.0 ft.  
Set - Brass cap in place of 1" I.P. marked: "T30S R1W W.M. S29 S30 S31 S32 RLS 430, 1981"  
New BT's- 6" D. Fir BT, I scribed "T30S R1W S29 BT" bears N.74°E., 25.1 ft.  
6" D. Fir BT, I scribed "T30S, R1W S32 BT" bears S.68°E., 8.1 ft.

Bruce Shaner  
For: U.S. Forest  
Service  
January 1981  
M 79 - 72  
RM 3 - 43

1/81