

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 30 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Loyd R. Moffit LS 944
For: U.S. Forest Service
April 1985
C.S. 63/8

1/4 Corner for Secs. 21 and 22 Ren. #164
Found - A 2 1/2" brass cap on a 2" iron pipe marked "T30S R1W R1/4
S22 N.89°01'13"W 1978 LS 866" and bears S.89°01'13"E.,
218.79
218.79 feet from true 1/4 corner between sections 21 and 22.
From reference monument, I scribed:
An 8" fir marked "X" BT, bears N.89°W., 46.3 ft.
A 6" fir marked "X" BT, bears N.42°W., 65.7 ft.
Found - A 2 1/2" brass cap on a 2" iron pipe marked "S.89°01'13"E
61/92
1/4 S21 RLS 866 1978" and bears N.89°01'13"W., 61.92 ft.
from true corner between Sections 21 and 22.
From this reference monument, I scribed:
A 12" fir marked "X" BT, bears S.0;°E., 60.1 ft.
A 12" chinquipin marked "X" BT, bears West 7.0 ft.

222

1/4 Corner for Sections 22 and 27. 223
Found - 2" brass cap on a 2" iron pipe projecting 6" above stone mound.
Ren. #165
An 8" snag bears S.32°E., 24.5 ft. scar visible.
An 8" snag bears S.34°W., 22.5 ft. scar visible.
A 16" cedar bears N.64°W., 51.0 ft. scribe visible.
A 12" oak bears N.52°W., 47.0 ft. scar visible.
New BT - A 6" fir which bears S.16°E., 4.3 ft. marked 1/4 S27 BT.

Section corner for Secs. 32 and 33; and Secs. 5 and 4 of T.31-1 224
Found - A 2 1/2" brass cap on a 1 1/2" iron pipe. Ren. #56
A 32" fir bears N.42°E., 10.8 ft. scar visible.
A 20" madrone bears S.74°E., 10.6 ft. scar visible.
A 17" pine bears S.01°E., 16.9 ft. scribe visible. (no record)
A fir stump bears S.88°W., 9.7 ft. scar visible.
A 15" fir bears N.56°W., 36.5 ft. scribe visible.
New BT - An 8" fir which bears S.43°W., 35.6 ft. marked "T31S R1W S5 BT".

1/4 Corner for Sections 12 and 13. 225
Found - A 1923 GLO brass cap on a 3/4" iron pipe.
A 12" dead fir bears N. 15° E., 10.1 ft. scribe visible.
A 16" fir, down, bears S. 41° W., 11.4 ft. healed blaze.
A 14" fir bears S. 72° W., 58.6 ft. scribe visible. (Rec.
S. 65° 19' W.) Ren. #175
A pine stump (orig. BT) bears N. 17° W., 87.4 ft. scar visible.
A 40" pine (orig. BT.) bears S. 25° E., 103.5 ft. scribe visible.
New BT - 10" fir which bears East 9.4 ft. scribed 1/4 S12 BT.

*FD OK 4/86
R. GE 5/86
C.S. 63/34
FD To Be 5.65 W*

Loyd R. Moffit
L.S. #944
For: U.S.F.S.
May 1985
C. S. 63/8

Section corner for Sections 2 and 1 only. 226
Found - 2 1/2" alum. cap on 3/4" iron pipe. Ren. #117
30" fir bears S. 62° W., 17.2 ft. scribe visible.
48" dead fir bears S. 46° E., 20.5 ft. scribe visible.
40" fir bears N. 10° E., 88.9 ft. scribe visible. (no rec.)
New BT - 10" fir, bears S. 33° E., 24. 1 ft. scribed T30S R1W S1 BT.

Section corner for Secs. 10, 11, 14 and 15. 227
Found - 2 1/2" bronze cap on a 1" iron pipe. (DCSO) Ren. #66
A dead oak bears S.80°E., 95.2 ft. rotted blaze.
14" oak bears S.54°E., 15.0 ft. scar visible.
A fir stump bears S.58°W., 86.4 ft. scar visible.
A fir stump bears S.87°W., 133.4 ft. axe work visible.
26" oak bears N.83°W., 147.5 ft. scar visible.
14" fir bears N.33°W., 12.0 ft. scribe visible.
50" oak bears N.14°E., 101.8 ft. scar visible.
New BT - 10" oak bears S.47°W., 9.4 ft. scribed T30S R1W S15 BT.