

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30

T. S.

R 1

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

234

Loyd R. Moffit  
L.S. #944  
For: U.S. Forest Serv.  
Dec. 1985  
C.S. 63/30  
62

Closing Corner for Sections 9 and 10  
Found - 1" Iron pipe with 2 1/2" brass cap exposed 16" in small  
rock mound. Corner re-monumented in 1969 by County. Ren. #155  
New BT - Marked a new 15" cedar BT which bears S.33 1/3°E., 102.1 ft. from  
the corner, scribed T30S RLW S10 BT with brass L.S. tag #944  
in lower part of blaze.

235

Loyd R. Moffit  
For: U.S. Forest  
Service  
April, 1986  
C.S. 62/30

1/4 Corner for Sections 7 and 8  
Found - 2 1/2" brass cap on 1" iron pipe exposed 12". Ren. No. 76  
A 26" hemlock (dead) bears N.48°E., 12.4 ft. scribe visible.  
24" hemlock bears S.26°E., 39.6 ft. scribe visible.  
A hemlock (down) bears N.18°W., 22.3 ft. scribe visible.  
New BT - I marked a 7" fir BT which bears N.67 1/2°W., 29.8 ft.  
from the corner, scribed 1/4 S7 BT. Nailed L.S. 944 brass  
washer to BT scribe.

RE-RENEWED, SEE CORNER NO. #239

236

Ron Geisler L.S. 1988  
For: Champion Int'l.  
July 18, 1986  
C.S. 63/34

North 1/4 Corner for Section 2  
Found - 2 1/2" alum. cap on a 1" I.P. extends 14" above ground. Ren. #55  
9" W. fir bears S.47°W., 14.6 ft. Closed face (1967)  
19" Fir (stump) bears S.20°E., 42.2 ft. Closed face (1967)  
New BT - 6" W. fir bears S.30°E., 18.06 ft. and scribed 1/4 S2 BT. (1986)

237

Loyd R. Moffit  
For: U.S.F.S.  
Dec. 1986  
C.S. 62/30

Section Corner for Sections 31 and 32; and 5 and 6 of T.31-1  
Found - 1966 County 2 1/2" brass cap on 1" I.P. Ren. #16  
24" rotted Fir stump which bears N.02°E., 21.8 ft.  
12" Fir which bears N.80°E., 40.8 ft. Scar visible.  
18" dead Fir which bears S.52°E., 51.3 ft. Scribe visible.  
14" Fir which bears S.35°W., 9.2 ft. Scar visible.  
20" dead Fir which bears S.72°W., 21.2 ft. Scribe visible.  
16" Fir which bears N.56°W., 140.1 ft. Scribe visible. Ren. #197  
27" uprooted Fir which bears N.20°W., 15.2 ft.  
24" Fir which bears N.89°W., 23.0 ft. Scar visible. (orig. unknown)  
New BT - 7" Cedar which bears S.40°E., 62.8 ft. from the corner, scribed  
T31S RLW S5 BT, with LS washer No. 944 nailed to BT scribe.  
12/86

238

Maurice E. Farr  
U.S.F.S.  
Leonard Herzstein  
Randy Lopez,  
Witnessess.  
March 26, 1987  
C.S. 62/44

South 1/4 Corner for Section 35 only, T.29-1  
Found - A 7/8" outside dia. I.P. firmly set projecting 10" above  
the ground, with a 2 1/2" alum. cap mkd. "U.S.P.C. Prop. Cor.  
S 1/4 T29S. R.1W RE 4287 1967 Do Not Disturb". Ren. #114  
Orig. BT, a 50" D. fir rootcrown, N.62°E., 25.5 ft. with scribes  
"BT" visible on a dedayed blaze.  
Orig. BT, a roothole, N.60°W., 32.5 ft. with a 45" D. fir stump  
alongside with fragmentary scribes visible on a previously  
opened blaze.  
An 8" D. fir stump, N.30°E., 20.3 ft. (Rec. N.32°E., 1919 ft.  
with log alongside with scribes "S 1/4 S35 BT" visible on a  
single blaze.  
Set - I set a 6 ft. alum. post, driven 2 ft. in the ground as a gua  
post., S/80°E., 1.2 ft. with F.S. sign #54-4 attached.  
New BTs - A 6" hemlock, N.12 3/4°E., 24.0 ft. scribed "1/4 S35 BT" on a  
single blaze.  
An 8" W. fir, N.67 3/4° W., 37.1 ft. scribed "1/4 S35 BT" on a  
double blaze.  
A 3/4" brass washer stamped "LS 1181" is nailed flush to the base of blaze  
on both new bearing trees.  
Note: Based on plat M72-24, I found the magnetic declination to be 18° E.  
The corner is in a low area with running water. An 18" culvert bears  
S.14°E., 56 ft. and a 12 ft. wide rock road bears South, 60 ft. To  
reach the corner from F. Rd. No. 28, "South Umpqua Road", turn right  
(south) onto F. Rd. No. 2980, "Zinc Creek Road", drive 4 miles and turn right  
onto Rd. No. 2980-700. Drive about 2 1/4 mi. and turn left onto rock road  
and drive 0.1 miles to corner.

3/26/87