

Douglas County Surveyor's Record of
Government Corners Renewed

30 T.S. 2 R.W.W.M.

SEE CORNER NO. 7 1

A. Boyer D.C.S. Arthur Boyer Dep. Co. Sur.
Wit. Witnesses
Geo. Stone
Donald Stone Sr.
Jan. 30, 1939
e.s. file 16/11

✓ CORNER BETWEEN SECTION 30, T.30S; R.2W., and SECTION 25 T.30S., R.3W.

No trees standing corresponding to bearing trees in General Land Office field notes. Set steel auto axle, gear on top, midway and on line between N.E. and S.E. corners of Section 25 from which

- A Fir 54" dia. scribed on bark, bears N.47 $\frac{1}{2}$ °W., 41.0 ft.
- A 110" Fir bears S.49°E., 29.7 ft., measured on slope
- A 54" Fir marked $\frac{1}{4}$ S.25 T.30S., R.3W., C.S.B.T.

No trees standing convenient for a B.T. in Section 30 so marked

A 10" Fir same as 54" Fir.

Found a 12" x 22" x 28" Granite Rock set in ground as if for a quarter corner but no chiseling was legible, this rock bears from the established corner S.58°W., 5.6 ft.

✓ S.W. CORNER OF SECTION 30 (CORR. COR.) 2

Maple tree to S.E. gone and rock originally set for corner loose and out of place. Set a $\frac{3}{4}$ " Pipe from Maple tree to the N.E. and put rock back in place as well as possible and marked a new B.T.

- A 12" Maple S.41 $\frac{1}{2}$ °E., 38 ft. marked C.C. S.31 T.30 R.2 C.S.B.T. SEE REN. #33

✓ SECTION CORNER TO SECTIONS 27, 28, 33 and 34. 3

Location identified from original B.T.s

- A Fir 24" diam. S.20°E., 25 lks. scribe marks partly visible.

Set a Rock 8" x 8" x 20", 16" in ground, marked X on top with 1 notch on South, 3 notches on West, 3 notches on North, and 3 notches on East corners from which

- Fir 30" diam. bears S.33°E., 42.2 ft. marked T.30S., R.2W., S.33 C.S.B.T.
- Fir 36" diam. bears S.33°W., 42.2 ft. marked T.30S., R.2W., S.33 C.S.B.T.
- Fir 30" diam. bears N.43 $\frac{1}{2}$ °E., 29.1 ft. marked T.30S., R.2W., S.27 C.S.B.T.
- Fir 30" diam. bears N.37°W., 20.0 ft. marked T.30S., R.2W., S.28 C.S.B.T.

✓ SECTION CORNER BETWEEN SECTIONS 23, 24, 25, and 26. 4

Location identified from original bearing trees

- A 72" Pine N.33°W., 50 lks.
- A 24" Fir (down) S.74°E., 46 lks.
- A 24" Fir (down) N.4°E., 75 lks.

all bearing scribe marks partly legible. Set Rock 8" x 8" x 18", 12" in ground in mounds of stone. Marked X on top, 7 notch East--2 notches South--5 notches West--and 4 notches on North, from which

- S.B. Fir Tree instead of S. Pine
- Sugar Pine 8" diam. bears S.80°W., 45.7 ft. marked T.30S., R.2W., S.26 C.S.B.T. SEE NOTE IN C.S. 16/55
- A Fir 30" diam. bears N. 4°E., 74.1 ft. marked T.30S., R.2W., S.24 C.S.B.T.
- A Fir 6" diam. bears S.34 $\frac{1}{2}$ °E., 42.8 ft. marked T.30S., R.2W., S.25 C.S.B.T.
- A Pine 72" diam. bears N.33°W., 33.9 ft. marked T.30S., R.2W., S.23 C.S.B.T.

✓ CORNER BETWEEN SECTIONS 23 and 24. 5

All signs of this have been obliterated an location falls in a wash. Established new corner mid-way between section corner 13, 14 23 and 24, and 23, 24, 25, and 26. Set a stone 8" x 8" x 22", marked X on top and $\frac{1}{4}$ S. on South face, 26" in ground with a stone 6" x 8" x 24" similarly marked on top and surrounded by a mound of stone. 6" x 6" x 72" Cedar post alongside mkd. $\frac{1}{4}$ S CS S23 - S24 - from which an

- An Oak 8" diam. bears N.15 $\frac{1}{2}$ °W., 87.2 ft. marked $\frac{1}{4}$ S. 23 C.S.B.T.
- A Cedar 18" dia. bears S.24 $\frac{1}{2}$ °E., 94.3 ft. marked $\frac{1}{4}$ S. 23 C.S.B.T.

Ben B. Irving D.C.S.
Wit. N. E. Richardson
Loren Weber
August 2, 1940
V.16-E.55