

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 2 R. W. W. M.

✓ 1/4 SECTION CORNER BETWEEN 13 and 24. 20

Original corner obliterated. Set a Rock 6" x 9" x 20" marked X 1/4 for corner with Cedar Post 6" x 6" x 48" along side, midway between Corner 13 and 24 T.30S., R.2W., 18 and 19 T.30S., R.1W., and 13, 14, 23 and 24 T.30S., R.2W., from which

A Fir 20" diam. bears N.40°W., 6.7 ft. marked 1/4 S.13 S.B.T.
A Fir 36" diam. bears S.10°E., 41.0 ft. marked 1/4 S.24, C.S.B.T.

Ben B. Irvine D.C.S.
Witnesses
M. E. Richardson
Loren Weber
August 2, 1940.
V.16-E.55

✓ SECTION CORNER BETWEEN 13, 14, 23 and 24. 21

Location identified from one Original P.T. which is down but scribe marks legible and two other which check for bearing and distance but marks obliterated. Set Cedar Post in field for corner from which

Oak 16" diam. bears N.55 1/2°W., 100.0 ft. marked T.30S., R.2W., S.14 C.S.B.T.
Oak 14" diam. bears N. 2°E., 46.6 ft. marked T.30S., R.2W., S.13 C.S.B.T.
Fir 24" diam. bears S.74°W., 118.4 ft. marked T.30S., R.2W., S.23 C.S.B.T.
No tree near in S.E.

H.L. Eppstein
Wit.
W.L. Dolan
Fred Tolle
Stanley Rosch
June 9, 1926.

✓ SECTION CORNER BETWEEN 28, 29, 32 and 33. 22

Set 4" x 4" x 30" Larl (?) Post from three old B.T.s Marked bearing trees as follows

A 36" Fir N.31°E., 81 lks.
A 20" Fir N.65°30'W., 72 lks.
A 24" Fir S.50°W., 7 lks. old B.T.
A 30" Fir S.72°E., 16 lks.

Set Germond
August 1916.

✓ CORNER TO SECTIONS 24, 25, 19 and 30. 23

Set a 1" x 36" Bar for corner on Range Line. Witness trees

An Oak 15" dia. N.45°E., 29 lks.
An Oak 15" dia. S.74°E., 55 lks.
An Oak 15" dia. S.54°W., 37 lks.
An Oak 18" dia. N.38°W., 1.41 ch. ?

C.S. 1/33
Vol 3
Pg 9

C. C. OF 19 and 18 SECTIONS. 24

Post 4" Square 2.12 ch. North of corner between 24 and 13 in T.30-3, from which

A Fir 15" dia. N.78 1/2°E., 29 lks.
A Fir 24" dia. S.55 1/2°E., 28 lks.

✓ 1/4 SECTION CORNER BETWEEN 28 and 33. 25

Corner location identified by a stone 6" x 8" x 14" and two O.B.T.s. O.B.T.s down and burned out no numbers or scribed marks visible. Mr. Parker claims to have seen numbers on one of the trees before fire of last year. Marked stone "X" on top and 1/4 on South face.

A 16" Pine N.65°30'E., 78.8 ft. blazed and scribed T.30S., R.2W., 1/4 S.28 C.S.B.T.
A 24" Fir S.77°45'W., 99.5 ft. blazed and scribed T.30S., R.4W., 1/4 S.33 C.S.B.T.

Ben B. Irvine D.C.S.
Jan. 18, 1933
Wit.
M. E. Richardson
J. D. Loffer
Parker

✓ SECTION CORNER BETWEEN 28 and 27. 26

Location identified from both original B.T.s as described original government field notes. Both trees have fallen down and decaying rapidly. Set a 2 1/2" x 18" Iron Pipe for corner with a Serpentine rock 6" x 10" x 18" along side and marked 1/4 on South face.

New B.T.s
Pine 30" dia. N.38°W., 32.5 ft. blazed 1/2. 28 C.S.B.T.
Fir 30" dia. N.40°40'E., 37.0 ft. blazed 1/2. 28 C.S.B.T.

Ben B. Irvine D.C.S.
Sept. 27, 1934
Wit.
M. E. Richardson
Walter Teriwill
Vern Teriwill

SEC. COR. 28, 29, 32, 33

Found 4 O.B.T.s as set by Eppstein 6-9-26 in good shape. Marked "X" on granite rock in place, 18" x 18". Drove 1 1/2" iron pipe alongside.

A.R. Evans - Dep. Co. Surveyor
April, 1951