

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 2 R. W. W. M.

S. E. Corner Section 12 - as det. by O.B.T.'s.:

24" Pine bears N.18°E. 25.7 ft. dist. O.B.T., found scribe.

14" Fir bears N.34°W. 20.4 ft. dist. O.B.T.

24" Fir bears S.47°W. 24.8 ft. dist. O.B.T.

At Corner Point Found Stone & Set 3" x 30" Iron Pipe from which:

5" Chip. bears N.87°W. 17.0 ft. dist. mkd. S12 X B.T.

5" Chip. bears N.69°W. 25.8 ft. dist. mkd. S12 T30S B.T.

Road bears West 230.0 ft. distance.

35

John H. Markham, Jr.
For Stomar
Lbr. Co.
C.S. 42/421
Dec. 158

S.W. Corner Section 12. - as determined by O.B.T.'s.:

20" Laurel windfall bears N.41°E. 27.7 ft. dist. O.B.T., fd. scribe.

At Corner Point Found Stone and Set 3" x 48" Iron Pipe from which:

7" Fir bears S. 4°W. 19.2 ft. dist. mkd. S13 BT.

5" Fir bears S.80°W. 8.0 ft. dist. mkd. S13 R2W BT.

12" La. bears N.52°W. 39.0 ft. dist. mkd. S11 T30S R2W BT.

6" Fir bears N. 9°W. 33.3 ft. dist. mkd. S11 R2W BT.

N. E. Corner Section 14 bears West 120.0 ft.

36

John H. Markham, Jr.
Witness: R. G. Boyd
For - Stomar Lumber Co.
Jan. 26, 1959
C. S. File No. 42/421

N. E. Corner Section 14 - as determined by O.B.T.'s.:

15" La. Stump bears S.76½°E. 10.5 ft. dist. O.B.T., fd. scribe.

At Corner Point found large Stone and Set 3" x 40" Iron Rod from which:

36" Fir bears S.24°E. 21.0 ft. dist. mkd. S13 B.T.

5" Fir bears N.33°E. 9.3 ft. dist. mkd. S11 B.T.

12" La. bears N.11°E. 10.8 ft. dist. mkd. S11 B.T.

9" La. bears S.72°W. 64.0 ft. dist. mkd. S14 T30S R2W B.T.

S. W. Corner Section 12 bears East 120.0 ft.

FOUND O.K.
Nov. '68 JMP

37

North ¼ Corner to Section 18.

Found - Orig. 18", now 26" Fir Stump S.31°E. 25.7 ft., shows good scribing "S18".

Orig. 5", now down 8" Hemlock, shows good scribing "S18BT" S.21°E. 39.6 ft.

1" Iron Pipe 3.0 ft. above ground at corner.

I Set 3" Iron Rod alongside Iron Pipe.

New BT's: 17" R. Fir bears S.62°W. 77.5 ft. scribed ¼ S18 CS BT.

24" Sugar Pine bears N.50°W. 3.5 ft. scribed ¼ S18 CS BT.

38

James W. Byron
Milo Godfrey
S. A. Bilow
Jan. 30, 1959
C. S. File No. 49/86

South ¼ Corner to Section 7.

Found - Orig. 42", now 44" Top dead R. Fir Corner Tree scribed ¼ S7 on North Face.

Both Orig. BT's now scribed stumps.

Set Witness Corner 5' east of ¼ Corner Mkd. Wit. Cor. 5' West to South ¼ S7 T30S R2W County Surveyor's Office, 1959.

New BT's: 8" R. Fir bears N.3°W. 23.7 ft. scribed W.C. ¼ S7 CS BT.

6" R. Fir bears N.47°E. 29.0 ft. scribed W.C. ¼ S7 CS BT.

FOUND O.K.
Nov. '68 JMP

39

North ¼ Corner to Section 14 only.

As determined by O.B.T.'s.:

18" Fir bears S.26°W. 51.0 ft., slope dist. O.B.T., Fd. Scribe.

At Corner Point found Stone & Set 3" x 40" Iron Rod from which:

14" La. bears S.17°E. 34.6 ft. dist. mkd: ¼ S14 T30S R2W BT.

3" Chip. " S.19°W. 11.5 ft. dist. mkd: ¼ S B.T.

7" La. bears N.89°W. 19.3 ft. dist. mkd: ¼ S14 B.T.

4" Fir bears N.49°W. 16.8 ft. dist. mkd: ¼ S11 B.T.

South ¼ Corner 11 bears East 116.0 ft.

40

John H. Markham, Jr.
For Stomar Lumber Co.
Wit: R. G. Boyd
April 28, 1959
C. S. File No. 42/421

South ¼ Corner Section 11 only.

As determined by O.B.T.'s:

36" Fir Snag bears N.50°W. 37.0 ft. dist., O.B.T., Fd. Scribe.

15" Fir, uproot, bears N.43°E. 27.7 ft. O.B.T.

At Corner Point Found Stone & Set Truck Axle with Gear up from which:

5" Fir N.36°E. 5.7 ft. mkd: ¼ S11 X B.T.

20" La. N.52°W. 50.8 ft. mkd. ¼ S11 T30S R2W B.T.

5" Fir N.61°W. 6.3 ft. mkd. ¼ S11 B.T.

6" Fir S.26°W. 23.0 ft. mkd. ¼ S14 B.T.

North ¼ Cor. 14 bears West 116.0 ft.

41