

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21901

1/4 Section Corner to Sections 10 and 11, as set by O. B. T's: 47
 15" W. Fir Snag N.29°W. 21.3 ft. O. B. T.
 45" Fir, uproot, S.47°E. 19.1 ft. dist. O.B.T., fd. scribe.
 At Corner Point found Stone & Set 1 1/2" x 30" Iron Pipe from which:
 7" W. Fir bears S.18°W. 34.0 ft. dist. mkd. 1/4 S10 B.T.
 11" W. Fir bears S.33°E. 44.7 ft. dist. mkd. 1/4 S11 B.T.
 4" Cedar bears S.75°E. 25.7 ft. dist. mkd. 1/4 S11 B.T.
 15" Cedar bears N.11°W. 41.0 ft. dist. mkd. 1/4 S10 B.T.
 Road bears South 450.0 ft.

1/4 Section Corner to Sections 9 and 10, as det. by O. B. T's: 48
 16" W. Fir Snag S.22°E. 17.8 ft. O.B.T.
 17" W. Fir Snag N.47°W. 6.0 ft. O. B.T.
 At Corner Point found 30" Fir Snag scribed on West face &
 Set 2" x 30" Iron Pipe from which:
 9" Cedar N.33°E. 21.7 ft. mkd. 1/4 S10 B.T.
 9" Cedar N.59°E. 27.0 ft. mkd. 1/4 S10 B.T. FOUND O.K. 10/23/68 JMP.
 9" W. Fir S.80°E. 24.0 ft. mkd. 1/4 S10 B.T.

S. W. Corner Section 10, as det by O.B.T.'s: 49
 36" Cedar N.70°W. 21.0 ft. O.B.T., fd. scribe.
 53" Fir N.60°E. 18.5 ft. O. B. T.
 At Corner Point found Stone & Set 2" x 30" Iron Pipe from which:
 9" W. Fir S.38°E. 15.0 ft. S15 B. T.
 12" W. Fir S.64°E. 21.6 ft. S15 B. T.
 7" Cedar N. 7°W. 23.0 ft. S9 R2W B.T. CORNER NO. 192

(cc)
 N. W. Corner Section 15, as det. by O. B. T's: 50
 12" Fir S.22°E. 33.7 ft. O.B.T.
 10" Fir S.35°W. 26.4 ft. O.B.T., fd. scribed
 At Corner Point found 12" Fir mkd. on 4 Faces &
 Set 2" x 30" Iron Pipe from which:
 10" W. Fir bears S.50°E. 14.4 ft. dist. mkd. S15 X B.T.
 18" Cedar bears S.21°W. 47.0 ft. dist. mkd. S16 R2W B.T. FOUND O.K. 10/11/68 VRT

Section Corner to Sections 3-4-9-10, as det. by O. B. T's: 51
 36" Cedar S.36°W. 6.0 ft. O.B.T., fd. scribe.
 7" Dead Cedar S.15°E. 6.0 ft. O.B.T., fd. scribe.
 9" Cedar N.13°E. 11.2 ft. O.B.T., fd. scribe.
 16" Fir N.25°W. 11.2 ft. O.B.T.
 At Corner Point found Stone & Set 2" x 30" Iron Pipe from which:
 12" Cedar S.1°E. 10.4 ft. mkd. S10 R2W B.T. CORNER NO. #185
 21" Laurel N.82°E. 11.0 ft. dist. Mkd. S3 T30S R2W B.T.
 10" Cedar N.35°W. 19.8 ft. mkd. S4 R2W B.T.

1/4 Section Corner to Sections 3 and 10, as det. by O.B.T. 52
 30" Fir N.14 1/2°E. 9.9 ft. O.B.T.
 30" Fir Stump, logged, S.42°E. 20.0 ft. O.B.T.
 At Corner Point Set 2" x 30" Iron Pipe from which:
 12" Fir S.47°E. 10.1 ft. mkd. 1/4 S10 B.T. CORNER NO. #186
 12" Fir S.47°E. 22.0 ft. mkd. 1/4 S 3 B°T.
 8" W. Fir N.21°W. 8.8 ft. mkd. 1/4 S 3 B.T.
 7" W. Fir S.21°W. 15.9 ft. mkd. 1/4 S10 B.T.

South 1/4 Corner Section 12 only, as det. by O.B.T. 53
 20" Fir, uproot, N.40°E. 5.9 ft., fd. scribe
 At Corner Point Set 1 1/2" x 30" Iron Pipe from which:
 9" Cedar S.21°W. 36.5 ft. mkd. 1/4 S12 B.T.
 28" Cedar N.47°W. 41.0 ft. mkd. 1/4 S12 B.T.
 North 1/4 Corner 13 bears West 58.0 ft. distance. CORNER NO. #216

John H. Markham, Jr.
 O. A. Keatley
 For Stomar Lumber Co.
 Feb. 1960
 C. S. File No. 42/421

John H. Markham, Jr.
 Witness: O. A. Keatley
 For Stomar Lumber Co.
 March 24, 1960
 C. S. File No. 42/421

RE-RENEWED CORNER NO. 192

RE-RENEWED CORNER NO. #189

RE-RENEWED CORNER NO. #185

RE-RENEWED CORNER NO. #186

RE-RENEWED CORNER NO. #216