

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 2 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

John H. Markham, Jr.
Witness O. A. Keatley
For Stomar Lumber Co.
March 24, 1960
C. S. File No. 42/421

North $\frac{1}{4}$ Corner Section 13 only, as det. by O.B.T.
33" Fir S.77°E. 33.6 ft. O.B.T. fd. scribe. # 217
At Corner Point Found Stone and Set $\frac{1}{2}$ " x 36" Iron Pipe from which:
12" Cedar N.17°W. 27.8 ft. mkd. $\frac{1}{4}$ S19 B.T.
10" Fir S. 4°W. 52.0 ft. mkd. $\frac{1}{4}$ S13 R2W B.T.
South $\frac{1}{4}$ Corner 12 bears East 58.0 feet distance.

54

Center of Section 2.
At Corner Point Set $\frac{1}{2}$ " x 36" Iron Pipe from which:
9" W. Fir bears N.48°W. 9.0 ft. dist. mkd. $\frac{1}{4}$ S2 CC B.T.
5" Yew bears N.60°E. 12.3 ft. dist. mkd. $\frac{1}{4}$ S2 CC B.T.
18" Fir bears N.87°W. 9.8 ft. dist. Mkd. $\frac{1}{4}$ S2° CC B.T.
Road bears North 71.0 feet distance.

55

Grant &
Art. Evans
C. S. File
No. 41/66

$\frac{1}{4}$ Corner to Sec. 13, T30S R2W, & Sec. 18, T30S R1W.
Set Fir Stake from 2 O. B. T.'s: Scribe Marks Plain. # 103
48" Fir S.10°W. 8 lks.
30" Fir, new set, S.50°E. 12 lks.
November 1951

56

Bruce A. Shaner
For National Plywood, Inc.
Wit: W. James &
J. Griffin
July 12, 1960
C.S. File No. 51/105

$\frac{1}{4}$ Corner common to Sections 4 and 5.
Original - A slate Stone 18"x10"x10", 12" in the ground, mkd " $\frac{1}{4}$ "
on west face. This stone is missing; two windfalls
have recently slid over the area.
From this Stone, a: Fir, 15" diam., bears N.75°E., 21 lks., mkd. 195
" $\frac{1}{4}$ S 4BT". (A rotten D. Fir Stump with scribes visible,
was found here.)
18" Fir bears S.11 $\frac{1}{2}$ °W, 7 lks., mkd. " $\frac{1}{4}$ S 5 BT".
(A 10" Hemlock, dead & down, mkd, " $\frac{1}{4}$ S 5 BT", was fd. here.)
Restored: I set a $\frac{1}{2}$ " Iron Pipe for the $\frac{1}{4}$ Corner, from which:
Pair of Orig. BT's., as described above, fit the
correct description.
40" D. Fir, scribed " $\frac{1}{4}$ S BT", bears N.69°E., 8,8 ft.
5" Yew, scribed " $\frac{1}{4}$ S BT", bears S.46°30'W. 12.5 ft.

57

Bruce A. Shaner
Wit. James B. Griffin
For National Plywood, Inc.
Aug. 5, 1960
C. S. File No. 51/105

Section Corner common to Secs. 21, 22; 27 and 28.
Orig - We found the stone established in the 1908 Retracement Survey,
marked with 2 notches on the W. edge & 3 notches on the E.
edge, 14 x 8 x 5", 9 $\frac{1}{2}$ " in ground, and from which a:
12" Ponderosa Pine, now blown down, but with scribes
visible, bears N.71 $\frac{1}{2}$ °E. 79 lks. dist.
Ponderosa Pine Root Collar & chunk with scribes visible
bears S.46 $\frac{1}{2}$ °E. 25 lks. dist.
Ponderosa Pine Root Collar & chunk with scribes visible
bears S.51°W. 25 lks. dist.
16" Oak with faces visible, bears N.44 $\frac{1}{2}$ °W. 20 lks. 160
Rstrd. - Left the Orig. Stone in place & from which a:
16" D. Fir bears N70 $\frac{1}{2}$ °E. 46.9 ft., newly scribed "T30S R2WS27 BT".
8" D. Fir bears S.64°E. 20.3 ft., newly scribed "T30S R2W S27 BT".
22" D. Fir bears S.55°W. 34.3 ft., newly scribed "T30S R2W S28 BT".

58