

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

James W. Byron, Deputy County Surveyor  
Mike Darby and Wm. Stoffel  
February and March 1963  
C. S. File No. 52/138

1/4 Corner to Sec. 7, T30-2W. & Sec. 12, T30-3W. 66  
Found - Both Orig. BT's. Orig. 11", now 30" Fir N.2 1/2°E. 50.2 ft.,  
shows good scribing, previously opened.  
Orig. S.W. BT. shows good scar. BT's. check record.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963  
1/4 R3W S12/S 7 R2W T30S  
New BT's: 16" R.Fir bears S.46 1/2°E. 28.4 ft. scribed 1/4 S7 CS BT.  
20" R.Fir bears N.28°W. 18.5 ft. scribed 1/4 S12 CS BT.

Corner to Sections 12 and 13, only, T30-3W. 67  
Found - 1 1/4" I.P. at corner & both Orig. BT's. S12 | T30S  
Orig. S.W. BT., previously opened. Face rotted. R3W S13 | R2W  
Orig. N.W. BT. shows scar.  
New BT: 20" Cedar bears S.49°W. 17.6 ft. scribed S13 T30S R3W CS BT.

Closing Corner Section 7 & 18, T30-2W. 68  
Found - Orig. 12", now down 22" Fir, S.52°E. 9.3 ft., shows good scribing.  
Orig. N.E. BT not found. Corner Stone not found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 S 7 CC  
R3W | S18 R2W T30S  
New BT's: 7" R.Fir S.62°E. 48.0 ft. scribed CC S18 CS BT.  
7" Cedar N.54°E. 84.4 ft. scribed CC S 7 CS BT.

Section Corner to Secs. 6 & 7, T30-2W. & Secs. 1 & 12, T30-3W. 69  
Found - All Orig. BT's. All check record. S.W. BT. shows scribing.  
N. W. Bearing Tree down.  
Set - Brass Cap at Cor. & at hub with tack, set recently, Mkd. Cap:  
County Surveyor's Office, 1963 S 1 | S 6 T30S  
R3W S12 | S 7 R2W  
New BT's: 9" Fir bears N. 4°W. 14.2 ft. scribed S1 T30S R3W CS BT.  
12" Chinquapin bears N.30°E. 4.4 ft. scribed T30S R2W S6 CS BT.

Corner to Sections 18 and 19 only, T30-2W. 70  
Found - Brass Cap at Corner. N.E. BT. is in good condition. R3W | S18  
S.E. Bearing Tree, now down. - ~~Ren. #46~~ S19 R2W  
New BT: 17" Cedar bears S.25°E. 37.8 ft. scribed S19 T30S R2W CS BT.

East 1/4 Corner to Sections 24, T30-3W. 71  
Found - Orig. BT's. as recorded by Markham, & 7" W. Oak recorded by him. - Ren. #37 T30-3W.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963  
E 1/4 S24 T30S R3W  
New BT: 5" Laurel bears S.43°E. 27.5 ft. scribed 1/4 CS BT.  
No other trees near.  
Note - Corner is at top of steep north slope.

1/4 Corner to Sections 22 and 23. 72  
Found - Stone 4"x7"x16 at Corner as recorded by B.B. Irving, 1940. SEE GOVT SURVEY 1963  
16" Fir, now 18" N.39°E. 47.3 ft., shows scribing. - ~~Ren. #18~~  
16", now 18" Fir S.41°W., (not S.31°W.) 39.0 ft., shows scribing.  
Set - Brass Cap alongside Corner Stone & Mkd: County Surveyor's Office, 1963  
1/4 S22/S23 T30S R2W 183  
Note - North South Fence West 8.0 feet.

The section corner of Sections 28-29-32-33 73  
Location was determined by four O.B.T.'s in good shape, to-wit:  
36" Fir, N 31°E 81 lks.  
20" Fir, N 65 1/2°W 72 lks.  
24" Fir, S 50°W 7 lks.  
30" Fir, S 72° E 16 lks. - ~~Ren. No. 27~~

A cross was marked on an 18" x 18" granite stone in place for the exact location of the corner, and an 1 1/2" iron pipe was driven alongside. 170

A. R. Evans, Dep  
Irving & Clinton  
May, 1951  
S.F. 44/121

RE-TRIED CORNER NO. 170