

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section corner between Sections 28 & 33
Corner & accessories are renewed.
A 16" Pine bears N. 65° 30' E. 78.8 feet (scribes legible)
A 24" Fir bears S. 77° 45' W. 99.5 feet (bark scribe legible)
Corner stone easily displaceable, set 3 inch pipe 6 inches North.

Chas. S. Collins
Aug, 1947
Sur. File: 40/28

Township Corner: ; ;

Found - 15" Fir, now 36", Corner Tree, had been opened, scribing.
18" Fir, now stump, S. 70° W. 18.5 ft., shows good scar.
15" Fir, now stump, N. 66° W. 79.9 ft., shows scar.
48" Fir, now 49", N. 48° E. 19.8 ft., very old bark scribe.
15" Fir, now 34", S. 40° E. 13.2 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T30S R
(N-W Side of Office, 2 S 36 | S 31 1
Corner Tree) 1966 T31S W S 1 | S 6 W
New BT's: 12" D. Fir N. 19° W. 81.3 ft. scribed T30S R2W S 36 CS BT.
11" D. Fir S. 12° W. 109.3 ft. scribed T31S R2W S1 CS BT.
Distances to center of corner tree.
Corner lies on top of main ridge, running E. & W.

June 6, 1966

1/4 Corner to Sec. 35, T30-2W. & Sec. 2, T31-2W.

Found - 30" Pine, now 34", N. 80° E. 56.1 ft. (posted N.75°E.),
scribe "1/4 S" visible.

18", now 32" Oak S. 30° E. 87.1 ft., scribe visible "1/4 S".

Set - Brass Cap at 1/4 Cor. Mkd. County Surveyor's T30S R2W 1/4 S 35
Office, 1966 S 2

Reblazed & Rescribed: 32" Oak S. 30° E. 87.1 ft. scribed 1/4 S 2 CS BT.
Aug. 16, 1966

Sec. Cor. to Secs. 35 & 36, T30-2W. & Secs. 2 & 1, T31-2W.

Found - 10" Oak, now stob, N. 85° W. 31.0 ft., shows good scar.

10" Oak, now 15", S. 12° W. 44.2 ft.; shows good scar.

15" Oak, now stob, S. 25° E. 42.2 ft., scribe visible "2W".

15" Oak, now 26", N. 77° E. 25.1 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R S 35 | S 36
Office, 1966 T31S 2W S 2 | S 1

New BT's: 17" W. Oak N. 30° W. 39.3 ft. mkd. T30S R2W S35 CS BT.

15" W. Oak S. 22° E. 45.4 ft. mkd. T31S R2W S1 CS BT.

1/4 Corner to Section 32 only, T30-2W.

Found - Scribed Stake at 1/4 Cor. Mkd. "1/4 S32 CS". See Ren. #11.

Orig. 12" Laurel, now 18", N. 65° E. 44.8 ft., shows scar.

Orig. 8" Cedar Stump N. 60° W. 8.5 ft., scribe visible.

10" D. Fir N. 37° W. 17.5 ft., scribe visible "4".

17" Cedar N. 69 1/2° E. 46.4 ft., scribe visible, "1/4 S32 CS BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S
Office 1/4 S 32 R2W
1966 T31S

Do not mark new BT's., as all Trees in good condition.

Section Corner to Sections 33 & 34, T30-2W. and
Sections 4 & 3, T31-2W.

Found - 15" Corner Tree, scribe visible "T30S S33-34".

10" D. Fir, now 14", N. 62° E. 54.0 ft., shows good scar.

18", now 22" D. Fir, S. 70° W. 8.6 ft., shows good scar.

40" D. Fir N. 70° W. 11.2 ft., scribe visible "T30S R1W S33".

18" Fir, now stub, S. 20° E. 7.9 ft.

Set - Brass Cap on south side of Corner Tree Mkd. T30S S 33 | S 34 R2W
County Surv's. Office, 1966 T31S S 4 | S 3

New BT's: 20" D. Fir S. 10° E. 14.8 ft. mkd. T31S R2W S 3 BT.

8" Cedar N. 35° W. 15.2 ft. mkd. T30S R2W S33 CS BT.

RENEWED CORNER NO. 86 74
SEE #25

John M. Powell &
Crew
C. S. File 54/28

John M. Powell &
Crew
August, 1966
C. S. File 54/28

Fd. by Ruppert
February, 1984
M 96-39

RENEWED CORNER NO. 205