

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T.S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

80

1/4 Corner to Sec. 33, T30-2W. & Sec. 4, T31-2W.
Found - 24", now 30" Cedar, poor condition, N. 20° W. 11.9 ft.,
scribe visible "1/4 S". #198

18", now 25" D. Fir South 6.6 ft., shows faint scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office
1966

T 30 S	R
S 33	2
S 4	W
T 31 S	

New BT: 4" Hemlock N. 30° E. 26.3 ft. scribed 1/4 S CS BT.
Rescribed: 25" D. Fir South 6.6 ft. scribed 1/4 S 4 CS BT.

81

Section Corner to Sections 5 and 4 only, T31-2W.
Found - 36", now 42" Corner Tree, opened West Side for scribing "5".
12", now 23" Fir S. 33° E. 34.3 ft., shows good scar. #218
20", now 25" Laurel S. 1° W. 19.1 ft., shows good scar.

Set - Brass Cap on South Side of Corner Tree Mkd:
County Surveyor's Office
1966

T 30 S	R
S 32	2
S 5/S 4	W
T 31 S	

Reblazed & Rescribed: 25" Laurel mkd. "T31S R2W S5 CS BT", S. 1° W. 19.1 ft.

82

Section Corner to Sections 32 and 33 only, T30-2W. #197
Found - 10", now 18" D. Fir N. 50° E. 38.2 ft., shows good scar.
36" D. Fir, now down, N. 3° W. 26.4 ft., scribe marks visible,
but not legible.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office
1966

T 30 S	R
S 32/S 33	2
S 4	W
T 31 S	

New BT: 22" D. Fir N. 26° W. 33.5 ft.
mkd. T30S R2W S32 CS BT. Aug. 25, 1966

83

Sec. Corner to Sections 34 & 35, T30-2W. & Secs. 3 & 2, T31-2W.
Found - No trace of S.E. BT.
24", now 32" D. Fir S. 80° W. 16.5 ft., faint bark scribe & scar vis.
24", now 28" D. Fir N. 30° E. 11.9 ft., bark scribe visible.
6", now 15" Cedar N. 36° W. 22.4 ft., scribe visible "S3".

Set - Brass Cap at Cor. Mkd: County Surveyor's Office
1966

T 30 S	R 2 W
S 34	S 35
S 3	S 2
T 31 S	

Reblazed & Rescribed:
32" D. Fir S. 80° W. 16.5 ft. scribed T31S R2W S 3 CS BT.
28" D. Fir N. 30° E. 11.9 ft. scribed T30S R2W S 35 CS BT.
New BT: 6" D. Fir S. 38° E. 18.3 ft. scribed S 2 CS BT.
Note - This corner lies about 60.0 ft. south of small draw.

Sept. 22, 1966

MICROFILM TOHERE 10/67

84

1/4 Section Corner common to Sections 32 and 33.
Found - Granite Stone 15x12x10", 10" in ground, marked "1/4" from which a:
16" D. Fir BT with old face, bears S. 53° E. 7.9 ft.
15" Madrone BT, now blown down but with scribe visible, #221
bears N. 76° W., 12.5 ft.

Scribed: 40" D. Fir BT, I scribed "1/4 S, S32, BT," bears S. 86° W., 35.0 ft.

85

Section Corner common to Sections 27 - 28 - 33 - 34.
Found - 3/4" Bolt beside 8x8x20" Rock, from which a: (See Ren. #3)
24" D. Fir BT bears S. 20° E. 19.5 ft. to center. #191
30" D. Fir BT, now blown over & only a stump with an old face
visible, bears S. 53° W., 47.0 ft.
Scribed: 20" D. Fir BT with bark scribed visible bears N. 43 1/2° E. 29.1 ft.
30" D. Fir BT, with bark scribes visible bears N. 37° W., 20 ft. (face)
Scribed: 30" D. Fir BT Stamp, I scribed "S33, T30S, R2W, BT", bears
S. 5° W., 38.6 feet to face.

John M. Powell
Frank Jones & Terry Connell
August & Sept. 1966
C. S. File No. 54/28

Bruce A. Shaner
For Umpqua Nat'l. Forest
October, 1967
C.S. 55/51 RM 1 - 62