

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 2 W R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

86

1/4 Section Corner common to Sections 28 and 33.

Found - 3" Iron Pipe, 6" N. of 10x10x6" rock with old and new "1/4" mark (See Ren. #74), from which rock a:

24" D. Fir Stump, badly burnt but in right location for Collin's BT, bears S. 78° W., 99.5 feet.

16" Pine Snag, possible BT with an old face badly burnt, but no scribes visible now, bears N. 37 1/2° E., 117.5 ft. (Record N. 65 1/2° E., 78.8 ft.)

Scribed - 24" D. Fir Stump BT, I scribed "1/4 S 33 BT", bears S. 80° W., 108.0 feet.

16" Cedar BT, I scribed "T30S, R2W, S33, BT", bears S. 56 1/2° E. 153.0 ft.

24" Madrone BT, I scribed "T30S, R2W, S28, BT", bears N. 47 1/2° E., 157.7 ft.

87

Establishing CN 1/16 Corner of Section 33.

Set - Monument from which a:

26" D. Fir, I scribed "CN 1/16, S33, BT", bears N. 61 1/2° W. 83.8 ft.

32" D. Fir, I scribed "CN 1/16, S33, BT", bears N. 22° E., 118.0 ft.

88

Establishing E 1/16 on N. Section Line of Section 33.

By proportional measurement, I set a monument from which a:

30" D. Fir, I scribed "E 1/16, S28, BT", bears N. 66° E., 85.6 ft.

24" D. Fir, I scribed "E 1/16, S33, BT", bears S. 79 1/2° E., 79.4 ft.

89

Establishing NE 1/16 Corner in Section 33.

By subdividing Section 33, I set the NE 1/16 Corner, a monument, from which a:

18" D. Fir BT, I scribed "NE 1/16, S33, BT", bears S. 75° W., 12.0 ft.

26" D. Fir BT, I scribed "NE 1/16, S33, BT", bears N. 27° W., 12.7 ft.

90

Establishing the NE 1/16 Corner on the E. Line of Section 33.

By proportional measurement, I set a monument from which a:

16" D. Fir, I scribed "NE 1/16, S33, BT", bears S. 38° W., 107.0 ft.

30" Pine Stump, I scribed "NE 1/16, S34, BT", bears N. 17° E., 36.3 ft.

(SEE C.S. 62/38 FOR NEW BTs. 10/86)

91

Re-establishing 1/4 Sections 33 and 34.

By proportional measurement from the Section Corners immediately to North & South, I re-set the corner, which fell on bedrock on the South Side of Elk Creek, on which rock I scribed an "X" from which a:

16" Cedar, I scribed "1/4 S, S34, BT", bears N. 65° E., 86.8 ft.

10" D. Fir, I scribed "1/4 S, S34, BT", bears N. 16° E. 98.6 ft.

10" D. Fir, I scribed "1/4 S, S33, BT" bears N. 53° W., 111.7 ft.

No original evidence found.

92

Corner to Sections 29 and 30 only.

Found - No trace of Corner Stone, ground disturbed. Mound of stone fd.

20" D. Fir, now 36" Stump, N. 75° W. 32.3 ft., opened for scribe.

No trace of N.E. BT.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office 1967

T30S	R2 W
S 30	S 29
S 31	

New BT's: 9" Live Oak N. 85° W. 5.4 ft. mkd: T30S R2W S30 CS BT.

15" Live Oak S. 80° E. 14.2 ft. mkd. T30S R2W S31 CS BT.

No trees to N.E. in good condition.

Note - This corner lies 58.1 ft. west of Corner to Sections 31/32 & approx. 320 north of Highway #227.

FD OK
L. HERZSTADT
4.5.82
4/18/82
C.S. 61/32
6. M. 101-9 4/86
M. ARMSTRONG

RE-RENEWED CORNER NO. #244

FD OK
L. HERZSTADT
4.5.82
4/18/82
C.S. 61/32

SEE
Ren's #223 & 224

Bruce A. Shaner
Umpqua National Forest
Ocober, 1967
C. S. File No. 55/51

RM 1 - 62

John M. Powell
Frank Jones & W. Penley
Dec. 19, 1967
C. S. File No. 54/59