

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 2 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21891

286

93

Closing Corner Sections 31 and 32.
Found - 12", now 15" L. Oak, S. 24° E. 11.2 ft., opened for scribing,
found scribe marks but not legible.
12", now 23" D. Fir, S. 64° W. 33.0 ft., shows good scar.
No trace of stone, ground disturbed.

Set - Brass Cap at C.C. Mkd: County Surveyor's Office
1967

T 30 S	R 2 W
	S 29
CC	S 31 S 32

New BT: 12" Live Oak S. 29° E. 12.0 ft. mkd. T30S R2W S32 CC CS BT.
Note - This corner lies 58.1 ft. East of Cor. to Secs. 30 & 29, Ren. #92,
& approximately 320 ft. north of Highway #227. see c.s. 53/52
12/20/67

1/4 Corner to Sec. 31, T30-1W. & Sec. 36, T30-2W.
Found - Orig. 30", now 42" D. Fir, N. 86° E. 15.2 ft, opened for scribe "T".
No trace of S.W. BT.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office
1968

R T 30 S	W
	2 S 36 S 31 1
	W

New BT: 30" D. Fir N. 71° W. 68.0 ft. mkd. 1/4 S36 CS BT.
N. E. Bearing Tree in good condition. 1/9/68

Township Corner: Found Mkd: R T 29 S E
General Land Office 2 S 36 | S 31 1
1917 W S 1 | S 6 W

Found Orig. BT's: T 30 S
30" Pine, now down & burnt, S. 8° W. 24.4 ft.
18" Oak, now rotted out, N. 70° W. 37.0 ft.
18" Oak, now stob, N. 8° E. 17.5 ft.
12", now 17" Oak, S. 89° E. 118.8 ft., opened for scribe "BT".
(Fall, this tree as very rotten & would be hazard)

New BT's: 16" D. Fir N. 44° W. 26.8 ft. mkd. T29S R2W S36 CS BT.
15" D. Fir N. 73° E. 17.5 ft. mkd. T29S R1W S31 CS BT.
Reblzd. & Rescbd: 1904 BT's: 16" D. Fir S. 9° E. (Rec. S12° E.) 13.0 ft.
scribed T30S R1W S6 CS BT.
10" D. Fir S. 41° W. (Rec. S. 39° W.) 33.0 ft. mkd. T30S R2W S1 CS BT.

1/4 Cor. to Section 12 only, T30-2W. FD. OK BY NYEREN 4/95 - M121-76
Found - 10", now 18" D. Fir, S. 69° W. 17.8 ft., scribe visible "S12 BT".
5", now 6" W. Oak, N. 58° W. 31.7 ft., shows good scar.
Corner Stone with "1/4" on west face.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office
1968

R T 30 S	R
	2 S 12 1/4 1
	W

Bearing Trees O.K., tagged same.
Note - This cor. lies 33 ft. S. of 1/4 Cor. Sec. 7 only, see below and
on E-W cutting line.

1/4 Cor. to Section 7 only, T30-1W.
Found - 30", now 36" Corner Tree, tree opened "S7" visible. #246
8", now 12" B. Oak, S. 85° E. 20.5 ft., shows good scar.
18", now 22" Pine, N. 7° E. (Rec. N. 25° E.) 23.8 ft., shows good scar.

Set - Brass Cap on E. side of Corner Tree Mkd: County Surveyor's Office
1968

R T30 S	R
	2 1/4 S 7 1
	W

Bearing Trees Ok, tagged same.
Note - This corner lies 33.0 ft. north of 1/4 corner S. 12, T30-2W., see above.

1/4 Corner to Sec. 6 only, T30-2W. FD. B.C. 9/93 BY PIESKE M117-62
Found - 18x10x6 Basalt Stone, firmly in ground, "1/4" on East face.
28" Pine, now down, burnt, N. 71° E. 58.1 ft. No trace S.E. BT.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office
1968

R T 30 S	R
	2 1/4 S 6 1
	W

New BT's: 9" Pine N. 85° E. 12.0 ft. mkd. 1/4 S6 CS BT.
5" Pine S. 52° E. 3.5 ft. mkd. 1/4 S6 CS BT.
Note - This cor. lies 81.2' N. of 1/4 Sec. 1, T30-2W., see below, and lies
5 ft. south of fence corner, running N. & E.

JOHN M. POWELL
Frank Jones & W. Penley
January, 1968
C. S. File No. 54/59

FD 7/73 HAINES
SEE GIS FILE

RE-NEWED, SEE CORNER NO. #228

RE-NEWED, SEE CORNER NO. #228

RE-NEWED, SEE CORNER NO. #246