

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

105

Sec. Cor. to Sec. 19, T30-1W. and Sec. 24, T30-2W.

Corner established by Hathorn in 1857, no evidence found.

Set - 2"x30" I.P. with Brass Cap, stamped R T 30 S R  
2 1/4 S 24 | S 19 1  
W 1968 W  
OLS 536

New BT's: 16" Fir bears N.57°E. 19.4 ft. mkd. 1/4 S19 T30S R1W  
20" Fir bears West 3.5 ft. mkd. 1/4 S24 T30S R2W.

Note - place USFS BT signs on both trees, breast high, & facing pipe.

Glenn S. Baughman  
U.S.F.S.-Umpqua National Forest, Tiller  
July, 1968  
C.S. File 55/83  
Map M 36 - 12

106

1/4 Corner to Sec. 30, T30-1W and Sec. 25, T30-2W.

No evidence found of 1857 survey by Hathorn.

Set - 2"x30" I.P. with Brass Cap Mkd: ~~R T 30 S R~~ #210  
~~2 1/4 S 25 | S 30 1~~  
~~W 1968 W~~  
OLS 536

New BT's: 48" diam. Cedar bears N.12°E. 22.5 ft. mkd. T30S R1W S30 BT.  
12" diam. Fir bears S.38°W. 39.4 ft. mkd. T30S R2W S25 BT.

Note - Placed USFS BT signs on both trees, breast high, & facing pipe.

107

Sec. Cor. to Secs. 19 & 30, T30-1W and Secs. 24 & 25, T30-2W.

No evidence found of 1857 survey by Hathorn.

Set - 2"x30" I.P. with Brass Cap mkd: R T 30 S R  
2 S 24 | S 19 1  
W S 25 | S 30 W #211  
1968  
OLS 536

New BT's: 6" China. S.36°W. 23.5 ft. mkd. T30S R2W S25 BT.  
6" W. Fir S.17°E. 46.0 ft. mkd. T30S R1W S30 BT.  
24" D. Fir N.56°E. 22.4 ft. mkd. T30S R1W S19 BT.  
8" Maple N.20°W. 6.2 ft. mkd. T30S R2W S24 BT.

Note - Placed USFS BT. sign on both trees, breast high, & facing pipe.

Glenn S. Baughman  
U.S.F.S.-Umpqua National Forest, Tiller  
July, 1968  
C.S. File 55/83

108

Sec. Cor. to Sections 3 and 4, only, T30-2W.

Found - 48", now 56" Corner Tree, shows good scars.

Orig. 5" Cedar, now stob, S.89°W. 32.3 ft. No trace S.E. BT.  
Set - Brass Cap on S. Side Cor. Tree Mkd: T29S S 34  
County Surveyor's Office, 1968 T30S R2W S 4 | S 3

New BT's: 6" Cedar S.82°E. 17.0 ft. mkd: T30S R2W S3 CS BT.  
8" Red Fir S.64°W. 16.2 ft. mkd: T30S R2W S4 CS BT.  
9" W. Fir N.80°E. 7.3 ft. mkd: T29S R2W S34 CS BT.

This corner lies 26.8 ft. East of Sec. Cor. to Secs. 33 & 34, T29-2W.

John M. Powell  
Frank Jones & W. Penley  
October, 1968  
C. S. File No. 54/73

109

Section Corner to Sections 33 & 34 only, T29-2W.

Found - 12", now 18" Cedar, N.30 1/2°W. 38.9 ft., scribe visible.

14" Fir, now stump, N.5°E. 69.3 ft., scribe visible.  
Stone, approx. 15x10x8 at section corner, no notches seen.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S S 33 | S 34  
Office, 1968 T30S R2W S 4

New BT: 6" D. Fir N.24°E. 29.3 ft. scribed T29S R2W S34 CS BT.  
7" D. Fir S.13°W. 11.7 ft. scribed T30S R2W S 4 CS BT.

This corner lies 26.8 ft. W. of Cor. to Secs. 4 & 3, T30-2W, see above.

110

1/4 Corner to Sections 4 and 3.

Found - No trace of Corner Stone.

18" Cedar, now Snag, N.41°E. 4.6 ft., shows good scar.  
9" Cedar, now snag, N.19°W. (Rec. N9W) 23.1 ft., opened for scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W  
Office, 1968 1/4 S 4 | S 3

New BT's: 6" D. Fir S.15°W. 41.5 ft. scribed 1/4 S 4 CS BT.  
34" Cedar N.65°E. 20.6 ft. scribed 1/4 S 3 CS BT.

10/14/68