

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

117

$\frac{1}{4}$ Corner to Section 16.
Found - No Trace of Corner Tree nor S. E. BT.
10" Cedar, now dead, N.81°E. 46.2 ft., opened for scribe "S16".
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R2W
Office, 1968 $\frac{1}{4}$ S 16
New BT's: 12" Cedar S. 66°E. 176.3 ft. mkd: $\frac{1}{4}$ S16 CS BT.
8" Cedar S. 34°E. 140.3 ft. mkd: $\frac{1}{4}$ S16 CS BT.

118

Section Corner to Sections 17 - 18 - 19 - 20.
Found - 15x8x6 Stone at corner, no notches as described.
12" D.Fir, now down & rotten, N.42 $\frac{1}{2}$ °E. 6.6 ft., found scribing.
12", now 16" D.Fir, S.22 $\frac{1}{2}$ °E. 7.9 ft., shows good scar.
10" D.Fir, now stump, N.41 $\frac{1}{2}$ °W. 33.0 ft., shows good scar.
15", now 23" Laurel, S.34°W. 23.1 ft., shows faint scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R2W
Office S 18 | S 17
1968 S 19 | S 20
New BT's: 18" D.Fir N.49°E. 15.4 ft., mkd: T30S R2W S17 CS BT.
7" Hemlock N.23°W. 34.4 ft. mkd: T30S R2W S18 CS BT.
Note - This corner lies directly on top of large ridge, running E-W.

119

$\frac{1}{4}$ Corner to Sections 17 and 18.
Found - Stone, approx. size, no marks visible at $\frac{1}{4}$ Corner.
18", now 30" D.Fir, S.60°E. 39.6 ft., shows good scar.
12", now 26" Cedar, S.4°W. 13.9 ft., tree opened before, scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R2W
Office, 1968 $\frac{1}{4}$ S 18 | S 17
Reblzd. & Rescbd: 26" Cedar S. 4° W. 13.9 ft. mkd: $\frac{1}{4}$ S18 CS BT.

120

Section Corner to Sections 17 and 18 only.
Found - No trace of corner stone.
12", now 17" D.Fir, S.38°E. 22.4 ft., shows good scar.
12" Hemlock, now dead, S.13°W. 33.7 ft., scribe visible "S18".
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R2W
Office S 7
1968 S 18 | S 17
New BT's: 10" Hemlock S.54°W. 12.6 ft. mkd: T30S R2W S18 CS BT.
11" Cedar N.20°E. 24.2 ft. mkd: T30S R2W S7 CS BT.
This corner lies east of creek, about 50 ft.

121

Section Corner to Sections 7 and 8 only.
Found - 16x16x4 Stone with 5 notches, out of ground.
16" D.Fir, now stump, N.53°E. 39.6 ft., found scribe.
No trace of N.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R2W
Office S 7 | S 8
1968 S 17
New BT's: 11" Hemlock S.47°E. 29.1 ft. mkd: T30S R2W S17 CS BT.
13" D.Fir N. 7°E. 19.0 ft. mkd: T30S R2W S8 CS BT.
10" Hemlock N.16°W. 67.4 ft. mkd: T30S R2W S7 CS BT.

122

$\frac{1}{4}$ Corner to Section 30 and 29.
Found - Basalt Stone, 14x10x4, firmly in ground, mkd: " $\frac{1}{4}$ " on West face.
20" Oak, now down & burnt, N.4°E. 280.3 ft., found scribing.
20" Oak, now down & burnt, N.2 $\frac{1}{2}$ °W. 340.6 ft., found scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R2W
Office, 1968 $\frac{1}{4}$ S 30 | S 29
New BT's: 12" S.Pine N.74°W. 54.7 ft. mkd: $\frac{1}{4}$ S30 CS BT.
30" S.Pine S.85°E. 208.0 ft. mkd: $\frac{1}{4}$ S29 CS BT.
Set Steel Fence Post alongside Brass Cap as corner lies on S. slope
in large opening.

10/31/68

Fd OK
12/95-286
H. Johnstone
M100-21

John M. Powell
Frank Jones & W. Penley
October, 1968
C. S. File No. 54/73