

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

130

1/4 Corner to Section 35 only, T29-2W.  
Found - 15", now 22" D. Fir, N. 56 1/2° E. 45.5 ft., shows good scar.  
15", now 22" W. Fir, N. 51° W. 38.3 ft., opened for scribing.  
No trace of 1917 Brass Cap at Corner falls in cut for old  
skid road which comes directly down section line.

Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W 1/4 S 35  
Office, 1968 T30S

All Bearing Trees in good condition & tagged.  
This corner lies 39.1 ft. west of 1/4 Cor. Sec. 2, T30S-R2W.

131

Section Corner to Sections 35 and 36, T29-2W.  
Found - Stone approx. size found at corner, but no marks found.  
30" D. Fir, now down, N. 45 1/2° E. 12.5 ft., scribe visible.  
No trace of N.W. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W 1/4 S 35 | S 36  
Office, 1968 T30S

New BT's: 24" D. Fir North 38.0 ft. mkd: T29SR2WS36 CS BT.  
20" D. Fir N. 10° W. 25.7 ft. mkd: T29SR2WS35 CS BT.  
8" W. Fir; S. 24° W. 18.6 ft. mkd: T30S R2W S 2 CS BT.

Section Corner to Sections 1 and 2, T30-2W.  
Found - Stone at corner approx. size & 5 grooves on the west side.  
5" W. Fir, now dead, S. 11° E. 23.8 ft. scribe visible.  
15" D. Fir, now down, S. 43° W. 56.1 ft., shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W 1/4 S 2 | S 1  
Office, 1968 T30S

New BT's: 7" W. Fir S. 12° W. 34.4 ft. mkd: T30SR2WS2 CS BT.  
9" W. Fir S. 4° E. 43.0 ft. mkd: T30SR2WS1 CS BT.  
15" D. Fir N. 47° W. 14.7 ft. mkd: T29SR2WS26CS BT.

132

North 1/4 Corner to Section 32 only.

Found - Stone at 1/4 corner mkd. with an "X", See Ren. #10, T30-2W.  
20" D. Fir, now stump, S. 5° E. 21.1 ft., scribe visible.  
12" D. Fir, now stump, S. 84° E. 21.3 ft., scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W  
Office 1968 1/4 S 32

New BT's: 8" D. Fir S. 46° W. 37.2 ft. mkd: 1/4 S32 CSBT.  
9" D. Fir S. 50° E. 11.8 ft. mkd: 1/4 S32 CS BT.  
This corner lies 29.0 ft. East of 1/4 Corner to Section 29, see below.

133

South 1/4 Corner to Section 29, T30-2W.  
Found - Stone at Corner Mkd. with "X", See Ren. #9.  
Orig. 8", now 14" Fir, N. 41° W. 16.5 ft., opened, scribe visible.  
Orig. 8", now 27" D. Fir, N. 5° E. 9.2 ft.  
10", now 12" D. Fir, N. 24° E. 13.1 ft., shows good scar.  
18", now 18" D. Fir, N. 56 1/2° W. (Rec. N45W) 33.3 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W  
Office 1968 1/4 S 29

All Bearing Trees O.K. and Tagged.  
This corner lies 29.0 ft. W. of 1/4 Cor. Sec. 32, see above.

134

1/4 Corner to Sections 19 and 20.  
Found - Stone at 1/4 Cor. approx. size but no marks.  
9", now 11" D. Fir, S. 88° W. 8.6 ft., scribing visible.  
36", now 40" D. Fir, N. 33 1/2° E. 26.4 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W  
Office, 1968 1/4 S 19 | S 20

All Bearing Trees O. K. and Tagged.

135

John M. Powell  
Jack Heritage & W. Penley  
November, 1968  
C.S. File No. 54/73

RE-RENEWED, SEE CORNER NO. #219

Fd 7/73 HAWK  
FOR BLM  
SEE GIS FILE

BOOK  
495 Mark  
M 121-77  
Fd. by Ruppert  
February, 1984  
M 96-39