

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. B. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

136

South $\frac{1}{4}$ Corner to Section 36 only, T29-2W
Found - GLO Brass Cap properly marked in 1917.
10", now 12" D. Fir, N. 45° E. 11.9 ft., shows scar, badly
scared by logging.
14", now 17" D. Fir, N. 37° W. 31.0 ft., shows good scar.
New BT: 16" W. Fir N. 51° E. 23.1 ft. mkd: $\frac{1}{4}$ S36 CS BT.
This corner lies 25.7 ft. west of $\frac{1}{4}$ Cor. Sec. 1, T30-2W, see below.

RENEWED, SEE CORNER NO. #267

137

$\frac{1}{4}$ Corner to Section 1 only, T30-2W.
Found - Stone at $\frac{1}{4}$ corner, approx. size, no marks visible.
8" D. Fir, now stump, S. 20° E. 30.4 ft., opened for scribe.
No trace of S.W. Bearing Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W $\frac{1}{4}$ S 1
Office, 1968 T30S
New BT's: 10" W. Fir S. 21° E. 23.7 ft. mkd: $\frac{1}{4}$ S1 CS BT.
9" W. Fir S. 24° W. 28.3 ft. mkd: $\frac{1}{4}$ S1 CS BT.
This corner lies 25.7 ft. east of $\frac{1}{4}$ Cor. Sec. 36, T29-2W, see above.

FD 7/13 HAINES
FOR G.I.S. FILE

138

$\frac{1}{4}$ Corner to Section 2 only, T30-2W.
Found - No trace of stone or S.E. BT.
20" D. Fir, now stump, S. 84° E. 34.4 ft., opened for scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W $\frac{1}{4}$ S 2
Office, 1968 T30S
New BT's: 10" Hemlock S. 22° E. 15.8 ft. mkd: $\frac{1}{4}$ S2 CS BT.
10" Hemlock S. 72° W. 48.4 ft. mkd: $\frac{1}{4}$ S2 CS BT.
This corner lies 39.1 ft. east of $\frac{1}{4}$ Sec. 35, T29-2W., Ren. #130.

RENEWED, SEE CORNER NO. #271

139

$\frac{1}{4}$ Corner to Sections 1 and 2.
Found - Stone at $\frac{1}{4}$ corner, 5x10x10, "1" on west face, See Ren. #29.
18" D. Fir, now down, N. 84 $\frac{1}{2}$ ° W. 21.9 ft., scribe visible.
40", now 40" S. Pine, N. 30° E. 47.6 ft., pitched over, scribe visible.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's T 30 S R 2 W
Office, 1968 $\frac{1}{4}$ S 2 S 1
New BT: 18" Fir N. 53° W. 86.8 ft. mkd: $\frac{1}{4}$ S2 CS BT.
This corner lies on top of large ridge, running NE.

FD 7/13 HAINES
FOR G.I.S. FILE

John M. Powell
Jack Heritage & W. Penley
November, 1968
C. S. File No. 54/73

140

Section Corner to Sections 5 - 6 - 7 - 8.
Found - 1" I. Pipe at corner, See Ren. #13.
Orig. 16", now 22" Laurel, N. 86° E. 19.8 ft., face & scribing rotten.
Orig. 18", now 28" D. Fir, S. 40 $\frac{1}{2}$ ° E. 26.4 ft., shows good scar,
Also bark scribe "S8 BT".
Orig. 8", now 12" Laurel, S. 23 $\frac{1}{2}$ ° W. 25.1 ft., rotten face & scribe.
Orig. 16", now 24" Laurel, N. 66° W. 17.8 ft., shows scar.
New BT's: 5" D. Fir S. 16° W. 7.5 ft. mkd: S 7 CS BT.
11" Laurel North 19.4 ft. mkd: T30S R2WS5 CS BT.
All Tree tagged. This corner lies on top of ridge running N - S.

141

$\frac{1}{4}$ Corner to Sections 11 and 12. FD OK 4/95 BY NYGREN M121-76
Found - 16" D. Fir, now stump, N. 31 $\frac{1}{2}$ ° W. 25.1 ft., scribe visible.
16" D. Fir, now stump, N. 60° W. 16.5 ft., opened for scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W
Office, 1968 $\frac{1}{4}$ S 11 | S 12
New BT's: 16" D. Fir S. 72° W. 60.9 ft. mkd: $\frac{1}{4}$ S11 CS BT.
14" D. Fir S. 84° E. 29.8 ft. mkd: $\frac{1}{4}$ S12 CS BT.

142

$\frac{1}{4}$ Corner to Section 2 and 11.
Found - No trace of Stone at $\frac{1}{4}$ corner.
16" D. Fir, now stump, N. 37° W. 21.8 ft., opened stump for scribng.
24" D. Fir, now stump, S. 61° W. 14.5 ft., shows good scar.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's T 30 S R 2 W
Office 1968 S 2
S 11
New BT's: 10" Cedar S. 71° W. 17.4 ft. mkd: $\frac{1}{4}$ S11 CS BT.
8" Cedar N. 42° W. 20.8 ft. mkd: $\frac{1}{4}$ S 2 CS BT.

11/15/68