

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 2 W. R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21001

143

Section Corner to Sections 1 - 2 - 11 - 12.
Found - Stone, approx. size, no marks.
8", now 13" D. Fir, N. 46 $\frac{1}{2}$ ° E. 12.5 ft., shows good scar.
36" D. Fir, now stump, S. 50° E. 38.9 ft., scribe visible.
12", now 16" D. Fir, S. 59° W. 23.8 ft., shows good scar.
6", now 10" Laurel, N. 29° W. 29.0 ft., faint rotten scribing visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 T 30 S R 2 W
S 2 | S 1
S 11 | S 12
New BT: 9" Laurel S. 32° E. 38.5 ft. mkd: T30S R2W S12 CS BT.
Reblzd. & Rescbd: 10" Laurel N. 29° W. 29.0 ft. mkd: T30S R2W S2CS BT.

144

$\frac{1}{4}$ Corner to Sections 21 and 22.
Found - 16", now 23" Cedar N. 51° W. 35.6 ft., shows good scar. #273
28" Pine, now stump, N. 52° E. 19.1 ft. (Rec. 20.5) burnt scribing
visible and other marks
Stone, approx. size but with "+" on top instead of " $\frac{1}{4}$ ".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T 30 S R 2 W
 $\frac{1}{4}$ S 21 | S 22
New BT: 40" D. Fir S. 80° E. 96.7 ft. mkd: $\frac{1}{4}$ S21 CS BT.

145

$\frac{1}{4}$ Corner to Section 14 and 13. (Witness Corner)
Found - 12", now 22" Laurel, N. 2° E. 20.5 ft., opened earlier but
below face, opened high for "BT".
No trace of N.W. BT.
 $\frac{1}{4}$ corner point falls on rock face, unable to set corner at proper point.
Set - Wit. Cor. Brass Cap Mkd: County Surveyor's Office 1968 T 30 S R 2 W
Wit. Cor. 5' South to
 $\frac{1}{4}$ S 14 | S 13
New BT's: 14" Cedar N. 60° W. 18.6 ft. mkd: W.C. $\frac{1}{4}$ S14 CS BT.
16" D. Fir S. 43° E. 19.6 ft. mkd: W.C. $\frac{1}{4}$ S13 CS BT.
This corner lies just north of small rock outcrop.

146

$\frac{1}{4}$ Corner to Section 13 and 24.
Found - Stone 6x9x20" at $\frac{1}{4}$ corner, also post, mkd: " $\frac{1}{4}$ ", see Ren. #20.
20", now 28" D. Fir, N. 40° W. 6.7 ft., bark scribed.
36", now 40" D. Fir, S. 10° E. 41.0 ft., bark scribed.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 T 30 S R 2 W
 $\frac{1}{4}$ S 13
S 24
Reblzd. & Rescbd: 28" D. Fir N. 40° W. 6.7 ft. mkd: $\frac{1}{4}$ S13 CS BT.
40" D. Fir S. 10° E. 41.0 ft. mkd: $\frac{1}{4}$ S24 CS BT.
11/14/68

147

$\frac{1}{4}$ Corner North Side of Section 17.
Found - Stone, appr. 12x7x7, mkd: " $\frac{1}{4}$ ".
18", now 28" Cedar, S. 49 $\frac{1}{2}$ ° E. 23.8 ft., shows good scar.
40", now 50" D. Fir, S. 67° W. 19.8 ft., shows good scar.
All Bearing Trees O. K. and Tagged.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 T 30 S R 2 W
 $\frac{1}{4}$ S 17

148

$\frac{1}{4}$ Corner South Side of Section 8.
Found - Stone at $\frac{1}{4}$ corner mkd: with X on top. No other marks.
24" D. Fir, now stump, N. 41 $\frac{1}{2}$ ° W. 21.8 ft., opened for scribing, "B".
12" Maple, now rotten, N. 40° E. 29.0 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T 30 S R 2 W
 $\frac{1}{4}$ S 8
New BT's: 9" Hemlock N. 2° W. 24.6 ft. mkd: $\frac{1}{4}$ S8 CS BT.
11" Hemlock N. 67° W. 21.2 ft. mkd: $\frac{1}{4}$ S8 CS BT.

John M. Powell
Jack Heritage & W. Penley
November, 1968
C. S. File No. 54/73

RE-RENEWED, SET CORNER NO. #242