

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 2 W. R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

149

1/4 Corner to Section 33 only, T29-2W.
Found - GLO Brass Cap properly marked in 1917.
12", now 15" Cedar, N.20 1/2° E. 69.3 ft., scribe visible.
28" D. Fir, now stump, N.56° W. 48.2 ft., shws. good scar.
New BT: 10" Hemlock N.49° W. 34.5 ft. mkd: "1/4 S33 CS BT."
This corner lies 42.2 ft. W. of 1/4 Cor. Sec. 4, T30-2W, see below.

150

1/4 Corner to Section 4 only, T30-2W.
Found - No trace of stone at corner.
32" D. Fir, now stump, S.20° E. 24.4 ft., opened for scribe.
14", now 26" Cedar, S.20° W. 31.9 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W 1/4 S 4
Office, 1968 T30S
New BT: 6" Hemlock S. 2° E. 19.0 ft. mkd: "1/4 S4 CS BT".
This cor. lies 42.2' E. of 1/4 Sec. 33, T29-2, see above.

151

Section Corner to Sections 32 & 33 only, T29-2W.
Found - Stone, approx. size, 4 notches E., 2 notches W.
36", now 39" D. Fir, N.21° E. 33.7 ft., shows good scar.
15", now 19" Fir, N. 64 3/4° W. 37.0 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W 1/4 S32/S33
Office, 1968 T30S
New BT: 14" Cedar S.20° E. 28.6 ft. mkd: T30S R2W S5 CS BT.
This corner lies 62.7 ft. W. of Cor. Secs. 5 & 4, T30-2, below.

152

Section Corner to Sections 5 and 4 only, T30-2W.
Found - No trace of Stone at section corner.
30", now 38" D. Fir, S.29° E. 4.0 ft., shows good scar.
12", Cedar, now stob, S.22 1/2° W. 13.9 ft., opened for scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W 1/4 S 5 | S 4
Office, 1968 T30S
New BT's: 14" Hemlock S.64° W. 39.7 ft. mkd: T30S R2W S5 CS BT.
8" Fir N.34° W. 10.0 ft. mkd: T29S R2W S33 CS BT.
This corner lies 62.7 ft. E. of Secs. 32 & 33, above.

153

Section Corner to Sections 34 & 35 T29-2W.
Found - Stone at corner mkd: 2 notches on E. and 4 on W.
40", now 45" D. Fir, N.12 1/2° W. 31.0 ft., shows good scar.
24" Fir, now stob, N.32 1/2° E. 37.6 ft. scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W S 34 S 35
Office, 1968 T30S S 3

154

Section Corner to Sections 3 and 2, T30-2W.
Found - Stone at corner mkd: + on top, Rec. Dist. 33.7 E. of #153, above.
10", now 26" R. Fir, S.66 1/2° W. 15.2 ft., shows good scar.
6" Fir, now down laying on face, S.32 3/4° E. 15.2 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R2W S 35
Office, 1968 T30S S 3 S 2
New BT's: 7" D. Fir S. 71° E. 26.5 ft. mkd: T30S R2W S2 CS BT.
12" Hemlock N.14° E. 13.6 ft. mkd: T29S R2W S35 CS BT.

155

1/4 Corner to Section 3 only, T30-2W.
Found - Stone at 1/4 corner approx. size mkd: "1/4" on N. side.
18", now 30" R. Fir, S.13° E (Rec. S1W) 31.7 ft., shows good scar.
14", now 20" R. Fir, S.25° W. 29.7 ft., shows good scar.
Record Distance of 26.4 ft. E. of 1/4 Sec. 34, T29-2W, see below.

156

1/4 Corner to Section 34 only, T29-2W.
Found - GLO Brass Cap properly marked in 1917.
14", now 26" D. Fir, N.18° E. 34.3 ft., no scar visible.
18", now 26" R. Fir, N.72 1/2° W. 19.8 ft., shows scar.
Reblazed & Rescribed: 26" D. Fir N.18° E. 34.3 ft. mkd: 1/4 S34 CS BT.

11/26/68

John M. Powell
Jack Heritage & W. Penley
November, 1968
C. S. File No. 54/73