# Douglas County Surveyor's Record of Government Corners Renewed

T. 30 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Jack Heritage & W. Penley
December, 1968 C.S. File No. 54/73

FD OK BY G. Lang 7/94 M120-69

157

¼ Corner to Sections 27 and 34.
Found - 12",now 17" Oak, tree opened, N.55°W. 120.8 ft., scribe visible.
18" Oak, now down, S.38°W. 68.6 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 — T 30 S R 2 W: S 27 / S 34
New BT's: 22" D.Fir S.17°W. 7.5 ft. mkd: "¼ S34 CS BT".
15" D.Fir N.32½°W. 21.8 ft. mkd: "¼ S27 CS BT".

– – – – – – –

158

Section Corner to Sections 26 - 27 - 34 - 35.
Found - 15", now 20" S.Pine, S.81°W. 285.8 ft., scribe visible, BT scar, tree opened.
15" Fir, now stump, N.89°W. 351.8 ft., shows good scar.
No trace of N.E. or S.E. Bearing Trees.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 — T 30 S R 2 W: S 27 | S 26 / S 34 | S 35
New BT's: 19" S.Pine N. 5° W. 94.1 ft. mkd: T30S R2W S27 CS BT.
12" D.Fir N. 2° E. 103.0 ft. mkd: T30S R2W S26 CS BT.
14" D.Fir S.81°E. 74.4 ft. mkd: T30S R2WS35 CS BT.
This corner lies 15.0 ft. south of telephone line running NE - SW.

#245 RE-RENEWED, SEE CORNER NO.

– – – – – – –

159

¼ Corner to Sections 28 and 27.
Found - 30" Pine, now stump, N.38°W. 32.5 ft., See Ren. #26.
30" D.Fir, now stump, N.40½°E. 37.0 ft., bark scribe visible.
Set - Brass Cap at ¼ Cor.Mkd: County Surveyor's Office, 1968 — T 30 S R 2 W: ¼ S 28 | S 27
New BT's: 14" D.Fir West 10.5 ft. mkd: ¼ S28 CS BT.
17" D.Fir N.63°E. 12.3 ft. mkd: ¼ S27 CS BT.

– – – – – – –

FD OK PER BENTZ M.110-16 5/90

160

Section Corner to Sections 21 - 22 - 27 - 28.
Found - Stone firmly set at corner marked with grooves.
Orig. 16" B.Oak, now 16", N.44½°W. 13.2 ft., shows good scar
8",now 10" D.Fir S.64°E. 20.3 ft., shows good scars. Ren. #58.
16",now 16" D.Fir, N.70½°E. 46.9 ft., to face., pitched over scribe visible.
22" D.Fir S.55°W. 34.3 ft. to face, pitched over scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 — T 30 S R 2 W: S 21 | S 22 / S 28 | S 27
All Bearing Trees O. K. and Tagged.

– – – – – – –

FD OK PER BENTZ M.110-16 5/90

161

¼ Corner to Sections 22 and 27.
Found - 2 x 4 scribed Post, "¼S CS", No trace of I. Pipe, See Ren. #17.
26", now 32" Cedar, S.25°W. 13.5 ft., shows good scar.
6",now 14" D.Fir, north 5.7 ft., tree opened, scribe marks visible.
Logged to the west, probably when I.P. was pulled.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 — T 30 S R 2 W: ¼ S 22 / S 27
All BT's. O.k. and Tagged.

– – – – – – –

162

¼ Corner to Sections 21 and 28.
Found - Stone, approx. size, firmly in ground, with + on top, no marks visible.
18",now 26" Hemlock, S.57°E. 14.5 ft., tree opened, scribe visible.
No trace of N.W. Bearing Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 — T 30 S R 2 W: ¼ S 21 / S 28
New BT's: 16" Hemlock N.22°W. 13.3 ft. mkd: ¼ S21 CS BT.
Reblzd. & Rescbd: 26" Hemlock S.57°E. 14.5 ft. mkd: ¼ S28 CS BT.

#278 RE-RENEWED, SEE CORNER NO.

12/2/68

– – – – – – –