

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

163

1/4 Corner to Sections 5 and 8.
Found - No trace of Corner Stone.
Orig. 30", now 30" D. Fir, North 19.8 ft., shows good scar.
16", now 18" Laurel N. 69° W. 29.4 ft., scribe visible, "1/4 S". *REN. #28*
5", now 8" Cedar, S. 16° E. 14.0 ft. scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W
Office 1/4 S 5
1968 S 8

All Bearing Trees O. K. & Tagged.

164

1/4 Corner to Sections 8 and 9.
Found - Stone, approximate size marked "1/4".
12", now 16" Maple, S. 53 1/2° W. 5.9 ft., found scribing "8",
tree opened earlier.
No trace of N. E. Bearing Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W
Office, 1968 1/4 S 8 | S 9
New BT's: 8" D. Fir N. 60° E. 54.0 ft. mkd: 1/4 S 9 CS BT.
8" R. Fir N. 65° W. 32.7 ft. mkd: 1/4 S 8 CS BT.

165

Section Corner to Sections 4 - 5 - 8 - 9.
Found - Stone 15x10x5, firmly set at corner, marked with 5 notches
on south and 4 notches on east.
48" D. Fir, now stob, N. 31° E. 22.4 ft., shows good scar,
partly opened, faint burnt scribe marks.
6", now 16" Maple S. 60° E. 38.3 ft., shows scar.
No trace of S.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W
Office 1968 S 5 | S 4
S 8 | S 9
New BT's: 10" D. Fir N. 57° E. 16.8 ft. mkd: T30S R2WS4 CS BT.
9" D. Fir N. 7° W. 46.7 ft. mkd: T30S R2W S5 CS BT.
14" D. Fir S. 69° W. 123.5 ft. mkd: T30S R2W S8 CS BT.

166

1/4 Corner to Sections 6 and 7.
Found - Corner Stone & 1" Iron Pipe at 1/4 Corner, See Ren. #14.
Orig. 26" Pine N. 80° E. 40.0 ft., shows scar.
26" Pine, now down, S. 86° E. 149.0 ft., scribe visible.
8" Laurel, now 16" Double, N. 3° E. 32.6 ft., bark scribe
visible and other faint marks.
New BT's: 25" D. Fir West 89.3 ft. mkd: 1/4 S 7 CS BT.
Reblzd. & Rescbd: 16" Double Laurel N. 3° E. 32.6 ft., mkd: 1/4 S 6 CS BT.

167

Section Corner (Closing Corner) to Section 16 & 21 only.
Found - Stone 16x10x8 set firmly with C C on East face.
30", now 37" D. Fir, N. 25° E. 25.1 ft., shows good scar.
24", now 29" D. Fir, S. 72° E. 12.5 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W
Office 1968 S 20 | S 16 C.C.
S 21

All Bearing Trees O. K. and Tagged.
This corner lies 100 ft. south of Sec. Cor. 17 and 20, see below.

168

Section Corner to Sections 17 and 20.
Found - No trace of stone.
20", now 26" D. Fir, S. 54° W. 15.8 ft., shows good scar, we open
and find scribe.
40", now 48" D. Fir, N. 35° W. 33.7 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 2 W
Office 1968 S 17 | S 16
S 20
All Bearing Trees O. K. and Tagged.
This corner lies 100 ft. north of C. C. Sections 16 and 21, see above.
12/5/68

John M. Powell
Jack Heritage & W. Penly
December, 1968 C.S. File No. 54/73