

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

198

1/4 Corner For Sec. 33 only.

Found - County Surveyor 1966 BCIP mkd. 33 Ren. 780

BT's - 30" Cedar N.19°W., 12.2 ft. OBT
5" Hemlock, N73 1/2°E., 26.3 ft. County BT
28" Fir, S.2 1/2°W., 6.5 ft. OBT.

Changed cap to read "Sec. 33 only".

RE-RENEWED, SEE CORNER NO. #269

199

1/4 Corner For Sec. 4 only, T31 - 2.

Set - 5/8" x 30" Iron Rod & Alum. Cap.

BT's - 32" Fir, S.8 1/4°W., 21.0 ft.

5" Oak, S.56 1/2°W., 20.4 ft.

7/15/76

1/4 Corner for Sec. 36 only, T30-3.

Found - A 7" Maple bears N.60 1/4° W., 14.5 ft. Tree is dead & shows old opened face. Rotted & no visible scribing.

A 6" now 8" Laurel stump bears N.28 1/4°E., 15.8 ft. No visible scribing.

The intersecting point from above BT's places cor. point approx. .10 chs. North of an east-west ravine as per orig. line notes. Also found orig. Fir line tree approx 4.40 chs. North of cor. point. At the cor. point, we find a 40" windfall making it impossible to occupy. We set a witness corner:

Set - 1" x30" iron pipe with brass cap stamped:

Douglas Co. Surveyor Witness Corner
1976 T 30 S

R 3 W R 2 W
S 36

South
1/4 47.3' ↓

New BT's A 7" W. Fir, bears S.84 1/2°W., 9.8 ft. mkd. "WC 1/4 S36 CS BT" in a double blaze.

An 8" D. Fir, bears S.40 1/2°E., 11.9 ft. mkd. "WC 1/4 RP CS BT" in a double blaze.

9/8/76

Closing Corner only for Sec. 31 and Sec. 36 of T30-3.

Found - An orig. 26" now 36" Fir, bears N.59 1/2°E., 64.5 ft. (Rec. 67.3')
Alive & well. Shows good scar.

An orig. 30" now 36" Cedar, bears N.16 1/4°W., 48.5 ft. Tree is alive and shows good scar.

An orig. 29" now 31" stump that bears S.82 1/2°E., 24.4 ft. Visible scribing showing.

Set - A 1" x 30" Iron pipe with brass cap stamped:

Douglas County Surveyor T 30 S
1976

R 3 W R 2 W
S 36 S 31

Closing
Corner

New BT - A 12" Hemlock bears N.80°E., 34.3 ft. mkd. "T30S R2W S31 CS BT" in a double blaze.

9/14/76

1/4 Corner for Secs. 34 and 35.

Found - 3" x 3" Fir post laying down, not of record, 4.0 ft. South, 0.5 ft. East of corner as set from B.T.

A Pine log and stump bears S.15°E., 141.9 ft. with fragmentary scribing at top of blaze "1/", appears to be portion of 1/4.

Remains of Pine stump with previously opened blaze bears N.5°30' E. 186.9 ft. but exact orig. standing place not determined. Both BT's are in small creek.

Set - Brass cap marked "Douglas County Surveyor" T 30 S R 2 W
1977 1/4 S 34 S 35

at record bearing and distance from only BT.

New BT's- A 27" D. Fir bears S.57 1/2°E., 46.0 ft. double blazed and scribed "1/4 S35 CS BT".

A 12" D. Fir bears S.41°W., 7.5 ft. double blazed and scribed "1/4 S34 CS BT".

5/3/77

Howard Johnstone
For: Roseburg Lbr.
July 15, 1976
M 56 - 49

A. Victor Cangie
Pete Earle
Doug. Co. Surveyor's Office
Sept. 8, 1976
C. S. 59/24

A. Victor Cangie
Jim Cook
Mike Tompkins
Doug. Co. Surveyors
Office
Sept. 14, 1976
C.S. 59/24

L. E. Monrean
R. B. Kimberling
Doug. Co. Surveyors
Office
May 3, 1977
C.S. 59/34

FD OK
BIG Long
M120-69
7/94

202
- Code. See entry chert

JAN 78