

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30 T. S. R 2 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97101

Glenn Baughman  
For: U.S. Forest  
Service  
February, 1978  
M 65 - 56

1/4 Corner for Secs. 26 and 35.  
Found - 14" D. Fir (orig.) bears S.45°W., 2.0 ft. down & rotted.  
Set - 2" x 30" I.P. with brass cap stamped:T30S F2W WM 1/4  
S26 S35 1978 OLS 536.  
New BT's-26" D. Fir bears N.70°E., 21.5 ft. scribed 1/4 S26 BT.  
8" D. Fir bears S.3°W., 18.8 ft. scribed 1/4 S35 BT.  
2/78

203

Center 1/4 Corner for Sec. 35.  
Set - 2" x 30" I.P. with brass cap stamped T30S R2W WM C1/4 S35  
1978 OLS 536.  
BT's- 30" Cedar bears N.44°E., 13.8 ft. scribed C 1/4 S35 BT.  
22" Cedar bears N.25°W., 20.7 ft. scribed C 1/4 S35 BT.  
2/78

204

Section corner for Secs. 33 and 34; and 4 & 3 of T31-2  
Found - 1966 County Surveyors brass cap Ren. #79  
14" D. Fir bears N.62°E., 54.0 ft.  
24" D. Fir bears S.70°W., 8.6 ft.  
42" Fir bears N.70°W., 11.2 ft.  
18" D. Fir bears S.20°E., 7.9 ft. (snag)  
20" D. Fir bears S.10°E., 14.8 ft.  
8" Cedar bears N.35°W., 15.2 ft. (now down)  
15" Cedar corner tree.  
New BT - 12" D. Fir bears N.12°W., 33.4 ft. scribed T20S R2W S33 BT.  
3/78

205

Glenn Baughman  
PLS 536  
For: U.S. Forest  
Service  
March 1978  
M 65 - 69

1/4 Corner for Sec. 34 and Sec. 3 of T31-2  
Set - 2" x 30" I.P. with brass cap stamped T30S R2W WM 1/4 S34 S3 T31S  
1978 OLS 536.  
BT's- 12" Pine bears S.28°W., 349.6 ft. scribed 1/4 S3 BT.  
12" Double Cedar bears N.48°W., 38.0 ft. scribed 1/4 S34 BT.  
3/78

FOOK  
BY G L 997 7/94 M122-206

206

SEE C.S. 62/15 FOR  
COUNTY INVESTIGATION  
OF CORNER.  
12/18/83 J.R.

Center 1/4 Corner for Sec. 27  
Set - 2" x 30" I.P. with brass cap marked "T30S R2 W WM  
C 1/4 + S27 1978 OLS 536.  
BT's- 16" D. Fir bears S.32°W., 14.5 ft. scribed C 1/4 S27 BT.  
8" D. Fir bears N.83°E., 10.9 ft. scribed C 1/4 S27 BT.  
4/78

207

Glenn Baughman  
LS #536  
For: U.S. Forest  
Service  
April 1978  
M 65 - 78

1/4 Corner for Secs. 27 and 26  
Set - 2" x 30" I.P. with brass cap stamped T30S R2W WM 1/4 S27 S26  
1978 OLS 536.  
BT's - 10" S. Pine bears S.47°W., 43.5 ft. scribed 1/4 S27 BT.  
7" D. Fir bears N.86°E., 28.4 ft. scribed 1/4 S26 BT.  
4/78

208

Glenn S. Baughman  
L.S. #536  
For: U.S. Forest Serv.  
Filed May 23, 1978  
C.S. 58/153

Section Corner for Secs. 18 & 19; and Secs. 13, 24 of T30-1.  
Found - A 1" I.P. with 2 1/2" brass cap 14" above ground.  
8" D. Fir stob bears S.9°E., 7.9 ft. (Rec. S.14°E.) scribe  
visible open blaze. Ren. #104  
20" D. Fir bears S.53 1/2°E., 14.8 ft. bark scribes visible.  
24" D. Fir bears N.56°E., 20.0 ft. bark scribes visible.  
18" D. Fir stump bears S.79°W., 19.4 ft. bark scribes visible.  
24" D. Fir bears N.62°W., 48.2 ft. bark scribes visible.  
6" x 8" x 5" high stone buried alongside 1" I.P.  
New BT - A10" Madrone bears S.74°W., 18.0 ft. scribed "T30S R2W S24 BT"  
on a double blazed face.  
Corner lies at the foot of a very steep north slope and 50 ft. south of  
dirt road built recently. Corner has been run over by Cat. during logging  
and Iron pipe is badly bent.

209

FO OK, Dec '94, M121-45

1/4 Corner for Sec. 25 and Sec. 30 of T.30-1.  
Found - 1968 Brass Cap set by Baughman and Ackaret. Ren. #106  
48" Cedar stump bears N.12°E., 22.7 ft.  
No BT in SW 1/4.  
New BT's- 8" D. Fir bears S.9°W., 34.2 ft. scribed 1/4 S25 BT.  
9" D. Fir bears N.51°E., 51.0 ft. scribed 1/4 S30 BT.

210

Glenn Baughman  
L.S. #536  
For: U.S. Forest SER  
May 1978  
M 70-15