

Douglas County Surveyor's Record of
Government Corners Renewed

T 30

T. S.

R 2

R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

217

Dennis Gaylord
USFS
Deputy, Douglas Co.
Surveyors Office
Witness: James
Davis
Aug. 30, 1978
C.S. 60/11

1/4 Corner for Section 13 only. (north)
Found - 1" x 30" Iron pipe set firmly alongside a 6" x 8" x 12" stone.
Orig. BT, a 23" D. Fir stump bears S.77°E., 33.6 ft. scribing
visible on previously opened blaze, "S 13 BT"
A 17" Cedar bears N.17°W., 27.4 ft. scribing visible on a
partially healed blaze, "BT 1/4 S" on a single blaze. Ren. #54
A 12" Fir stump bears S.2°W., 51.2 ft. scribing visible, "B".
Set - I reference the iron pipe and moving it aside, I replace it
with a 1 1/2" iron pipe with a 2 1/2" brass cap attached and
stamped: County Surveyor's Office T30S R2W 1/4 S13 1978.
I bury the stone and 1" pipe alongside the brass cap.
New BT's - A 6" D. Fir bears S.33°30'E., 46.0 ft. scribed "1/4 S13 CS
BT" on a double blaze.
I placed County BT signs on all BTs and BT stumps.
Local attraction created by a steel fence post setting 1.2 ft. east of
corner.

8/30/78

1-79

218

William Ruppert
LS #866
For: U.S. Forest
Service
Feb. 1979
C.S. 58/176

Closing Corner for Secs. 5 and 4 only, T.31-2
Found - 42" D. Fir corner tree.
A 1" Iron pipe and 1966 County Surveyors Office Brass cap attached
properly marked, is next to south side of tree. Ren. #81
24" Madrone, S. 5 1/2°W., 18.4 ft. scribe visible.
Set - No suitable bearing trees in Southeast quadrant
Set 6 foot steel fence post approx. 2 feet into the ground and
attached bearing tree sign. Painted top of post red. Post
bears S.70 3/4°E., 17.8 ft. from corner tree.

2/79

219

Glenn Baughman
For: U.S. Forest
Service
April, 1979
C.S. 58/176

Section Corner for Secs. 35 and 36 only. (South, for T.29-2 only.)
Found - 1" Iron pipe with 1968 County brass cap. Ren. #131
10" White fir, S.24°W., 18.6 ft.
20" Douglas Fir N.10°W., 25.7 ft.
24" D. Fir (snag), N.38.0 ft.
30" Douglas Fir, (down) N.45 1/2°E., 12.5 ft.
Marked - 6" White Fir N.24°E., 31.1 ft. "S 36 B T" and attached brass
washer stamped Land Surveyor 536 on lower face.

4/79

220

William Ruppert, LS #866
For: U. S. Forest Service
April, 1979
M 70 - 61

1/4 Corner for Secs. 28 and 33.
Found- 2 1/2" Iron pipe with nipple. (no cap)
stone marked "1/4" 6" south of pipe. Ren. #86
24" Fir stump burned face S.76°32'W., 101.0 ft.
18" Fir stump, burned "S33 BT" vis. S.79°16'W., 108.5 ft.
24" Madrone, faint bark scribing vis. N.45°40'E., 156.6 ft.
24" Cedar, "T30S R2W S33 1/4 S BT" vis. S-57°08'E., 153.9 ft.
Set - 2" x 30" Galv. iron pipe with 2 1/2" brass cap. Buried 2 1/2"
iron pipe and stone with 2" x 30" iron pipe in mound of stone

221

1/4 Corner for Secs. 32 and 33.
Found - Stone set firmly in ground with "X" on top and "1/4" on
west face. Ren. #84
42" D. Fir S.85°13'W., 35.4 ft. "1/4 S 32 BT" visible.
22" D. Fir S.64°28'E., 8.0 ft. good scar
20" Madrone windfall N.76°W., 12.5 ft.
Set - 2" x 30" Galv. iron pipe with 2 1/2" brass cap.
Buried the stone with the pipe.

222

Center 1/4 Corner for Sec. 33
Set - 2" x 30" Galv. iron pipe with 2 1/2" brass cap in mound of
stones. Marked T30S R2W C 1/4 S33 RLS 866 1979"
Scribed BT's -
18" D. Fir, "C 1/4 S33 BT" N.7°38'W., 27.8 ft.
8" Cedar "C 1/4 S33 BT" N.56°46'E., 26.3 ft.

FND. OK 11-92
BY CENTER, M 116-33

618