

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 30 S      T. S.      R 2 W      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97301

**230**

Bruce A. Shaner  
L.S.#430  
For: Longview Fibre Co.  
Aug. 1980  
RM 3 - 35

North 1/4 corner to Sec. 16 only  
Fd. - Orig. 16" x 10" x 6" basalt stone mkd. "1/4".  
Orig. 12" D. Fir bears S.9°W., 11.9 ft. down and rotted with partial scribes visible.  
Set - Brass cap mkd. "T30S, R2W, W.M. 1/4S S16 only RLS 430 1980".  
New BT's - 8" D. Fir bears S.8°W., 25.1 ft. scribed "1/4 S16 BT".  
19" Cedar bears S.53°E., 37.9 ft. scribed "1/4 S16 BT".  
I reset stone alongside brass cap.

**231**

South 1/4 Corner to Sec. 9 only      See Ren. #113  
Fd. - Orig. 32" D. Fir, new uprooted stump bears N.32°E., 22.4 ft.  
Brass cap mkd. "T30W, R2W 1/4 S9 1968 Co. Surveyor" Ren. #113  
15" Cedar bears N.83°W., 18.4 ft. with visible scribes.  
New BT's - 9" Cedar bears N.15°W., 31.7 ft. scribed "1/4 S9 BT".

**232**

Center 1/4 Corner to Sec. 16  
Set - Brass cap mkd. "T30S, R2W., W.M. S16 C1/4 RLS 430 1980".  
BT's - 5" Cedar bears S.1°W., 5.6 ft. scribed "S16 C1/4 BT".  
14" D. Fir bears N.2°W., 20.6 ft. scribed "S16 C1/4 BT".

**233**

Howard Johnstone  
For: Roseburg Lbr.  
March 17, 1981  
M 87 - 13

Center 1/4 corner for Section 28  
Set - 5/8" x 30" Iron rod and alum. cap.  
BT's - 6" Madrone, N.10°W., 9.2 ft.  
4" Madrone, S.62°E., 5.2 ft.

3/17/81

**234**

Leonard Herzstein  
U.D.F.S., Deputy  
Doug. Co. Surveyors  
Office  
Tom Wolford: Jim  
Landrum  
April, 1981  
C.S. 61/19

Section corner for Secs. 25 and 36; and Secs. 30 & 31 of T.30-1  
Fbund' - 1968 County brass cap, properly mkd. or 1" I.P. firmly let projecting 4" above ground. Ren. #102  
Orig. BT, a roothole, S.45°E., 5.3 ft. with D. fir stump 36" diam. alongside with bark blaze vis. on underside.  
18" yew, N.37°E., 61.0 ft. with scribe marks "T30S R1W S30 CS BT" vis. on partly healed blaze. Ren. #102  
13" yew, S.50°E., 49.0 ft. with scribe marks "T30S R1W S31 CS BT" vis. on partly healed blaze. Ren. #102  
16" hemlock, N.4°W., 47.1 ft. (Rec. W. fir, 47.5 ft.) with healed blaze. Ren. #102  
New BT's- 4" D. fir, N.42 1/4°E., 45.8 ft. mkd. "T30S R1W S30 CS BT" on double blaze.  
6" D. fir, S.34 34/°W., 79.9 ft. mkd. "T30S R1W S36 CS BT" on double blaze.

4/14/81

**235**

Gregory E. Quibell  
Deputy, Douglas County  
Surveyor Office  
Terrie Plouff, and  
Teresa Buley, witnesses  
Sept. 30, 1981  
C.S. 61/27

1/4 corner for Sec's. 28 & 33.  
Found - Brass Cap on I. Pipe per Ren.# 220, lying on ground nears its correct location. I estab.temp.position based on the followi  
BT's- 24" Fir stump w/ burned face, bears S.76°W., 101.0-ft. Ren.#220  
18" Fir stump, burned, w/ S33 BT visible, bears S.79°W., 108.5-ft.  
24" Madrone bears N.45°E., 157.3-ft. (Rec. 156.6-ft.) Ren#220 with scribed T30S R visible in bark.  
24", now 25" Cedar bears S.57°E., 153.9-ft. w/ T30S R2W S33 1/4 S BT visible in unhealed blaze.  
Set - I ref. my temp. position, then reset Fnd. Brass Cap at that location. Cap now is in a steep firetrail protruding 4" out of ground. I add marks: Reset 1981

9/30/81

**236**

Larry E. Monrean  
Deputy Douglas County  
Surveyors Office  
Greg Quibell & Terrie  
Plouff, witnesses  
Oct. 20, 1981  
C.S. 61 / 29

NE corner of Sec. 1, T.31-3 only.  
Found - Orig. 15" x 10" x 8", now 14" x 7" x 5" stone marked with CC on South face & 6grooves on the South, East & West faces, firmly set with top flush with ground.  
BT's - Orig. 30" now 36" Fir w/good scar bears S.42 1/2 °W., 38.0-ft., (Rec. 38.6-ft.).  
Orig. 10" now 21" Hemlock w/good scar bears N.18 1/2 °W., 22.2-ft.  
Set - At the exact location of the orig. stone, I set a B.C. protruding (Replaced stone at Southerly edge of the cap).

( CONTINUED )