

Douglas County Surveyor's Record of
Government Corners Renewed

T.30 S. T. S. R.2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Bruce Shaner RLS #430
For: Longview Fibre Company
October 1981 thru January 1982
R M 3 - 5 5

Jim Landrum - Leonard Herzstein
U.S.F.S.
March - April 1982
C.S. 61/32

1/4 Corner common to Secs. 8, & 9. 240
Found - 1968 B.C., properly mkd., w/10" x 9" x 5" stone Ren. #164.
laying alongside, from which: (no marks on stone)
BTs. - 16" split maple, w/no scribes visible bears Orig.
S. 53-1/2°W., 4.2-ft. (Rec. 5.9-ft.).
8" Doug. fir stump w/tin covering, and no scribes Ren. #164.
visible, bears N.55°E., 54.0-ft. (Rec. N.60°E.).
12" W. fir, dead & down, w/scribes visible, bears Ren. #164.
N.61°W., 32.7-ft. (Rec. N.65°W.).
New BTs- 14" D. fir, I scribed "1/4 S8 BT", bears S.76°W., 63.3-ft.
16" D. fir, I scribed "1/4 S9 BT", bears S.40°E., 48.9-ft.
12/81

Sec. Corner common to Secs. 8, 9 only, adjacent to Sec. 16. 241
Found - 1968 B.C., properly mkd., from which:
BTs - 7" D. fir, down & burnt, bearing N.24°E., 13.2-ft. Orig.
is now GONE .
14" D. fir w/healed over face, bears N.56°W., 65.0-ft. Ren. #111
12" D. fir w/healed over face, bears S.25°W., 18.2-ft. Ren. #111
(Rec. 17.0-ft.).
New BTs.-8" D. fir, I scribed "T30S R2W S9 BT", bears N65°E., 21.4-ft.
12/81

South 1/4 Corner to Sec. 8 only. 242
Found - 1968 B.C., properly mkd., with a 10" x 8" x 7" stone,
marked with an X alongside, from which:
BTs. - 24" D. fir stump w/the scribe "B" visible, bears Orig.
N.41-1/2°W., 21.8-ft.
12" maple, rotted, bears N.40°E., 29.0-ft. Orig.
12" hemlock w/scribes visible, bears N.2°W., 24.6-ft. Ren. #148.
12" hemlock, dead & down, no scribes vis., bears Ren. #148.
N.67°W., 21.2-ft.
New BTs.-8" W. fir, I scribed "1/4 S17 BT", bears S.68°W., 21.9-ft.
12/81

Center 1/4 Corner in Sec. 8. 243
Set - Brass Cap mkd. "T30S R2W WM C1/4 S8 Shaner Engineering
RLS 430 1981", from which:
14" D. fir, I scribed "C 1/4 S8 BT", bears S.5°W., 8.4-ft.
10" D. fir, I scribed "C 1/4 S8 BT", bears N.53°W., 16.7-ft.
Steel fence post set alongside. 12/81

East 1/16 - Sections 28 and 33 244
Found- 1967 brass cap flush with and set in 6" diam. concrete column.
which projects 6" above ground, properly marked. Set in 1967
by Bruce Shaner. Ren. #88
30" D. fir snag, N.66°E., 85.6 ft. with scribe marks "E 1/16
S28 BT" visible on partly healed blaze.
24" D. fir, S.79 1/2°E., 80.6 ft. (Rec. 79.4 ft.) with scribe
marks "E S33 BT" visible on partly healed blaze.
New BT - 4" madrone, N.02 1/2°W., 14.9 ft. scribed "E 1/16 S28 CS" on
upper bark blaze and "BT" on lower axe blaze.
Also - New tie to existing Douglas County Road dept. monument: a 1 1/2"
alum. cap on 5/8" rebar firmly set, projecting 1" above ground
with cap marked R/W Douglas Co. Rd. Dpt." bears N.87°E.,
47.7 ft. with guard post mkd. "P.I. 28+78.29 100' R/W lt."
set 1 ft. west.
Corner lies on steep SE slope; 5 ft. west of old N-S fence line; about 25 ft.
west of 3 wire power line; and about 130 ft. northwest of county road #46.
4/8/82

Section corner for Secs. 27, 26, 34 and 35 245
Found - 2 1/2" brass cap on 1" iron pipe, firm, projecting 14" properly
marked set by Douglas Co. Surveyors Office. Ren. #158
Orig. 24" Ponderosa pine bears S.81°W., 285.8 ft. now snag.
scribed visible "T20S R2W S34" on previous opened double blaze.