

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30

T. S.

R 2

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Howard Johnstone  
For: Roseburg Lumber  
September 20, 1984  
C. S. 58/296

**RE-RENEWED, SEE CORNER NO. #274**

Section corner for Secs. 17 and 20 only.  
Found - 1968 County brass cap and iron pipe. Good. Ren. #168  
45" Fir, N.35°W., 33.7 ft. Good.  
24" Fir, S.54°W., 15.8 ft. Snag and Rotten.  
New BT - White fir, 6", S.35°W., 25.2 ft. scribed with section and BT.  
9/20/84

252

Center 1/4 Corner for Section 27  
Found - A 3" brass cap on a 2" iron pipe. Ren. #207  
A blown down 16" fir bears S.32°W., 14.5 ft. scribe visible.  
A blown down 8" fir bears N.83°E., 10.9 ft. scribe visible.  
New BTs - An 18" fir bears S.43°E., 12.9 ft. marked C 1/4 S27 BT.  
A 24" fir bears S.44°W., 39.9 ft. marked C 1/4 S27 BT.

253

Section corner for Secs. 27, 28, 33 and 34  
Found - 2 1/2" BC on a 1" I.P. on south side of 7"x8"x18" stone  
w/"x" chiseled on top. Ren. #191  
Found - A 30" fir bears N.30°W., 22.2 ft. bark scribe visible.  
A 24" fir bears N.42°E., 30.2 ft. bark scribe visible.  
A 30" fir bears S.20°E., 18.4 ft. scribe visible.  
A 26" fir stump bears S.10°W., 38.5 ft. scribe visible.  
The remains of a 12" fir bears S.54 1/2°W., 16.7 ft. scribe visible.  
New BT - A 6" fir which bears S.33°W., 71.7 ft. marked T30S R2W S33 BT.

254

Loyd R. Moffit  
L.S. #944  
For: U.S. Forest Service  
April 1985  
C.S. 63/8

1/4 Corner for Sections 24 and 25  
Found - A 2" brass cap on a 1" iron pipe. (1974 County) Ren. #187  
An 18" fir bears N.51°E., 51.7 ft. scar visible.  
A down 12" madrone is destroyed.  
New BT - A 10" madrone which bears S.55°E., 18.0 ft. marked 1/4 S25 BT.

255

Section corner for Secs. 25, 26, 35 and 36  
Found - A 2 1/2" brass cap on a 1" pipe exposed 12". Ren. #116  
A 22" fir stump bears N.15°W., 1.7 ft.  
A 16" fir bears N.59°W., 73.5 ft. scar visible.  
A 12" pine bears S.74°E., 33.4 ft. scar visible.  
A 16" fir bears S.03°E., 20.9 ft. scar visible.  
A 38" fir bears N.50°E., 9.0 ft. no scar  
A 16" fir bears S.43°W., 39.5 ft. scribe visible. (no record)  
New BT - A 4" fir which bears N.30°W., 18.0 ft. marked "X" BT.

256

1/4 Corner to Section 31 only, T29-2W Renewal #126  
Found - A 1917 U.S. G.L.O. Brass Cap on an I.P., protruding 14 ins. above ground. Properly mkd. 257  
BT's - 20" now 22" diam. D. fir tipped out, with covered face. Center of root hole bears N.8 1/2°E., 12.5 ft. (Agrees with original)  
30" now 38" diam. D. fir with a well healed single blaze, bears N.32 1/2°W., 19.8 ft. (Agrees with orig.)  
20" now 24" diam. D. fir with a well healed single blaze, bears N.30°E., 25.1 ft. (Agrees with Ren. #126)  
New BT's- 7" Cedar, double blazed and scribed "1/4 S31 CS BT", bears N.76 3/4°E., 9.7 ft.  
5" D. fir, double blazed and scribed "1/4 S31 CS BT", bears N.60 3/4°W., 30.9 ft.  
NOTE: Corner is S.89°50'26"W., 88.18 ft. from N 1/4 Cor. of Sec. 6, T30-2W. (See M97-65)

Douglas County  
Surveyor's Office  
Randall W. Smith, &  
Stephen J. Flause  
June 24, 1985  
C.S. 62/28

Continue on next page...