

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 30 T. S. R 2 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORG. 21881

258

Douglas County Surveyors
Office
Stephen J. Flause, &
Randall W. Smith
June 6, 1985
C.S. 62/28

North 1/4 Section Corner to Section 6 only, T30S R2W. REN #127
Found - Original Porphyry stone, measuring approx. 14" x 12" x 6"
with possible "4" marked on south face; this stone is
loosely set on surface of ground at east edge of brass cap
monument. (1909)
An iron pipe and brass cap monument (Ren #127) properly
marked and firmly set, protruding 12 ins. from ground.
Orig. BT, A 10 in. fir, now a 16 in. DBH D. Fir with x
chopped in bark and a partially healed, obliterated face,
bears N.35°E., 2.6 ft. dist. (Rec. N.35°W., 2.6 ft.)
Orig. BT, A madrone, 6 ins. diam., now a 9 inch DBH
madrone with a partially healed rotted out blaze, bears
S.57°W., at center of root crown, and S.40°W at center
of trunk blaze height, 2.3 ft. dist. (Rec. S.40°E.,
2.3 ft.)
A 12 in. diam. Fir, now a severely rotted, 6" tall broken
fir stub with no identifiable marks (1917 resurvey) bears
S.2 1/4°E., 12.7 ft. dist. to center of apparent root crown,
(Rec. S.2 1/4°E., 13.2 ft.)
Two bearing trees from REN #127 - A 5" D. fir now a 9" DBH
D. Fir, bears S. 41°E., 17.4 ft. dist. (As per record),
with fully healed single blaze. And a 30" DBH D. Fir with
a fully healed single blaze and a "B" chopped into the bark,
bears S.35°W., 18.9 ft. dist. (As per record.)
New BT's - A 6" DBH Doug. Fir, double blazed and scribed 1/4 S6 CS BT,
bears S.14 1/2°E., 18.0 ft. dist.

259

Sec. Cor. for secs. 19 and 30 (T.30-2) and secs. 24 and 25 (T.30-3)
Found - 3/4 in. drill steel REN #6
18 in. Madrone, bears N.49°50'W., 26.0 ft. dist. (SNAG)
24" Madrone snag, bears N.2°26'E., 30.9 ft. dist.
16" Madrone snag, bears S.31°25'E., 9.3 ft. dist.
16" Madrone stump, bears S.64°32' W., 19.2 ft. dist.,
(Record 18.2 ft. dist.)
15" Oak, bears S. 54°W., 24.4 ft. dist. (SNAG)
SET - A 5/8" iron rod and Aluminum cap, marked "LS 498"
NEW BT's - 5" Fir, bears N.46°W., 24.0 ft. dist. (Scribed)
Scribed a 6" Madrone, bears N.46°E., 43.8 ft.
Scribed a 6" Madrone, bears S.58°E., 21.3 ft.
Scribed a 5" Madrone, bears S.22 1/2°W., 29.6 ft.

260

Center 1/4 Section Corner for Section 30
SET - 5/8" by 30" iron rod with aluminum cap marked "LS 498"
BT's - Scribed a 24" Fir, bears S.40°E., 33.0 ft. dist.
Scribed a 24" Fir, bears N.72°W., 12.7 ft. dist.

261

South 1/4 Section Corner for Section 30 ONLY REN #31
Found - DID NOT find 1958 County Brass Cap.
BT's - A 24" Hemlock, bears N.33°W., 29.7 ft. Fd. scribe.
A 60" Fir stump, bears N.62°E., 41.0 ft. dist.
NEW BT - Scribed a 12" Hemlock, bearing N.48°E., 31.7 ft.
Set - 5/8"x36" I.R. & Alum. cap from above found BTs.

262

North 1/4 Section Corner for Section 31 ONLY
Found - Original Stone and Square Post.
- 50" Fir, bears S.62°E., (Record, S.55°E.), 37.0 ft. dist.
With healed blaze. (ORIG)
8" Maple Split Snag, bears S.32°W., (Record, S.39°W)
9.9 ft. dist.

263

Ronald Geisler "LS #1988" C 1/4 Corner S18.
For: Champion Inter-
national Corporation.
M 100 - 78
April - May 1986
Set - A Aluminum Cap W/Iron Pipe.
BT's - A 5" fir bears S 78° W, 10.2'.
A 7" fir bears N 14° E, 20.8'.
Both trees scribed : C1/4 S18 BT
Note - An unrecorded 1 1/4: Iron pipe bears N 0°30'34" E, 34.5'
from cap.

Howard Johnstone
"LS #498"
For: Roseburg Resources Company
December 30, 1985
M 100 - 21