

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 2 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21881

C O N T - - - -

(1/4 Cor. 28 & 33)

272

Douglas County Surveyors
Randall Smith and Stephen Flause
September 26, 1987
C.S. 62/45

Northwest bearing tree per ren#25 gone.
BT's - A 24" now a 14" dia. 20" high broken and burnt douglas fir stump,
with blaze and scribing visible "S33 BT" bears S79°W, 108.5'
(rec. S 80°W, 108.0 ft. per ren. #86; S 79¼°W, 108.5 ft. per
ren..#220.; S 79°W, 108.5 ft. per ren.#235). Ren. #86 BT.
16" now 28" dia. incense cedar with a fully healed single blaze,
bears S 57°E, 153.9 ft. (rec. S 56½°E, 153.0 ft. per ren.#
86; S 57°E, 153.9 ft. per ren.#220; S 57°E, 153.9 ft. per
ren.#235.) Ren. #86 BT
24" now 24" dia. 4 ft. high madrone stump with illegible bark
scribing bears N 45°E, 156.6 ft. (rec. N47½°E, 157.7 ft. per
ren. #86; N 45 3/4°E, 156.6 ft. per ren. #220; N 45°E,
157.3 ft.per ren. # 235) Ren. #86 BT
Set - Brass cap with iron pipe per ren. #220 was returned to plumb pos-
ition,now protrudes 6 inches above ground.
New BT - A 9" douglas fir double blazed and scribed "¼ S28 CS BT" bears
N 35°E, 32.6 ft.
Corner lies in fire trail on steep southerly slope.

273

Douglas County
Surveyors Office
Randall Smith;
Stephen Flause;
Terrie Franssen
Feb. 26, 1991
C.S. 64/13

1/4 Corner for Sections 21 and 22
Found - A 2½" dia. DCSO brass cap on a 1¼" O.D. iron pipe, protruding
12" above ground. Ren. #144
Stone not visible on top of ground, we did not dig to look.
16" now 23" dia. 40 ft. high cedar snag with a fully healed
single blaze, bears N.51°W., 35.6 ft. (1909)
28" now 20" dia. 2 ft. high pine stump with rotted, open blazes
scribing visible "2" bears N.50°E., 19.1 ft. (record N.52°E.,
19.1 ft.) (1909)
40" now 42" dia. 4 ft. high D. fir stump with a partially healed
blaze, scribing visible "1/4 S22 CS BT" bears S.81½°E.,
96.7 ft. (Rec. S.80°E., 96.7 ft.) Ren. No. 144
New BTs - 7" dia. D. fir double blazed and scribed "1/4 S22 CS BT" bears
N.42°E., 31.7 ft.
9" dia. D. fir double blazed and scribed "1/4 S22 CS BT" bears
N.13°E., 20.1 ft.
10" dia. D. fir double blazed and scribed "1/4 S21 CS BT" bears
N.27°W., 31.3 ft.

2/26/91

274

Douglas County Surveyors Office
Randall Smith, Deputy
Stephen Flause - Terrie Franssen
March 22, 1991
C.S. 64/13

Section Corner for Sections 17 and 20 only.
Found - 2½" dia. 1968 DCSO brass cap on a 1¼" O.D. iron pipe protrudes
11" above ground. Ren. #168
20" now 26" dia. 6 ft. high D. fir stump with a previously
opened bark, scribing visible "T" bears S.54°W., 15.8 ft.
(agrees with record) Original BT.
40" now 44" dia. D. fir with a fully healed single blaze bears
N.35°W., 33.7 ft. (agrees with record) Original BT.
6" now 6" dia. 5 ft. high fir stump with an unhealed single
blaze, scribing visible "S20 SC BT" bears S.35°W., 25.2 ft.
(agrees with record) Ren. #252
New BTs - 15" dia. W. fir double blazed and scribed "T30S R2W S17 CS BT"
bears N.78°W., 20.3 ft.
4" dia. W. fir double blazed and scribed "X BT" bears
S.75½°W., 22.8 ft.
DCSO BC/IP T30S R2W SW C.C. S16 bears South 100 ft.

3/22/91

275

Section Corner for Section 16 and 21 only.
Found - 2½" 1968 DCSO brass cap on a 1¼" O.D. iron pipe protruding
14" above ground. Ren. #167
Orig. 16" x 10" x 8" stone with faint marks "CC" on south
face, found loose on top of ground along north side of DCSO BC.
30" now 32" dia. 6 ft. high burnt and rotted D. fir snag, no
blazes or scribing visible, bears N.21°E., 25.1 ft. (Rec.
N.25°E., 25.1 ft.) Original.
24" now 30" dia. 4 ft. high burnt and rotted D. fir stump with
a healed blaze, bears S.72°E., 12.5 ft. (agrees with record)
Original BT.