

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 30 T. S. R 2 R.W.W.M.

FORE-CHAPMAN CO., EUGENE, ORE. 91881

278

1/4 Corner for Sections 21 and 28

Found - A 2 1/2" dia. 1968 County brass cap on a 1 1/2" O.D. iron pipe is firmly set and protrudes 10" above ground. Ren. No. 162
(Basalt stone set in 1909 retracement and found in Ren. #162 is searched for but not found.)

A 18" Hemlock now a 24" DBH Hemlock with the scribing "1/4 8 BT" partly visible on a previously opened double blaze bears S.60°E., 14.5 ft. (Original) (Rec. S.57°E., 14.5 ft.)

(No evidence northwest bearing tree found.)

a 16" hemlock now a 19" DBH 5 1/2 ft. tall alum. capped hemlock stump with a fully healed double blaze bears N.15°W., 13.3 ft. Ren. No. 162. (Rec. N.22°W., 13.3 ft.)

New BTs - A 3" DBH Hemlock scribed "X BT" on a double blaze bears N.50°E., 15.2 ft. distant.

An 11" DBH Hemlock scribed "1/4 S28 CS BT" on a double blaze bears S.16 1/2°E., 24.0 ft. distant.

A double trunked Maple 9" DBH most easterly trunk is scribed "1/4 S21 CS BT" on a double blaze. The root crown of the double trunked tree bears N.55°W., 59.6 ft. distant.

Monument is on steep easterly slope approx. 500 ft. west of Salt Creek.

3/18/91

Douglas County
Surveyors Office
Stephen J. Flause
T. R. Franssen
March 18, 1991
C.S. 64/13

Harold Stockhoff
L.S. # 1663
For: R. Curtis
Feb. 14, 1991
M 111 - 49

Center 1/4 corner for section 21.

Set - 5/8" X 30" iron rod w/plastic cap marked PLS 1663.

BT's - 8" dia. MADRONE N.70°W., 20.8 ft. (bark scribed C1/4 BT)

10" dia. cedar N.10°W., 10.4 ft. (scribed C1/4 BT)

12" dia. madrone N.77°E., 17.2 ft. (bark scribed C1/4 BT)

8" dia. madrone S.5°W., 8.7 ft. (bark scribed C1/4 BT)

7/16/91

Secs. 33 & 34; & 3 & 4 T31-2

Found - Brass Cap

17 3/4" Cedar Cor. Tree (turning snag)

18" Fir, bears N.62°E., 43.3' (Ren #227)

21" Fir, bears S.68°32'W., 7.3'

42" Fir, bears N.66°35'W., 10.4'

Fir stump pile bears S.35°52'E., 8.0'

24" Fir, bears S.6°22'E., 14.7'

9" Cedar bears N.36°09'W., 13.8' (now down)

12" Fir, bears N.9°09'W., 32.6'

279

280

Greg Lang
For: Phil Washburn
Roseburg Resources
Mark Hubbard
7/94 M 120-69

281

Center 1/4 Section 12

Set - 5/8" x 30" iron rod with yellow plastic cap marked "Nygren LS1035"

Bearing Trees scribed -

10" D.Fir, S.40°E., 47.7 ft.

7" D.Fir, N.37°E., 25.1 ft.

8" D.Fir, N.73°W., 19.6 ft.

8" D.Fir, S.76°W., 18.6 ft.

Gerald Nygren
For: John Hayden
April 1995
M121 - 76

282

C 1/4 Cor. Sec. 32

Found - Badly rotted 20" fir stump corner tree

27" cedar S.77°E., 5.2' (Ren. #30)

22" cedar S.42 1/2°W., 31.4', rotten stump

Set - 5/8"x48" I.R. & alum. cap stamped L.S. 2354 in center of stump.

New BTs - 12" fir S.82°W., 22.8', "1/4 C BT"

7" fir N.24°E., 18.9', "1/4 C BT"

16" madrone N.88°E., 33.5' "1/4 C BT"

Mark Smalley,
L.S. #2354
For: Roseburg
Resources Co.
April 1995
M 121-77