

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 3 R. W. W. M.

N.W. CORNER OF JACOB AMSLER D.L.C. NO. 39 *pg 109 pg 44* 28
Established by original B.T.s. I renew corner by setting
buggy axle in mound of boulders.

SEC. COR. 19-30 (R 2 W), 24-25 (R 3 W) 29

Found 1" iron bar and old B. T. *REN.#23*
15" Oak N 45° E 38.9 ft.
15" Oak N 74° E 36.9 ft.
15" Oak S 54° W 24.2 ft.
18" Oak N 38° W 93.0 ft.
All B. T.'s in poor shape so mark new B. T.'s.
24" Madrona N 2° 26' E 30.9 ft.
18" Madrona N 49° 50' W 36.0 ft.
16" Madrona S 64° 32' W 18".2 ft.
16" Madrona S 31° 25' E 9.3 ft.

RE-RENEWED CORNER NO. #231

SEC. COR. 19 and 30. 30

Location determined from O. B. T's.
Set 1 1/2 inch x 30 inch I. P. for corner.
O.B.T. 20" Laurel, N 40° E 33 links - alive
30" Laurel, S 45° E 40 links - alive
18" Laurel, N 50° W 19 links - alive
14" Laurel, S 47° W 36 links - dead
N.B.T. Blazed and Scribed
10" Chinquapin, N 31 1/2° W 16.7 ft.
12" Fir, S 72 1/2° W 50.2 ft. - No suitable trees in S. 19-30

1/4 COR. 19-30 31

Reset corner by driving 2 1/2" x 36" Boiler tube.
Identified from O. B. T's. *(REN.#19)*
14" Fir, N 53° E 65 lks. *165*
30" Fir, S 80° E 39 lks.

1/4 COR. W SIDE SEC. 30 32

Location identified from O. B. T's.
30" Fir, S 80° E 80 lks., alive Standing, scribe mks. plain
22" Fir Stump, N 65° E 63 lks., scribe mks. visible. *156*
Set 2 1/2" x 36" I. P. for corner
Blazed and Scribed B. T., 12" Fir, N 70° E 38.0 ft., marked
1/4 S 30 C S B T. *REN.#11*

EXT. L COR. DLC #39 33

Reset by intersection of East line and North line of DLC
Set 2 1/2" x 42" I. P. for cor.
Blazed and scribed B T's.
30" Fir, N 10° W, 71.6 ft.
12" Fir, N 85° W 98.5 ft.

NE COR. DLC#39 34

Found iron bar and O. B. T's.
Set Wagon Skein for corner to replace bar, which was too short.
O. B. T's. *REN # 13*
16" Fir bears S 20° W 22 lks.
18" Fir Stump bears S 73° W 43 lks.

C.C. 18-19 35

Found 30" Fir N 18° W 23.1 ft. Scribe burnt out
8" Laurel S 18° W 5.3 ft. Scribed
14" Madrona for Corner. *167*
Mark 16" Fir W 26° E 68.0 ft.
12" Fir S 89° 35' E 31.2 ft.

COR. 17-18-19-20 36

Found all B.T.s
36" Fir S 78° W 44.9 ft. only one good.
18" Maple N 18° E 43.5 ft. Rescribe.
Drive 1" I. Pipe.
Mark 12" Fir N 27° 45' W 58.9 ft. *206*
16" Cedar S 31° 20' E 42.0 ft.

1/4 COR. 17-18

Set 300 ft. South of Witness Corner on line to Cor. 17-18-19-20
Drive 1 1/2" I. Pipe. Mark 12" Fir

F. Cain
Mar. 26,
1923

G. J. Wenderoth
Dep. Cnty. Surv.
Frank Loso
John H. Howell
Witnesses
March 1948

Ben B. Irving - County Surveyor
Milo E. Godfrey and Franklin D. Smith - Witnesses
Surveyed November and December 1948

Arthur R. Evans - Deputy County Surveyor

Geo. J. Wenderoth - D.C.S
Francis Sincumb & Carl Hill
June, 1950

MS-60 CS 43/6

CS 45/91 M 7-56A