

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 3 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORK. 97196

John H. Markham - Engineer  
E. R. Sutton - Witness  
March 14, 1951

John H. Markham - Engineer  
Fred Seymour - Witness  
March 16, 1951 C.S. 40/302

J. H. Markham, Jr., Eng.  
Geo. Vaughn - Witness  
8-8-51

for Joe Ritter  
#0/363

J. H. Markham Jr.  
Witness  
Fred Seymour  
10-4-51  
C.S. 40/381

Bud Johnson  
Wm. Markham  
Fred Seymour  
10-4-51  
C.S. 40/381

East 1/4 Sec. Cor. 24

Determined by O.B.T.

A Fir stump 39 in. diam. bears N 88° W, 23.7 ft. dist.

I chopped this stump out and found scribe.

A Laurel snag 36 in. diam. bears S 38° E, 26.4 ft. dist.

I remark both O.B.T.s.

At corner point set wood stake, from which:

A W. Oak 7 in. diam. bears South 550.0 ft. dist. marked 1/4 S, B. T.

37

N. W. CORNER 2 SECTION 8

Determined by O.B.T.

A Fir stump 28 in. diam. bears S 38° W, 25.7 ft. dist. - O.B.T.

A Fir 26 ins. diam. bears N 7 1/2° W 15.5 ft. dist. - O.B.T., Rev #21

I rescribe both O.B.T.s

At corner point set 1" x 24" iron pipe, from which

A Maple 5 in. diam. bears S 12° E, 13.0 ft. dist. marked S 8, B.T.

38

S. W. CORNER - SECTION 5

At corner point found 4" x 4" wood post scribed. Both Fir B.T.s standing and in good condition. Rev #20

At corner point set 1" x 24" iron pipe, from which

A Maple 12 ins. in diam. bears S 46° W, 14.5 ft. dist. marked S 8, B.T.

Sec. Cor. 6-7-8 bears West 408.5 ft.

39

SOUTH 1/4 CORNER OF SECTION 33

As determined by Old Bearing Trees

A Dead Fir Snag 16" Diam. bears N. 4 1/2° E., 8.0 ft. distant scribe showing

A Dead Fir Snag 55" diam. bears S. 72° E., 18 1/2 ft. distant O.B.T.

At Corner point set 4' x 4' stone. From which:

An Alder 4" diam. bears S. 57° E., 12.0 ft. distant marked

1/4 S., B.T.

A Fir 8" diam. bears S. 49° W, 25.0 Ft. distant marked

1/4 S., B.T.

The Corner of Section 4 and 5 bears West approximately 200 feet distant.

40

1/4 CORNER BETWEEN 28 and 33

Determined by Old Bearing Trees

A Fir 30" diam. bears N. 61° W., 33.0 ft. distant found bark scribe

A Fir 36" diam. bears S. 82° E., 62.0 ft. distant O.B.T.

At Corner point found rotten stump of O. B. T. set for corner point, I drove a 1" x 30" Iron Pipe from which:

A Maple 6" diam. bears N. 10° E., 17.5 ft. distant marked 1/4 S, B.T.

FD OK  
By M. Hemburger  
for N. Neherbon  
6/94 M120-22  
FD OK 4/86  
RUPPERT  
C.S. 63/36

41

N.E. Cor. Sec. 8.

Sec. 8 T 30 S., R 3 W., NE corner

Determined from OBTs.

A fir 30" diam bears S 34° W 21.0 ft. dist. OBT

A fir 23" " " N 23° E 18.0 ft. " OBT

I remarked both OBTs.

At the corner point I found a large stone and set a 1x30" IP from which

A fir 17" diam. bears S 70° E 9.0 ft. dist. mkd. S 9 BT

10-4-51

42

Sec. Cor. 8-9-16-17 T 30 S., R 3 W. as det. by OBT

A fir 26" diam. bears N 13° W 33.0'

A fir 18" diam. bears N 15° E 35.0'

A fir 26" diam. bears S 56° W 18.0' I remark the 3 OBTs

At the corner point set 1x30" IP from which

A fir 13" diam. bears S 66° E 53.2' dist. mkd. S 16 BT

10-4-51

43