Douglas County Surveyor's Record of Government Corners Renewed

30 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

44

¼ Section Corner 21 & 28, T 30 S R.3 W W.M. as determined by O.B.T.
A Fir, 12" diam. bears S 80 W, 14.7 dist.
I remarked this O.B. T.
A dead Fir windfall 8" diam. bears N 80 W, 15.4 dist. O.B.T.
At corner point found original Stone and set I.P. from which
A Laurel, 14" diam. bears N 71 W, 29.6' dist. marked ¼ S. S 21 T.30 S R 3 W. 2880 B.T. #113
A Laurel, 13" diam. bears S. 44E, 17.6' dist. marked ¼ S S 28 T 30 S. R. 3 W 2880 O.B. T.

RE-RENEWED, SEE CORNER NO.

John H. Markham, Jr.
Witness
Ivan Kelly
Oct. 18, 1951.
C.S. 40/384

45

Section corner 20 - 21- - 28 - 29, T 30 S R 3 W, W.M. as determined by O.B.T.
A dead B.O. 14" diam. bears N 88 W 85.0' distant O.B.T.
A dead B.O. 14" diam. bears S 56 W 54.0' distant O.B.T.
A B.O. stump bears S. 4 W 27.7' distant O.B.T.
A corner post set ½ x 30" I.P. from which
A Fir 11" diam. bears N 36 W 26.4' dist. marked 520, B.T. 110
A Laurel 12" diam. bears S 41 W 5.0' dist. mkd. S 29 T 30S R 3 W 2880, B.T.
A Fir 11" in diam. bears N 28 W, 10.4' dist. mkd. 521 B.T.
A Laurel 16" diam bears 584 E 25.2' distant mkd. 528 B.T
A fence bears sputh from this corner.

RE-RENEWED, SEE CORNER NO.

John H. Markham Jr.
Witness
Dennis Vaughn
Elmer Sutton
Jan. 26, 1952
C.S. 40/384

46

¼ Corner 20 - 21, T 30 S R 3 W, W.M. as determined by O.B.T.
A Fir 14" in diam. bears S 16 W, 15.0' dist. O.B.T.
A Fir windfall bears N 80 E, 8.0' distant O.B.T. 123
At corner point set 1x30" I.P. from which
A Fir 30" diam. bears N 61 E, 20.0' dist. mkd. ¼S, B.T.
A Laurel 8" in diam. bears S 67 W, 55.0' dist. mkd. ¼ S, S 20 T 30 S R 3 W B.T.

RE-RENEWED, SEE CORNER NO.

John H. Markham Jr.
Witness
Geo. and Dennis Vaughn
Elmer Sutton
Jan. 26, 1952
C.S. 40/384

47

¼ Corner Section 20 - 29, T 30 S R 3 W, W.M. as determined by O.B.T.
A dead Fir snag 50" in diam. bears S 60° W, 10.5 feet distant, O.B.T.
~~A dead 10" bears N 38° 31.0 feet distant mkd. Section~~
At corner point set 3/8 x 30" Iron Rod, from which
A Maple 10" in diam. bears N 23° W 31.0 feet distant, mkd. ¼S, S 20° B.T.
A Yew 8" in diam. bears S 2°E, 31.0 feet distant, mkd. ¼s, S 29 B.T.

FD & USED CORNER PER MARKHAM APRIL 87 M104-25

Jno. H. Markham Jr.
Witness; Geo. Vaughn
Dennis "
Jan. 26, 1952
C.S. 40/384

48

¼ CORNER SECTION BET. SECTION 7 - 8.

SEE ALSO #65

Found 1" Iron pipe.
14" Oak, N 9°E. 50.2 feet.
14" Oak, N 57°E. 43.6 feet. Badly damaged.
Scribe 14" Oak, N 68°E. 46.5 feet.

Geo. Wenderoth
Witness,
Fred Seymour
1951
C.S. 41/16