

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 3 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

63

Section corner to secs. 7 and 18 on West boundary of Township.  
Found 3 B. T. Stumps. (Some scribing visible).  
Set  $\frac{3}{4}$  inch I. Pipe.  
From which 2 new trees:  
7 inch Cedar, N. 58° 11' E., 42.7 feet.  
17 inch D. Fir, N. 38° 55' W., 80.4 feet.

64

West  $\frac{1}{4}$  corner to sec. 7.  
Corner set by proportional measurement.  
Set 1 inch Axle.  
From which new trees:  
8 inch D. Fir, S. 72° 58' E., 32.8 feet.  
14 inch Madrone, S. 2° 10' W., 94.0 feet.

65

$\frac{1}{4}$  sec. corner to secs. 7 & 8. SEE ALSO # 48  
Found bent pipe and 3 B. T.s. (See prior renewal).  
Set 1 inch I. Pipe at corner. (Beside old bent pipe).  
Old B. T. described as N 9° E., is actually N. 9° W.

66

$\frac{1}{4}$  sec. corner to secs. 7 & 18.  
Found Stone and 2 BTs. (Scribing visible).  
Marked new trees:  
12 inch D. Fir, N. 41° 30' W., 24.1 feet.

#221 REFERENCED FOR  
LOCATING - 3/5/59  
L. MENREAN - Doug  
Co. Surveyor  
see C.S. 59/30

67

Center  $\frac{1}{4}$  corner to section 7.  
Set at intersection of North - South and East - West centerlines.  
Set a  $1\frac{1}{2}$  inch iron pipe.  
From which new trees:  
15 inch Maple, N. 5° 00' W., 7.0 feet.  
9 inch Maple, S. 77° 50' E., 31.7 feet.

68

Closing corner to secs. 3 & 4. (N. Bdy. of Twp.)  
Found stone as described in records.  
From which:  
A Fir, 14 inches, N. 24° 15' E., 8.4 feet marked "CC S 3 & 4 B. T." - Old BT.  
A Fir, 16 inches, S. 39° 15' E., 22.1 feet marked "S 3 B. T." - Old B. T.  
A Fir, 10 inches, S. 52° 30' W., 43.3 feet marked "S 4 T3OS, R3W BT" - New BT.

69

Section corner to sections 3, 4, 9 & 10.  
Found two B.T.s - A Fir, 54 inches, N. 66° W., 37.0 feet. - Old B. T.  
A Fir, 30 inches, S. 83° 35' W., 61.7 feet. - Old B. T.  
Drove  $\frac{3}{4}$  inch by 30 inch iron rod in ground for corner.  
From which:  
A Fir, 20 inches, N. 85° 22' E., 34.8 feet marked "S 3 T3OS, R3W., B. T."  
Madrone, 12 inches, S. 56° E., 46.9 feet mkd. "S 10 T3OS, R3W., B. T."  
(New B.T.s)

70

Corner to Section 30, T3OS, R2W, & Secs. 25 & 36, T3OS, R3W.  
Found - BT. as recorded by Boyer, 1939. SEE C.S. 14/11 REN. # 26  
16", now 24" Fir N. 52° 45' W. 23.0 ft.  
Orig. 11", now 20" Cedar N. 67 $\frac{1}{2}$ ° E. 17.8 ft.  
Both BT's. have good scribing & are alive & in good condition.  
Set Brass Cap Mkd.: County Surveyor's Office, 1958, T3OS R3W  $\frac{S25}{S36}$  | S30 R2W  
New BT.: 72" R. Fir bears N. 33° E. 14.5 ft. S30 T3OS R2W,  
CS BT, bark scribed.

Note - I find Closing Corner for  $\frac{S30}{R3W}$  |  $\frac{S30}{S31}$  R2W  
Pipe & BT's. O. K.

As recorded by  
Boyer, 1939.

Robert M. Thompson  
Feb. 11, 1956 - Apr. 1, 1956.  
C. S. File No. 42/173.

R. H. Gee, R. E. 3723.  
Joe Forrest  
Norman Walker  
Dec. 20 1955 and Feb. 16, 1956.  
C. S. File No. 42/193.

James W. Byron, Deputy  
M. Godfrey  
S. Billow  
May 7, 1958  
C. S. File No. 49/86