

Douglas County Surveyor's Record of
Government Corners Renewed

30

T. S.

3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

South $\frac{1}{4}$ Corner Section 34.

Det. by O.B.T. - 28" Maple bears S.66°E. 6.0 ft. dist, fd. scribe.
24" Fir bears N.54°W. 31.0 dist. O.B.T.

At Corner Point Set 1"x 30" Iron Pipe from which:

24" Maple bears N.77°E. 53.0 ft. dist. mkd. $\frac{1}{4}$ S34 BT.

18" W. Fir bears S.73°W. 16.0 ft. dist. mkd. $\frac{1}{4}$ S34 BT.

Sec. Cor $\frac{4}{3}$ T31S R3W bears West 441.5 ft. dist.

Stouts Creek bears East 520.0 ft.

Road bears East 590.0 ft.

71

Stomar Lumber Co.
John Markham, Jr.
Wit. R.G. Boyd
Sept. 1958
C.S. File No. 42/392

S. E. Corner Section 34.

As Det. by O.B.T.'s: 42" Fir bears N.74 $\frac{1}{2}$ °E. 45.2 ft. dist. O.B.T.

I remarked S35 B.T. Laurel Stump bears N.50°W. 4.6 ft. O.B.T.

10" La. Snag down, bears S.12°E. 22.0 ft. O.B.T., fd. scribe.

At Corner Point Set $\frac{3}{4}$ " x 24" Iron Pipe from which:

10" Fir bears N.69°E. 35.7 ft. dist. mkd S35 B.T.

7" La. bears N.79°W. 10.5 ft. dist. mkd. S34 T30S R3W B.T.

20" La. bears S.8°W. 22.5 ft. dist. mkd. S3 T31S R3W BT.

24" La. bears S.36°E. 18.0 ft. dist. mkd. S3 T31S R3W B.T.

Corner lies squarely on top of ridge.

South $\frac{1}{4}$ Corner Sec. 34 bears West 2564.0 ft.

Oct. 7, 1958

72

South $\frac{1}{4}$ Corner to Section 32.

as determined by O. B. T.

36" Fir bears N.71°E. 10.2 ft. O.B.T.

10" L. O. Stump bears S.15°W. 31.2 ft. O.B.T., fd. scribe.

At Corner Point Set 1 $\frac{1}{2}$ " x 30" Iron Pipe from which:

9" Laurel bears N.50°E. 52.0 ft. dist. mkd $\frac{1}{4}$ S32 X B.T.

10" Live Oak bears S.46°E. 41.0 ft. dist. mkd. $\frac{1}{4}$ S32 B.T.

23" Fir bears S.7°E. 38.0 ft. dist. mkd. $\frac{1}{4}$ S32 B.T.

Section Corner to Sections 5 & 6, bears West 167.0 ft.

73

John H. Markham, Jr.
For Stomar Lumber Co.
January 16, 1959
C. S. File
42/392

S. W. Corner Section 36.

As determined by O. B. T.'s:

11" Cedar N.56°E. 11.3 ft., fd. scribe O.B.T.

13" Cedar N.51°W. 12.0 ft. O. B.T.

At Corner Point Set $\frac{3}{4}$ " x 30" Iron Pipe from which:

14" La. S.80°E. 23.0 ft. mkd. S2 B.T.

12" La. N.77°E. 33.0 ft. mkd: S36 T30S R3W B.T.

10" Cedar N. 7°E. 44.4 ft. mkd: S36 B.T.

12" La. bears N.75°W. 44.4 ft. dist. Mkd: S35 T30S R3W B.T.

April 29, 1959

John H. Markham, Jr.
Witness: R. G. Boyd
For Stomar Lumber Co.
April 29, 1959
C. S. File No. 42/392

S. W. Corner Section 31, T30S R3W, & S. E. Cor. Sec. 36, T30S R4W, only.

As determined by O. B. T.'s.

13" Laurel bears S31°W. 26.4 ft. dist. O.B.T. fd. scribe

13" Laurel bears N.16°W. 33.0 ft. O.B.T., fd. scribe - I
remarked S36 T30S B.T.

24" Fir bears S.51°E. 29.7 ft. O.B.T. - I bark scribed
S31 T31S B.T.

At Corner Point Set 1" x 30" Iron Rod from which:

7" Chip bears N.43°W. 47.0 ft. dist. mkd: S36 R4W B.T.

30" Fir bears N.40°E. 17.0 ft. dist. mkd: S31 T30S B.T.

9" Laurel " N.80°E. 45.0 ft. dist. mkd: S31 T30S R3W B.T.

74

75

76

James W. Byron
Milo Godfrey
Olete Putnam
Feb. 4, 1960
C.S. File No. 49/86

Renew $\frac{S13}{R3W}$ T30S

$\frac{S24}{R2W}$

Found - Orig. 30", now 46", Fir Stump N.2°E. 5.3 ft. I open & find
good scribing "B".

Orig. N.W. BT., now down, shows good scar.

Set Brass Cap at Corner Mkd: County Surveyor's $\frac{S13}{R3W}$ T30S

Office, 1960 $\frac{S24}{R2W}$

New BT's: 18" Cedar bears N.74 $\frac{1}{2}$ °W. 88.0 ft. scribed S13 T30S R3W CS BT.

11" Cedar bears S.57°W. 101.4 ft. scribed S24 T30S R3W CS BT.

58
519
513
524