

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

X Section Corner to Sections 29 - 30 - 31 - 32.
as determined by O. B. T's.

24" Fir S.29°W. 63.0 ft. O.B.T.
30" Fir S.70°E. 12.9 ft. O.B.T., fd. scribe
30" Fir N.54°E. 16.2 ft. O.B.T.

At Corner Point Set 3" x 30" I. P. from which:

5" Chip. S.26°W. 38.0 ft. mkd. S31 R3W B.T.
12" La. N.44°W. 17.3 ft. mkd. S30 T30S R3W B.T.
12" La. N.10°E. 25.2 ft. mkd. S29 T30S R3W B.T.

RE-RENEWED CORNER NO. #233

84

John H. Markham, Jr.
For Stomar Lumber
Wit: R.G. Boyd
June 20, 1960
C.S. 42/392

1/4 Section Corner to Sections 2 and 3.

Found - Orig. 30", now 40" Fir Stump S.22 1/2°E. 20.3 ft. I
open & find good scribing "4".

Orig. 6", now 12" Chinquipin S.18°W. 4.3 ft.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

S3 / S2 T30S R3W

New BT's: 10" R.Fir bears N.41°E. 20.9 ft. scribed 1/4 S 2 CS BT.

Rescribe 12" Chinq. S.18°W. 4.3 ft. 1/4 S 3 CS BT.

RE-RENEWED CORNER NO. 194

85

Section Corner to Sections 3 - 2 - 10 - 11.

Found - Stake at Corner and three Original B. T's.:

8", now 24" Fir S.58 1/2°E. 18.5 ft., shows good scar,
I do not open.

Orig. 9", now 26" R.Fir N.31 1/2°W. 68.6 ft., shows good
scar, I do not open.

Orig. 8", Laurel, now 1" Stump, cut high, I open &
find good scribing "3" S.52°W. 25.2 ft. We
measure 23.2ft.

Original N. E. BT. not found.

Set Brass Cap alongside corner stake Mkd: County Surveyor's
Office, 1960

S 3 | S 2 T30S R3W
S10 | S11

New BT's: 12" R.Fir bears S. 8°W. 24.4 ft. scribed S10 T30S R3W CS BT.

17" R.Fir bears N.18°E. 6.5 ft. scribed S2 T30S R3W CS BT.

86

James W. Byron, Deputy
Kilo Godfrey
Glete Putnam
July 25, 1960
X.C.S. 49/47

Closing Corner Sections 2 and 3.

Found - All Orig. BT's, as recorded.

The S. E. BT. shows good scribing. All BT's. in good condtn.
Also find marked Stone at Corner.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

C C T29S R3W
S3 / S2 T30S

87

Corner to Sections 34 and 35 only, T. 29 S., R. 3 W.

Found - Both Orig. BT's. Orig. 24", now 40" Fir N.35°W. 46.2 ft.,
shows good scar.

Orig. 14", now 20" Laurel N.81°E. 19.8 ft. (record N.72°E)
shows good scribing "S35".

Also find Stone at Corner, notches not found. T29S

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

S34 | S35 R3W
T30S

Rescribe, now 20" Laurel N.81°E. 20.4 ft. T29S R3W S35. CS BT.

88

1/4 Section Corner to Sections 2 and 11.

Found - Corner Tree & Orig. S. W. BT. Corner tree previously
opened, shows good scribing "4".

Orig. 18", now 40" Fir B.T. S.41 1/2°W. 7.0 ft. shows
good scar. I do not open. Orig. S. E. not found.

Set Brass Cap at Corner & at West Edge of Corner Tree Mkd:

County Surveyor's 1/4 S 2 T30S R3W
Office, 1960 S11

Note - Corner Tree & BT. are good lumber trees so I mark

new BT's: 6" R.Fir bears N.30°W. 27.5 ft. scribed 1/4 S 2 CS BT.

6" R.Fir bears S.64° W.31.4 ft. scribed 1/4 S11 CS BT.

89