

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 3 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21081

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
August 18, 1960
C. S. File No. 49/47

Section Cor. Sec. 2 & 1, T30S R3W & Secs. 35-36, T29S R3W.
Found - Fir Tree, now 30", N.80°W. 27.7 ft., shows good scar, did not open.
Fir Tree, now 22", West 38.9 ft., shows good scar, old bark scribing above scar, did not open.
Fir Tree, now 18", S.35½°E. 30.4 ft., shows good scar, did not open.
Dead Fir Snag, 36", N.66°E. 41.6 ft., shows good scar. Fragments of very old bark scribing visible above scar. "S3" is all that is legible at present time, but traces of more fragmentary scribing also in evidence.

90

At Corner Set Iron Pipe with Brass Cap Mkd: County Surveyor's

T29S R3W	
S35	S36
S 2	S 1
T30S R3W	

Blaze & Scribe new Bearing Trees:

14" Fir N.29°E. 9.7 ft. Mkd. T29S R3W S36 CS BT.

No trace found of Orig. Chinquapin to S. E.

Corner lies on steep N. slope approximately ½ way from top of spur to draw.

Bruce A. Shaner
For National Plywood, Inc.
Wit. Wm. James & W. Griffin
August 16, 1960
C. S. File No. 51/105

¼ Section Corner to Sections 2 and 1.

91

Found - Laurel, dead snag(now 10") S.21°E. 4.0 ft., showing scribing "½S" in open blaze.

Fir Tree, (10") N.64°W. 5.6 ft., uprooted & down.

Opened & found scribing.

Corner Stone not found.

Set Iron Pipe with Brass Cap Mkd: County Surveyor's Office, 1960

T30S R3W ¼ S2/S1

Blaze & Scribe new Bearing Trees:

8" Fir S.23°W. 22.0 ft., mkd; ¼ S2 CS BT.

10" Fir S.59°E. 32.8 ft., mkd; ¼ S1 CS BT.

Corner lies on very steep North slope about 1 chain South of small creek.

¼ Section Corner common to Sections 14 and 15.

92

Orig - A Stone, now missing, 12"x12"x5" 9" in a mound of stone, with "½" on W. face, from which a:

34" Hemlock, now dead & down, but with the scribes "½S" visible on it, bears N.37°W., 52½ lks.

15" Alder, now missing, bears S.30½°E. 10A lks. 200

Rstrd- Set a Brass Rod, 5/8" x 27", in the proper position for the ¼ corner and from which a:

12" Yew, newly scribed "½S BT", bears N28½°W., 27.5 feet.

8" Heml., " " "½S BT", bears N.50°E., 4.0 feet.

D. Fir, 72", a line tree as described by the Surveyor General, bore South 1.65 chains (108.9 ft). This tree was logged a year or so ago & only the stump remains, but Wm. James & J. B. Griffin identified the line tree and the corner, prior to the line tree's being cut.

Section Corner to Sections 14-15-22-23, as det. by O.B.T's:

93

30" Fir Snag S.10°E. 19.8 ft. O.B.T., fd. scribe.

38" Fir Snag N.45°W. 19.2 ft. O.B.T., fd. scribe.

14" Fir Snag S.50°W. 48.8 ft. O.B.T., fd. scribe.

At Corner Point found Stone & Set ¾" x 30" I. R. from which:

14" Fir bears S.24°W. 55.6 ft. mkd. S22 R3W X BT. #213

3" Fir S.18°W. 15.9 ft. mkd. S22 B.T.

3" Fir S.58°W. 7.6 ft. mkd. S22 B.T.

2" Fir N.74°E. 6.3 ft. mkd. S14 B.T.

John H. Markham, Jr.
For Stomar Lumber Co.
Sept. 15, 1960
C. S. File No. 42/392

¼ Section Corner to Sections 22 and 27, as det. by O.B.T's:

94

18" Fir S.35°E. 22.0 ft. O.B.T.

30" Fir Stump, logged, N.65°E. 20.0 ft., O.B.T.

At Corner Point Set ¾" x 30" I.P. from which:

40" Fir S.35°E. 32.0 ft. mkd. ¼ S27 B.T.

32" Fir S.47°E. 38.0 ft. mkd. ¼ S27 B.T.

16" Hemlock N.29°E. 53.0 ft. mkd. ¼ S22 B.T.

Road bears East 510.0 ft.

Mar. 1968 - P.D.O.K. c.s. 54/52