

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO. EUGENE, ORE. 21881

Byron &  
Crew  
C.S. 52/126

*FOA 10-92 BY LANG M117-2*

1/4 Corner to Sec. 5, T30-3W. & Sec. 32, T29-3W.  
Found - 3/4" I. Bolt at corner & both BT's. as recorded. Each shows good bark scribing.  
New BT: 10" Cedar bears N.19°E. 18.4 ft. scribed 1/4 S32 CS BT.  
Nov. 26, 1962

101

West 1/4 Corner to Section 6 only, T30-2W.  
Found - Orig. Corner Tree & Both Orig. BT's., each shows good scars and check O. K.  
Set - Brass Cap at Corner along East Edge of Corner Tree and Mkd: County Surveyor's Office 1962 West 1/4 S6 T30S R2W  
New BT: 7" R.Fir bears S.38°E. 41.9 ft. scribed 1/4 S6 CS BT.

102

East 1/4 Corner Section 1 only, T30-3W.  
Found - Both Orig. BT's. Orig. S.W. BT. shows good scribing.  
New BT: 7" R.Fir bears S.51°W. 15.0 ft. scribed 1/4 S1 CS BT.

103

Renew 

S 1	S 6
R3W	R2W

 T30S

Found - Orig. 10"; now down, 14" Fir S.68°W. 23.8 ft., shows scribing. No other Orig. BT's. found. Do find shattered Stone at Corner.  
Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1962  
New BT's: 9" Fir bears S.77°W. 13.9 ft. scribed S1 T30S R3W CS BT.  
10" Hemlock bears N.78° E. 33.6 ft. scribed S6 T30S R2W CS BT.

104

South 1/4 Corner Section 34, T29-3W.  
Found - Both BT's. & Corner Tree as recorded. Corner Tree & N.W. BT. are good log trees and could now be cut.  
Set - Brass Cap 4.0 ft. North of Center of Cor. Tree & Mkd: County Surveyor's Office, 1962 Wit. Cor. 4' South to S 1/4 S34 T29S R3W.  
New BT: 14" R.Fir bears N.31°W. 54.5 ft. scribed W.C. 1/4 S34 CS BT.  
Orig., now 26", Cedar bears S.30°E. 39.3 ft., shows good scar.

105

S. E. Corner Section 36, T29-3W.  
Found - Both Orig. BT's. & Corner Tree., all as recorded.  
Orig. 15", now 20" Fir N.45°W. 2.6 ft., shows good scar, face may be rotted. I rescribe this B.T. S36 T29S R3W CS BT.

106

Renewed 1857 Gov't. Corner set 20 chains East of Sec. Cor. 

32	33
55	4

 T29S R3W  
Found - Orig. 36", now 40" Dead Fir N.25°E. 4.6 ft., shows old bark scribing above newer bark scribe. Also shows good scar near base which is typical of Hathorne's work.  
Also find 1" I.P. at Corner. Orig. S.W. BT. not found.  
New BT's: 18" R.Fir bears S.16°E. 27.2 ft. scribed S4 T30S R3W CS BT.  
8" R.Fir bears East 38.4 ft. scribed S33 T29S R3W CS BT.

107

1/4 Corner to Sections 11 and 12.  
Found - Rock at Corner & S.W. BT., shows good scar. Stump of Orig. N.E. BT. Rock & BT's. check record.  
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's Office, 1963  
1/4 S11/S12 T30S R3W  
New BT: 12" R.Fir bears N.16°E. 22.5 ft. scribed 1/4 S12 CS BT.

108

Section Corner to Sections 1 - 2 - 11 - 12.  
Found - All Orig. BT's. All check record & show scars.  
Set - Brass Cap at Cor. & Mkd: County Surveyor's Office, 1963 

S 2	S 1
S11	S12

 T30S R3W  
New BT's: 13" R.Fir bears S.45°W. 8.4 ft. scribed S11 T30S R3W CS BT.  
12" R.Fir bears South 19.1 ft. scribed S12 T30S R3W CS BT.  
14" R.Fir bears N.88°E. 14.2 ft. scribed S1 T30S R3W CS BT.  
10" R.Fir bears N.86°W. 40.3 ft. scribed S2 T30S R3W CS BT.

109

James W. Byron, Deputy County Surveyor  
Mike Darby and Wm. Stoffel  
December 1962 and January 1963  
C. S. File No. 52/126

James W. Byron, Deputy  
M. Darby and Wm. Stoffel  
Jan. 1963  
C.S. File No. 52/138

*FO: ok 11/89  
H. Johnson  
M 97-15*