

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

110

Section Corner to Sections 20 - 21 - 28 - 29.  
Found - 1/2" I.P. at corner & all BT's. as recorded by Markham, 1952.  
Rescribed - 12" Laurel S.41°W. 5.0 ft. S29 T30S R3W CS BT.  
All other BT's. O.K. - See Corner No. 45, Markham's corner.

FDOK 4/86  
RUPPERT  
C.S. 6/3/36

1/4 Corner to Sections 1 and 12.  
Found - Stone at Corner. Orig. 28" now 34" Fir N.25 1/4°E. 44.9 ft.,  
shows good scar. Orig. 8" BT., now down, shows scribing.  
Set - Brass Cap alongside Cor. Stone Mkd: County Surveyor's 1/4 S 1 T30S  
Office, 1963 SL2 R3W  
New BT: 8" Fir N.33°E. 21.0 ft. scribed 1/4 S1 CS BT.

RE-RENEWED, SEE CORNER NO. #224 111

112

1/4 Corner to Sections 28 and 27.  
Found - Both BT's. as recorded by Germond, open S.E. BT. & find good  
scribe marks. We do not find Stone at Corner. - REN. #2  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963  
1/4 S28/S27 T30S R3W  
New BT's: 7" Fir bears N.37°W. 23.0 ft. scribed 1/4 S28 CS BT.  
Rescribe, now 20" Maple S.30°E. 32.4 ft. 1/4 S27 CS BT.

FD OK  
Wm. P. RUPPERT  
7/18/64  
M 97-218

113

1/4 Corner to Sections 21 and 28.  
Found - Stone at Corner & Orig. S.W. BT. & both BT's. as recorded  
See Renewed Corner No 44 - - - - - by Markham.  
Do not find Pipe at Corner.  
Set - Brass Cap alongside Cor. Stone Mkd: County Surveyor's 1/4 S21 T30S  
Office, 1963 S28 R3W  
No New Bearing Trees Scribed.

James W. Byron, Deputy County Surveyor  
Mike Darby and Wm. Stoffel  
January 1963  
C. S. File No. 52/138

114

Corner to Secs. 1 & 12, T30-3W & Secs. 6 & 7, T30-2W.  
Found - All Orig. BT's. All check record. S.W. BT. shows scribing.  
N. W. BT. down.  
Set - Brass Cap at Cor. & at hub with tack, set recently.  
Marked Cap: County Surveyor's S 1 | S 6  
R3W SL2 | S 7 R2W T30S  
New BT's: 9" Fir bears N. 4°W. 14.2 ft. scribed S1 T30S R3W CS BT.  
12" Chinquapin bears N.30°E. 4.4 ft. scribed T30S R2W S6 CS BT.

115

1/4 Corner to Sec. 12, T30-3W & Sec. 7, T30-2W.  
Found - Both Orig. BT's. Orig. 11", now 30" Fir N.2 1/2°E. 50.2 ft., shows  
good scribing, previously opened.  
Orig. S.W. BT. shows good scar. BT's. check record. T30S  
Set - Brass Cap at Cor. Mkd: County Surveyor's 1/4 R3W SL2/S 7 R2W  
Office, 1963  
New BT's: 16" R.Fir bears S.46 1/2°E. 28.4 ft. scribed 1/4 S7 CS BT.  
20" R.Fir bears N.28°W. 18.5 ft. scribed 1/4 S12 CS BT.

116

Corner to Sections 12 & 13, T30-3W.  
Found - 1 1/4" I.P. at corner & both Orig. BT's. Check Record. R3W 12 | T30S  
13 | R2W  
Orig. S.W. BT., previously opened, face rotted.  
Orig. N.W. BT. shows scar.  
New BT: 20" Cedar bears S.49°W.17.6 ft. scribed S13 T30S R3W CS BT.

FDOK R. GEISLER  
5/86, M100-78

117

Corner to Sections 7 & 18, T30-2W, Closing Corner.  
Found - Orig. 12", now down 22" Fir, S.52°E. 9.3 ft.,  
shows good scribing. R3W | S 7 | T30S  
| S18 R2W  
Orig. N.W. BT., not found. Corner Stone not found.  
Set - Brass Cap at Cor. Mkd: County Surveyor R3W | S 7 | C.S. T30S  
Office, 1963 | S18 R2W  
New BT's: 7" R.Fir S.62°E. 48.0 ft. Scribed CC S18 CS BT.  
7" Cedar N.54°E. scribed CC S 7 CS BT.