

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy County Surveyor  
Mike Darby and Bill Stoffel  
January 1963  
C. S. File No. 52/138

Section Corner to Sections 22 - 23 - 26 - 27. 118  
Found - Orig. 24", now 40" Fir Snag S.20°W. 59.4 ft., shows good scribing on old face. No other BT's. found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R3W 

S22	S23
S27	S26

  
Office, 1963  
New BT's: 20" R.Fir bears S.39°E. 45.0 ft. scribed S26 T30S R3W CS BT.  
17" Cedar bears S.7°W. 54.8 ft. scribed S27 T30S R3W CS BT.  
19" Cedar bears N.58°E. 100.0 ft. scribed S23 T30S R3W CS BT.  
No trees near to N.W.

-----

1/4 Corner to Sections 10 and 15. 119  
Found - Stump Section of N.W. BT. & Orig. 14", now 18" Fir Snag, shows good scribing on old face. Corner Stone not found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R3W 

S10	S15
-----	-----

  
Office, 1963  
New BT's: 24" Laurel bears S.59°W. 53.2 ft. scribed 1/4 S15 CS BT.  
16" Laurel bears N.73°W. 65.5 ft. scribed 1/4 S10 CS BT.

-----

Section Corner to Sections 10 - 11 - 14 - 15. 120  
Found - Stone at Cor. as recorded. Orig. 18", now 26" Fir S.40°E. 64.0 ft., shows good scar. Orig. 7", now 18" Fir Stump N.16°E. 15.8 ft., shows scar. Orig. 18", now 30" Cedar N.28 1/2°W. 33.0 ft., down., shows scar. Orig. SW. BT. not found.  
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's 

S10	S11	T30S
S15	S14	R3W

  
Office, 1963  
New BT's: 12" R.Fir bears S.66°W. 14.7 ft. scribed S15 T30S R3W CS BT.  
10" R.Fir bears N.85 1/2°W. 36.3 ft. scribed S10 T30S R3W CS BT.  
18" Maple bears N.30°E. 20.6 ft. scribed S11 T30S R3W CS BT.

-----

1/4 Corner to Sections 19 and 20. 121  
Found - 1 1/2" I.Pipe, See renewal #50.  
14" Fir S.27°E. 35ft. Ok. (Scar)  
10" Laurel West. 34 feet, dead. (Scribed)  
New BT: 5" Fir S.76°W. 20.2 ft. scribed 1/4 S19 CS BT.

-----

Section Corner to Sections 16 - 17 - 20 - 21. 122  
Found - 1" I.Pipe & 12" Maple S.49°W. 43.0 ft., O.K. - REN #52  
12" Maple S.49°W. 43.0 ft., O.K.  
5" Chinquapin S.53°W. 85 ft., down.  
23" Laurel N.66°E. 53.0 ft., O.K.  
36" Fir N.66°W. 111.0 ft., O.K.  
New BT: 26" Cedar S.82°E. 89.8 ft. scribed S21 T30S R3W CS BT.

-----

1/4 Corner to Sections 20 and 21. 123  
Found - 1" I.Pipe at Cor. & Both BT's. as recorded by Markham. REN #46  
N.E. BT., now down, We rescribe SW. BT. 1/4 S20 CS BT.  
New BT: 10" Laurel N.56°E. 31.0 ft. 1/4 S21 CS BT.  
Orig. 12" Fir S.15°W. 28.0 ft. is OK.

-----

Section Corner to Sections 21 - 22 - 27 - 28. 124  
Found - Orig., now 20" R.Fir S.60°E. 65.4 ft., shows good scribing. Do not find evidence of other Orig. BT's.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R3W 

S21	S22
S28	S27

  
Office, 1963  
New BT's: 6" Fir bears N.41°W. 20.5 ft. scribed S21 CS BT.  
9" Fir bears S.71°W. 9.1 ft. scribed S28 CS BT.  
18" Laurel bears N.70°E. 4.8 ft. scribed S22 T30S R3W CS BT.