

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 S. T. S. R. 3 W. R. W. W. M.

KOBE-CHARMAN CO., EUGENE, ORE. 97101

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
February 1963
C. S. File No. 52/138

147
1/4 Corner to Sections 8 and 17.
Found - Orig. 5", now 17" R. Fir S. 51° E. 20.2 ft. We open & find good scribing "S". Orig. 7", now 14" Fir N. 62 1/2° E. 19.8 ft., down.
Set - Brass Cap at Cor Mkd: County Surveyor's 1/4 S 8 T30S R3W Office, 1963 S17
New BT's: Rescribe, now 17" R. Fir S. 51° E. 20.2 ft. 1/4 S17 CS BT.
10" R. Fir bears N. 43° W. scribed 1/4 S8 CS BT.

148
1/4 Corner to Sections 24 and 25.
Found - 1 1/4" I.P. at cor. & now 14" Pine Stump S. 50° E. 25.7 ft., shows good scribing "BT". N.E. BT. not found. REN #24
Set - Brass Cap alongside Cor. Pipe & Mkd: County Surveyor's 1/4 S24 T30SR3W Office, 1963 S25
New BT's: 17" Cedar bears N. 86° W. 77.7 ft. scribed 1/4 S24 CS BT.
14" Laurel bears S. 73° E. 44.0 ft. scribed 1/4 S25 CS BT.
Note - Corner is on steep south slope and about 75 ft. N. of toe of slope.

149
Section Corner to Sections 27 - 28 - 33 - 34. SERIBED POST
Found - Axle Flush & 1.0 ft. south of scribed Yewood Post. REN #27
Fences Thus:
RE-RENEWED, SEE CORNER NO. #227
E State Hwy. 227
New BT: 10" W. Oak bears N. 9° E. 40.0 ft. scribed S27 T30S R3W CS BT.
No other trees near. MAR. 1968 - FOUND O.K. C.S. 54/52

150
Section Corner to Sections 9 - 10 - 15 - 16.
Found - Orig. 14", now 14" Fir S. 20 1/2° W. 50.2 ft., shows scribing.
Orig. 14", now 24" Fir N. 60° E. 9.6 ft., shows scar.
Line Tree 6.0 ft. N. of cor., as recorded.
Orig. 7", now 7" Laurel S. 10 1/2° E. 21.8 ft., shows scars.
Orig. N.W. BT. not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's S 9 | S10 T30S R3W Office, 1963 S16 | S15
New BT's: Rescribe, now 7" Laurel S. 10° E. 21.5 ft. S15 CS BT.
Rescribe, now 24" Fir N. 61° E. 10.0 ft. S10 T30S R3W CS BT.
22" R. Fir bears S. 11° W. 51.2 ft. Scribed S16 T30S R3W CS BT.
36" R. Fir bears North 5.5 ft. scribed S9 T30S R3W CS BT.

151
1/4 Corner to Sections 18 and 17. #238
Found - 1" I.P. at Cor. & BT. as recorded, shows good scribing on stump sec. REN #57B-A
New BT: 6" R. Fir bears N. 19° E. 17.7 ft. scribed 1/4 S17 CS BT.

152
Witness Corner to Sections 17 and 18.
Found - Stump of Corner Tree, shows scribing. - REN #57B
Orig. 18", now 30" Fir Stump S15° W., not S. 30° W. 27.7 ft., shows scrb.
Orig. 15", now 30" Fir Stump S. 28° E. 12.5 ft., not S. 40° E. shows scar.
Set - Brass Cap 3.0 ft. South of Ctr. of Cor. Tree & Mkd: W.C. S18/S17 County Surveyor's Office, 1963. T30S R3W
New BT's: 4" R. Fir bears S. 38° E. 4.0 ft. scribed W.C. S17 CS BT.
5" R. Fir bears N. 77° W. 19.0 ft. scribed W.C. S18 CS BT.

153
Section Corner to Sections 23 - 24 - 25 - 26.
Found - N.W. & S.W. BT's., as recorded by Richardson, 1937, except N.W. BT., down, & SW. BT. has burned face. No scribing found.
N.W. BT. is face down. No trace of N.E. BT. REN #25
Set - Brass Cap at Cor. Mkd: County Surveyor's S23 | S24 T30S R3W Office, 1963 S26 | S25
Note - Corner is at East Edge of old road & about 8' W. of field fence.
New BT's: 16" Dbl. Cedar bears N. 11° E. 62.0 ft. scribed S24 T30S R3W CS BT.
12" Laurel bears N. 69° W. 20.1 ft. scribed S23 T30S R3W CS BT.
8" Cedar bears S. 28 1/2° W. 93.4 ft. scribed S26 T30S R3W CS BT.