

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 3 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Renewed R4W R3W
S 36/S 31 T30S
S 1 T31S

168

Found - 1" I. Bar at corner & BT's. as recorded by Markham, 1959. ~~Ren. #75~~
Orig., now 13" Laurel N.16°W. 33.0 ft., bark scribed, We
rescribe (wood) T30S R4W S36 CS BT.
Chinquapin to Northwest now dead.

Corner to Sections 25 and 36 only, T30-4W.

Found - Both Orig. BT's. Orig. 12", now 24" Fir S.48°W. 21.7 ft.,
shows old scars and good bark scribing (not old)
Orig. 8", now 12" Fir Stump section N.46½°W. 22.4 ft., shows old axe work.

169

Set - Brass Cap at Cor. Mkd: County Surveyor's R4W S25 R3W T30S
Office, 1963 S36

New BT: 14" R. Fir bears N.1°W. 40.8 ft. scribed S25 T30S R4W CS BT.

RE-RENEWED, SEE CORNER NO. #220

170

Closing Corner Sections 1 and 6, closing on S. line T30S.

Found - Orig. 14", now 24" Maple S.67°W. 42.5 ft., shows good scribing.
Orig. 36", now 40" Fir S.55½°E. 22.6 ft., shows scribing.
We also find Orig. N.E. BT. shows scar. Find Corner Stone as recorded.

Set - Brass Cap alongside Cor. Stone & Mkd: County CC T30S
Surveyor Office, 1963 R4W S 1 / S 6 R3W T31S

Rescribe now 24" Maple T31S S.67°W. 43.0 ft. S1 CS BT. CC.

171

South ¼ Corner to Section 31 only.

Found - Both Orig. BT's. & Stone. All as recorded. **GOOD CORNER** ~~SHOULD'N'T BE MKD. OUT.~~
Orig. 10", now 18" Fir S.58°W. 18.1 ft., shows good scar.
Orig. 11", now 16" Fir N.56°E. 9.5 ft., shows good scribing.

Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's
Office, 1963 S ¼ S31 T30S R3W.

No New Bearing Trees scribed.

172

¼ Corner to Sections 34 and 35.

Found - 1½" I.P. & mound of Rocks at Corner & SW. BT. as recorded. ~~Cor. #62~~
BT., now 14" Fir, down, bears N.52°E. 16.0 ft. scribed by
Templin.

New BT: 12" Cedar bears S.88°E. 19.2 ft. scribed ¼ S35 CS BT.

FD OK
8/1/89
H. JOHNSONE
M 95-6

173

Center ¼ Section 28

Set 3/8 x 1½" iron bar
Blaze & Scribe 2 BT's.
26" Fir N 4° E. 7.2 feet.
18" Fir N 66° W, 25.1 feet.

FD OK 11/89
H. JOHNSONE
M 101-64

FD OK
By M. Heimbarger
for Negherber
June 1994
M 120-22

174

Center ¼ corner Section 30

Stone
10" Fir N 10° W 58 lks.
14" Fir N 40° W 185 lks.

RE-RENEWED, SEE CORNER NO. #241

175

¼ Corner to Sections 16 & 17.

Found - Stake at corner.
10" Cedar (now 22" snag) N. 88½° W 16.5 ft. Chopped open
found scribing "1/8".
6" Chinq. N 78° E. 17.2 ft. Not found

Set - Brass cap mkd: Douglas County Surveyor's Office 1964
T. 30 SR 3 W. ¼ S17/S16"

New BTS: 6" Fir N 77° W 22.0 ft. Mkd: ¼ S 17 CS BT.
12" R. Cedar N 18° E 65.2 ft. Mkd: ¼ S 18 CS BT.

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
March 1963
C. S. File No. 52/138

Arthur R. Evans
April, 1953
C.S. 41/172

Arthur Boyer
April 3, 1937
C.S. 30/11

Wilo Godfrey, Deputy
Wm. Stoffel, Mike Darby
Mike Stone
June, 1964
C. S. File No. 52/138